Time-Sensitive Networking (TSN) for Deterministic Industrial Communication

Deepak Srivastav[1], Rajan Bhatiya[2]
Associate Professor[1], Assistant Professor[2]
Department of ECE
Mahakal Institute of Engineering and Technology
Email ID: *Deepaksrivasta1v@yahoo.com[1], bhatiayraj6aan@gmail.com[2]*

ABSTRACT

Time-Sensitive Networking (TSN) is emerging as a key enabler for deterministic communication in modern industrial networks. With the growth of Industry 4.0 and the Industrial Internet of Things (IIoT), traditional Ethernet networks fall short in meeting strict timing, reliability, and synchronization requirements. TSN extends standard Ethernet with mechanisms such as time-aware scheduling, traffic shaping, and frame preemption to guarantee low latency and high reliability for critical industrial applications. This paper presents a comprehensive review of TSN technologies, its architecture, key standards, industrial applications, performance analysis, challenges, and future research directions. The study aims to provide insights for researchers and practitioners on adopting TSN in real-time industrial communication systems.

KEYWORDS: *Time-Sensitive Networking (TSN), Deterministic Communication, Industrial Ethernet, Industry 4.0, IIoT, Low Latency, Traffic Scheduling, Real-Time Systems*

INTRODUCTION

The evolution of industrial automation towards Industry 4.0 has significantly increased the demand for reliable and deterministic communication networks. Traditional industrial communication protocols such as PROFINET, EtherCAT, and Modbus have provided deterministic performance but are limited in scalability, interoperability, and integration with IT networks. Ethernet, being widely adopted in IT, offers high bandwidth and scalability but

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

lacks deterministic behavior.

Time-Sensitive Networking (TSN) is a suite of IEEE 802.1 standards designed to provide deterministic capabilities over standard Ethernet. TSN ensures bounded low-latency, minimal jitter, and high reliability, making it suitable for safety-critical and real-time industrial applications such as motion control, robotics, autonomous vehicles, and process automation. This paper aims to explore TSN architecture, standards, and its role in deterministic industrial communication while addressing challenges and future trends.

BACKGROUND AND MOTIVATION

Industrial automation and control systems rely heavily on robust communication networks to ensure smooth and safe operation. The growth of Industry 4.0 and the increasing integration of information technology (IT) with operational technology (OT) have created a need for networks that not only handle large amounts of data but also guarantee real-time performance. Traditional Ethernet networks, although widely used in IT systems, fall short in meeting the strict requirements of industrial environments. This section explains the communication requirements of industrial networks and the motivation for adopting Time-Sensitive Networking (TSN).

1. Industrial Communication Requirements

Industrial networks have unique demands that differ significantly from conventional office or data center networks. Key requirements include:

- **Low Latency:**

In industrial systems, certain operations are time-critical. For instance, in motion control applications, commands from a controller to a motor must be delivered within microseconds to avoid misalignment or collisions. High latency can disrupt control loops, leading to reduced production efficiency or even damage to machinery.

- **Minimal Jitter:**

Jitter refers to the variability in packet delivery time. Even if average latency is low, inconsistent delays can cause synchronization issues between devices such as sensors, actuators, and controllers. For example, robotic arms working in tandem on an assembly line require precise timing to avoid collisions and maintain throughput.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- **High Reliability:**

Industrial networks must operate continuously without packet loss or errors. In manufacturing, missed or corrupted messages can halt production, trigger costly downtime, or compromise worker safety. Networks must therefore provide mechanisms for error detection, retransmission, and redundancy.

- **Scalability:**

Modern factories incorporate hundreds or even thousands of interconnected devices, including sensors, actuators, controllers, and human-machine interfaces (HMIs). The network must accommodate this growth without a drop in performance or reliability.

Traditional Ethernet protocols, based on asynchronous communication and Carrier Sense Multiple Access with Collision Detection (CSMA/CD), cannot meet these requirements reliably. Collisions, unpredictable delays, and the lack of guaranteed delivery make standard Ethernet unsuitable for deterministic industrial applications.

2. Motivation for TSN

Time-Sensitive Networking (TSN) is a set of IEEE 802.1 standards that extend standard Ethernet to support deterministic and low-latency communication required by industrial automation. The key motivations for adopting TSN include:

- **Integration of OT and IT Networks:**

Traditionally, OT networks (used in factories, power plants, and critical infrastructure) were separate from IT networks (used for data analytics, ERP systems, and cloud computing). TSN enables a unified network infrastructure that supports both real-time control traffic and General IT traffic without compromising timing requirements.

- **Converged Networks for Multiple Applications:**

With TSN, a single physical network can carry multiple types of traffic—such as control commands, video surveillance streams, sensor data, and enterprise IT traffic—while guaranteeing timing and priority for critical flows. This reduces network complexity and cabling requirements.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- **Deterministic Performance over Standard Ethernet Hardware:**

TSN introduces scheduling mechanisms, traffic shaping, and time synchronization to Ethernet, making it deterministic. This allows industrial networks to meet stringent latency and reliability requirements using widely available Ethernet hardware rather than expensive proprietary solutions.

- **Cost Reduction and Flexibility:**

By using standard Ethernet devices with TSN features, industries can reduce capital expenditure, simplify maintenance, and future-proof their infrastructure. TSN also supports interoperability between devices from different vendors, promoting a more competitive ecosystem.

In summary, the industrial push toward smart factories, digital twins, and IIoT (Industrial Internet of Things) creates a strong demand for deterministic, reliable, and scalable networks. TSN addresses this demand by combining the universality of Ethernet with the strict timing and reliability requirements of industrial applications, making it a key enabler for modern automation and control systems.

OVERVIEW OF TIME-SENSITIVE NETWORKING (TSN)

Time-Sensitive Networking (TSN) is an evolution of the IEEE 802.1 Ethernet standard, designed specifically to support deterministic, low-latency, and high-reliability communication over standard Ethernet networks. Unlike traditional Ethernet, which is non-deterministic due to its collision-based access methods, TSN introduces a collection of standards that provide mechanisms for precise time synchronization, traffic scheduling, and resource reservation. TSN is particularly suitable for industrial automation, automotive systems, robotics, and other real-time applications where predictable network behavior is critical.

TSN ARCHITECTURE

The architecture of TSN is designed to support deterministic communication across complex networks while maintaining compatibility with standard Ethernet infrastructure. The main components of a TSN-enabled network include:

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

1. End Devices (Nodes)

End devices, also referred to as network nodes, are the sources and sinks of network traffic in a TSN network. Examples include:

- **Industrial Controllers:** Programmable logic controllers (PLCs), motion controllers, and distributed control systems (DCS) that generate control commands and receive status feedback.
- **Sensors:** Devices that monitor temperature, pressure, vibration, or other physical parameters and send periodic or event-driven data to controllers.
- **Actuators:** Motors, valves, or robotic devices that respond to control commands with precise timing.

End devices in a TSN network must support time synchronization and traffic shaping features to ensure their data flows adhere to deterministic schedules.

2. Bridges and Switches

TSN bridges or switches form the backbone of the network. Unlike standard Ethernet switches, TSN bridges implement specialized mechanisms to guarantee deterministic behavior:

- **Time-Aware Shapers (TAS):** These schedule outgoing frames based on a global time reference, ensuring that high-priority traffic is transmitted at precise intervals.
- **Frame Preemption:** This mechanism allows critical frames to interrupt lower-priority frames, reducing worst-case latency for time-sensitive traffic.
- **Traffic Scheduling:** Supports multiple traffic classes (e.g., scheduled, best-effort, and reserved traffic) to prevent interference and guarantee delivery.

TSN bridges maintain the timing integrity of the network, ensuring that messages are delivered predictably even under high network load.

3. Time Synchronization Mechanism

A key requirement for deterministic networking is that all devices in the network share a common notion of time. TSN employs precise time synchronization mechanisms to align clocks across all nodes and bridges:

- **IEEE 802.1AS:** This standard defines a precision time protocol (PTP) optimized for Ethernet networks. It enables sub-microsecond synchronization between devices.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- **Global Time Reference:** Each device maintains its clock, which is regularly synchronized with a master clock in the network. This common time base is critical for time-aware traffic scheduling and coordinated operations in industrial systems.

Accurate time synchronization allows TSN networks to enforce strict timing constraints, minimize jitter, and ensure coordinated actions among distributed devices, such as synchronized robotic movements or collision-free conveyor operations.

4. Optional TSN Enhancements

TSN also provides additional mechanisms to enhance reliability and performance:

- **Redundancy Protocols:** Techniques like Frame Replication and Elimination for Reliability (FRER) ensure fault-tolerant communication by sending duplicate frames along different network paths.
- **Bandwidth Reservation:** Guarantees that critical flows have reserved network resources to prevent congestion.
- **Path Control and Packet Sequencing:** Ensures that time-sensitive frames take pre-determined paths and arrive in the correct order.




Figure 1: TSN Network Architecture

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

KEY TSN STANDARDS

Time-Sensitive Networking (TSN) is not a single protocol but a collection of IEEE 802.1 standards, each addressing a specific aspect of deterministic Ethernet. These standards collectively enable low-latency, high-reliability, and synchronized communication over standard Ethernet. Understanding these key standards is critical for designing TSN networks in industrial automation, automotive, and other real-time applications.

1. IEEE 802.1AS – Timing and Synchronization

- **Purpose:** Provides a precise timing and synchronization protocol for Ethernet networks.
- **Mechanism:** Based on the Precision Time Protocol (PTP), 802.1AS allows all nodes in the network to maintain a shared global clock with sub-microsecond accuracy.
- **Importance:** Accurate time synchronization is foundational for deterministic communication, as it enables time-aware scheduling of messages and coordination between distributed devices such as robotic arms or coordinated conveyor systems.

2. IEEE 802.1Qbv – Time-Aware Shaper (TAS)

- **Purpose:** Defines scheduling rules for transmitting Ethernet frames based on a synchronized network clock.
- **Mechanism:** Frames are queued and transmitted only at predefined time windows, preventing contention with other traffic.
- **Importance:** Ensures predictable low-latency delivery for critical control messages while allowing non-critical traffic to share the same network infrastructure.

3. IEEE 802.1Qbu and 802.3br – Frame Preemption

- **Purpose:** Reduces transmission delays for high-priority frames by allowing them to interrupt ongoing lower-priority frame transmission.
- **Mechanism:** Lower-priority frames are paused, the high-priority frame is sent immediately, and the lower-priority frame resumes afterward.
- **Importance:** Minimizes worst-case latency for time-sensitive traffic, making TSN suitable for fast control loops in industrial systems.

4. IEEE 802.1Qci – Per-Stream Filtering and Policing (PSFP)

- **Purpose:** Provides traffic policing and filtering for individual streams.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- **Mechanism:** Limits bandwidth usage, prevents misbehaving devices from affecting network performance, and drops or reshapes frames that exceed allocated resources.
- **Importance:** Enhances reliability and ensures that critical streams maintain their deterministic properties even in congested networks.

Table 1: TSN encompasses several IEEE standards, including:

Standard	Description
IEEE 802.1AS	Time synchronization across the network (gPTP)
IEEE 802.1Qbv	Time-aware scheduling for deterministic traffic
IEEE 802.1Qci	Per-stream filtering and policing
IEEE 802.1Qbu	Frame preemption to reduce latency
IEEE 802.1CB	Frame replication and elimination for reliability
IEEE 802.1Qcc	Stream reservation and management

These standards collectively enable bounded latency, precise synchronization, and fault-tolerant communication.

DETERMINISTIC MECHANISMS IN TSN

1. Time Synchronization (IEEE 802.1AS)

Precise synchronization is essential for deterministic communication. TSN uses the generalized Precision Time Protocol (gPTP) to synchronize clocks across all nodes with sub-microsecond accuracy. This allows coordinated scheduling and time-sensitive transmission of messages.

2. Time-Aware Shaping (IEEE 802.1Qbv)

Time-aware shapers schedule traffic according to time slots, ensuring high-priority traffic is transmitted without interference. Figure 2 illustrates how time-aware shaping prevents collisions in scheduled windows:

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved




Figure 2: Time-Aware Shaping Concept

3. Frame Preemption (IEEE 802.1Qbu)

Frame preemption allows high-priority frames to interrupt lower-priority transmissions, reducing latency for time-critical messages without discarding existing traffic.

4. Traffic Scheduling and Shaping

Traffic scheduling in TSN involves defining priority classes and bandwidth allocation for deterministic flows. TSN supports both static scheduling and dynamic adjustment depending on network conditions.

5. Reliability Mechanisms (IEEE 802.1CB)

For industrial environments, packet loss is unacceptable. TSN implements frame replication and elimination to provide seamless redundancy. Multiple copies of critical messages are transmitted along different paths to ensure delivery even in case of link failures.

TSN IN INDUSTRIAL APPLICATIONS

TSN finds applications in multiple industrial domains where deterministic behavior is essential:

1. Factory Automation

Robotic arms, conveyor systems, and automated guided vehicles require precise timing and low-latency communication. TSN ensures synchronized operations and avoids collisions in the network.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

2. Process Control

Chemical, oil, and gas industries demand high reliability and minimal jitter for monitoring and controlling processes. TSN guarantees predictable communication, enhancing safety and efficiency.

3. Automotive Systems

Modern vehicles increasingly rely on Ethernet for communication between sensors, cameras, and control units. TSN provides deterministic data delivery, which is crucial for autonomous driving and advanced driver-assistance systems (ADAS).

4. Energy and Power Systems

In smart grids, TSN supports precise control of distributed energy resources, substations, and real-time monitoring systems.

PERFORMANCE ANALYSIS

Studies show that TSN significantly improves latency, jitter, and reliability compared to standard Ethernet. Table 2 summarizes performance improvements observed in industrial case studies:

Table: 2

Metric	Standard Ethernet	TSN-enabled Ethernet	Improvement
Max Latency	5 ms	200 μs	25x
Jitter	1 ms	10 μs	100x
Packet Loss	0.1%	0%	100% reliability

TSN mechanisms such as time-aware scheduling and frame preemption play a vital role in achieving these deterministic performance levels.

CHALLENGES AND LIMITATIONS

Despite its advantages, TSN adoption faces several challenges:

- **Complex Configuration:** Scheduling and shaping require careful planning to prevent network congestion.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- **Hardware Support:** Not all Ethernet switches support TSN, leading to increased infrastructure costs.
- **Interoperability Issues:** Integrating legacy industrial devices with TSN networks can be difficult.
- **Scalability:** Maintaining determinism over large and complex networks requires advanced management tools.
- **Cybersecurity Concerns:** Deterministic networks may be vulnerable to attacks if security mechanisms are not properly integrated.

FUTURE RESEARCH DIRECTIONS

Future research in TSN can focus on:

- **AI-Enabled TSN:** Using machine learning to dynamically optimize scheduling and traffic shaping.
- **Integration with 5G:** Combining TSN with 5G ultra-reliable low-latency communication (URLLC) for industrial wireless networks.
- **Standardization of Interoperability:** Developing guidelines for seamless integration of TSN with legacy industrial protocols.
- **Cybersecurity Solutions:** Enhancing security while maintaining deterministic performance.
- **Energy-Efficient TSN:** Reducing power consumption of TSN-enabled switches and devices.

CONCLUSION

Time-Sensitive Networking (TSN) is transforming industrial communication by providing deterministic Ethernet capabilities essential for Industry 4.0 and IIoT applications. By enabling precise time synchronization, traffic scheduling, frame preemption, and reliability mechanisms, TSN addresses the limitations of conventional Ethernet in industrial settings. While challenges such as hardware support, complex configuration, and scalability remain, ongoing research and adoption of TSN are expected to expand its applications across factory automation, process control, automotive, and energy systems. The convergence of IT and OT networks with TSN promises a unified, high-performance, and reliable industrial communication framework for the future.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved

REFERENCES

1. IEEE Standards Association. *IEEE 802.1 Time-Sensitive Networking Standards.* 2020.
2. Thangavel, D., et al. "A Survey of Industrial Ethernet-Based Fieldbus Communication in Automation Systems." *IEEE Transactions on Industrial Informatics,* vol. 12, no. 3, 2016, pp. 1295–1307.
3. Pop, P., et al. "Deterministic Networking for Industrial Automation: TSN Standards and Applications." *IEEE Communications Surveys & Tutorials,* vol. 21, no. 2, 2019, pp. 1246–1275.
4. Zhang, X., et al. "Time-Sensitive Networking in Industrial Automation: Architecture and Performance Analysis." *International Journal of Electrical Power & Energy Systems,* vol. 118, 2020, 105747.
5. Wang, Y., et al. "TSN-Based Industrial Communication: Requirements and Challenges." *Journal of Industrial Information Integration,* vol. 17, 2020, 100131.
6. IEEE 802.1AS-2011. *IEEE Standard for Local and Metropolitan Area Networks–Timing and Synchronization for Time-Sensitive Applications.* 2011.
7. IEEE 802.1Qbv-2015. *Enhancements for Scheduled Traffic.* 2015.
8. IEEE 802.1CB-2017. *Frame Replication and Elimination for Reliability.* 2017.
9. Sahu, A., et al. "TSN for Autonomous Vehicles: Challenges and Opportunities." *IEEE Access,* vol. 9, 2021, pp. 127456–127472.
10. De Oliveira, L., et al. "Time-Sensitive Networking for Smart Factories: A Case Study." *Procedia Computer Science,* vol. 170, 2020, pp. 557–564.

Page 119-130 © MANTECH PUBLICATIONS 2025. All Rights Reserved