

Tsunami Impact Assessment Using Remote Sensing

Dr. Ananya Sharma

Associate Professor

Department of Civil Engineering

Coastal Engineering Institute, Chennai, India

Email: ananya.sharma@cei.ac.in

Rohan Verma

Research Scholar

Department of Remote Sensing

National Institute of Technology, Surat, India

Email: rohan.verma@nit.ac.in

ABSTRACT

Tsunamis are among the most devastating natural disasters, causing large-scale destruction to coastal communities, infrastructure, and ecosystems. The rapid detection, monitoring, and assessment of tsunami impacts are essential for effective disaster management and mitigation. Remote sensing technologies, including optical, thermal, and radar imaging, have emerged as powerful tools for assessing tsunami impacts in near-real time and over large geographic areas. These technologies facilitate damage mapping, inundation assessment, and post-disaster recovery planning. This paper presents a comprehensive examination of tsunami impact assessment using remote sensing techniques, highlighting the capabilities and limitations of different sensors, data processing methodologies, and integration with Geographic Information Systems (GIS). Emphasis is placed on historical case studies, such as the 2004 Indian Ocean tsunami and the 2011 Tōhoku tsunami, to illustrate how

remote sensing data have enhanced understanding of tsunami dynamics and damage patterns. The study also explores advancements in real-time satellite monitoring, AI-based image analysis, and multi-sensor fusion to improve accuracy and response time. The insights gained can aid policymakers, urban planners, and disaster management authorities in strengthening coastal resilience against future tsunami events.

INTRODUCTION

Tsunamis, triggered primarily by undersea earthquakes, landslides, or volcanic eruptions, represent one of the most destructive natural hazards, capable of causing catastrophic loss of life and extensive damage to infrastructure. Historically, major tsunami events such as the 2004 Indian Ocean tsunami and the 2011 Japan tsunami have highlighted the urgent need for robust monitoring, early warning, and impact assessment systems. Remote sensing technologies have emerged as indispensable tools in both the immediate aftermath of a tsunami and during long-term recovery planning.

Remote sensing refers to the acquisition of information about the Earth's surface without direct contact, typically through satellite or airborne sensors. These sensors capture electromagnetic radiation in various spectral bands, enabling the detection of land cover changes, water movement, and damage to built-up areas. The integration of remote sensing data with Geographic Information Systems (GIS) has revolutionized tsunami impact assessment, allowing for accurate inundation mapping, damage quantification, and rapid dissemination of results.

This paper investigates the application of optical, radar, and LiDAR-based remote sensing systems for tsunami impact analysis. Optical sensors provide high-resolution imagery suitable for visual interpretation of damage, while radar sensors can penetrate cloud cover and capture surface roughness changes, making them invaluable during post-tsunami conditions when atmospheric disturbances may prevail. LiDAR offers precise elevation data, essential for modeling tsunami inundation and flood extents.

The following sections present detailed methodologies, case studies, and emerging technologies that are transforming tsunami assessment capabilities. By analyzing historical data and integrating modern advancements such as AI-driven image classification and multi-temporal analysis, the paper aims to contribute to the development of more resilient coastal communities and effective disaster response strategies.

LITERATURE REVIEW

Several studies have explored the use of remote sensing for tsunami impact assessment, highlighting the benefits and challenges of various sensor technologies. After the 2004 Indian Ocean tsunami, satellite imagery from sensors such as Landsat, IKONOS, and MODIS played a critical role in mapping inundation zones and assessing coastal damage. Optical remote sensing allowed high-resolution visualization of affected areas, while radar systems like Synthetic Aperture Radar (SAR) provided cloud-penetrating capabilities, ensuring continuous monitoring even under adverse weather conditions.

Research by Moya et al. (2015) emphasized the integration of remote sensing with hydrodynamic models to improve tsunami hazard mapping. Similarly, studies conducted after the 2011 Tōhoku tsunami demonstrated the application of multi-temporal satellite imagery to track shoreline changes, sediment deposition, and infrastructure loss. These case studies reveal that while remote sensing offers unparalleled spatial coverage, its effectiveness depends on rapid data acquisition, timely processing, and the availability of pre-event imagery for comparison.

Emerging literature also focuses on AI and machine learning applications for automated damage classification, enabling faster disaster response. With the increasing availability of free, high-resolution datasets from platforms like Sentinel-1 and Sentinel-2, tsunami assessment is becoming more accessible to developing nations, promoting global disaster resilience.

METHODOLOGY

The methodology for tsunami impact assessment using remote sensing involves several key stages:

1. **Pre-event Data Collection** – Acquisition of baseline imagery from optical or radar satellites to serve as reference datasets for change detection.
2. **Post-event Data Acquisition** – Rapid procurement of satellite images immediately after the tsunami, preferably from multiple sensors to ensure redundancy.
3. **Image Preprocessing** – Radiometric and geometric corrections are applied to ensure consistency between pre- and post-event images.
4. **Change Detection Analysis** – Techniques such as image differencing, supervised classification, and object-based image analysis (OBIA) are used to identify inundated and damaged areas.
5. **GIS Integration** – Remote sensing outputs are integrated into GIS platforms to overlay damage maps with population, infrastructure, and land-use datasets.
6. **Validation** – Field surveys and UAV-based observations are conducted to verify the accuracy of satellite-derived results.

The workflow ensures that assessment results are accurate, reliable, and delivered in time to inform disaster management decisions.

Table 1: Common Remote Sensing Sensors Used in Tsunami Assessment

Sensor	Type	Application
Landsat	Optical	Coastal change detection
Sentinel-1	Radar	Inundation mapping
LiDAR	Active	Elevation and topography mapping

FUTURE SCOPE

The future of tsunami impact assessment using remote sensing lies in integrating advanced technologies such as real-time satellite tasking, AI-driven image analysis, and cloud-based data processing. The development of nanosatellite constellations will significantly reduce data latency, enabling near-instantaneous damage mapping. Furthermore, the fusion of multi-sensor data—including optical, radar, and hyperspectral imagery—will provide more comprehensive assessments. Crowdsourced data from smartphones and social media, when validated, could complement satellite observations, creating a more holistic picture of disaster impacts. The integration of Internet of Things (IoT) devices in coastal regions could provide real-time water level and structural integrity data, feeding into predictive tsunami models and enhancing early warning systems.

CONCLUSION

Remote sensing has revolutionized tsunami impact assessment by offering rapid, accurate, and large-scale damage evaluation capabilities. The combination of optical, radar, and LiDAR technologies, integrated with GIS platforms, allows for detailed mapping of inundation zones and damage extents. Historical case studies demonstrate the critical role of remote sensing in both immediate disaster response and long-term coastal planning. With the continued advancement of satellite technology, AI, and IoT-based monitoring, future tsunami assessments will become faster, more precise, and more accessible, ultimately contributing to enhanced coastal resilience and disaster preparedness.

REFERENCES

- [1] Moya, L., et al. 'Tsunami Hazard Mapping Using Remote Sensing and Hydrodynamic Models.' *Natural Hazards*, vol. 78, no. 2, 2015, pp. 1119–1136.

- [2] Gokon, H., et al. 'Mapping of the 2011 Tōhoku Tsunami Inundation and Run-up Using SAR Data.' *IEEE Transactions on Geoscience and Remote Sensing*, vol. 53, no. 4, 2015, pp. 1612–1622.
- [3] Liu, W., and Yamazaki, F. 'Detection of Tsunami Inundation Areas Using TerraSAR-X Data.' *Remote Sensing*, vol. 5, no. 7, 2013, pp. 3379–3392.
- [4] Chini, M., et al. 'The 2011 Tōhoku Tsunami: Remote Sensing Data Analysis and Modeling.' *Coastal Engineering Journal*, vol. 54, no. 1, 2012.
- [5] United Nations ESCAP. 'Guidelines for Tsunami Risk Assessment.' UN Publications, 2014.
- [6] Senthil Kumar, A., et al. 'Role of Remote Sensing in Disaster Management.' *International Journal of Remote Sensing*, vol. 37, no. 23, 2016, pp. 5405–5425.
- [7] NOAA. 'Tsunami Detection and Forecasting.' National Oceanic and Atmospheric Administration, 2020.
- [8] Smith, R., and Brown, T. 'SAR Applications in Coastal Disaster Monitoring.' *Remote Sensing Letters*, vol. 9, no. 10, 2018, pp. 935–944.
- [9] Singh, A., et al. 'Geospatial Technologies for Coastal Hazard Assessment.' Springer, 2019.
- [10] European Space Agency. 'Sentinel-1 for Tsunami Mapping.' ESA Reports, 2021.