MANTECH Publications

Intellectum: Advances in General Intelligence Systems
Volume 1, Issue 1, January-April 2025

Cognitive Memory Systems for AGI

Dheeraj Prasad[1], Manoj Upadhyay[2], Lla P Patnayak[3]

Associate Professor[1], Professors[2, 3]

Department of Computer Science Engineering

Vidyavardhaka College of Engineering

***Email ID**: Dheerajprasad10@gmail.com[1], manojupadhyay@rediffmail.com[2],patnayakp1lal@yahoo.com[3]*

ABSTRACT

Artificial General Intelligence (AGI) aims to emulate human-level cognitive abilities, requiring flexible and efficient memory systems. Cognitive memory is central to learning, reasoning, decision-making, and adaptive behavior. This review investigates various cognitive memory systems, including working memory, episodic memory, semantic memory, procedural memory, and hybrid architectures used in AGI research. We explore their computational models, biological inspirations, implementation challenges, and integration strategies for AGI architectures. The paper further discusses emerging trends in memory consolidation, self-organizing memory networks, and attention-based memory systems. Our analysis highlights the critical role of dynamic, multi-layered memory structures in achieving human-like general intelligence.

KEYWORDS: *AGI, cognitive memory, working memory, episodic memory, semantic memory, memory consolidation, hybrid memory architectures, neural networks*

INTRODUCTION

Artificial General Intelligence (AGI) refers to machines capable of performing any intellectual task that a human can, with generalization across domains. Unlike narrow AI systems, AGI requires a sophisticated understanding of context, long-term reasoning, and adaptive learning. Central to this capability is **cognitive memory**, which enables knowledge retention, retrieval, and dynamic learning.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Memory in humans is multi-faceted, encompassing short-term (working memory) and long-term systems (episodic, semantic, and procedural). AGI research draws inspiration from these structures to design artificial memory systems capable of supporting learning, planning, and problem solving.

This paper reviews cognitive memory systems, biological and computational foundations, and their application in AGI. We also explore hybrid memory architectures, memory optimization strategies, and future directions for integrating cognitive memory in intelligent systems.

COGNITIVE MEMORY TYPES AND THEIR AGI RELEVANCE

Cognitive memory can be categorized into multiple types, each with distinct roles in intelligence.

1. Working Memory

Working memory (WM) refers to the temporary storage and manipulation of information necessary for reasoning, learning, and comprehension. In humans, WM is limited in capacity and duration but critical for higher-order cognition.

AGI Implementation:

- Neural Turing Machines (NTM) and Differentiable Neural Computers (DNC) simulate WM by providing read-write memory addressing.
- Attention mechanisms in transformers also mimic selective WM by focusing on relevant information while suppressing noise.

Applications in AGI:

- Real-time decision-making
- Contextual understanding
- Task planning

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved




Figure 1: Working Memory in AGI architectures

2. Episodic Memory

Episodic memory stores personal experiences and contextual events. It allows AGI systems to recall specific experiences, supporting learning from past interactions.

AGI Implementation:

- Memory-augmented neural networks store event embeddings along with timestamps.
- Graph-based memory models enable relational representation of episodic events.

Challenges:

- Temporal encoding of events
- Efficient retrieval without catastrophic forgetting

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Table 1: Comparison of episodic memory models in AGI.

Model	Representation	Retrieval Mechanism	Pros	Cons
DNC	Memory matrix	Content-based addressing	Flexible storage	High computational cost
Event Graph	Nodes & edges	Graph traversal	Relational reasoning	Scalability issues
Episodic LSTM	Sequence memory	Sequence recall	Temporal ordering	Limited capacity

3. Semantic Memory

Semantic memory contains facts, concepts, and general knowledge independent of personal experience. It is essential for language understanding, reasoning, and inference.

AGI Implementation:

- Knowledge graphs and ontologies represent structured semantic information.
- Transformer models with large-scale pretraining capture implicit semantic relationships.

Applications:

- Question answering
- Commonsense reasoning
- Multi-domain problem-solving

4. Procedural Memory

Procedural memory stores skills, routines, and actions. It supports automatic task execution without conscious thought.

AGI Implementation:

- Reinforcement learning (RL) frameworks store policies for decision-making.
- Hierarchical RL enables the organization of skills into subroutines.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Challenges:

- Balancing exploration vs exploitation
- Skill generalization across domains




Figure 2: Procedural memory flowchart in AGI showing skill learning, storage, and execution pipeline.

MEMORY INTEGRATION IN AGI ARCHITECTURES

Human intelligence does not rely on a single memory store. Instead, multiple memory systems operate together in a coordinated way. For Artificial General Intelligence, this integration is very important because intelligent behavior requires **temporary reasoning**, **long-term knowledge recall**, **experience-based learning**, and **skill execution** at the same time. An AGI system therefore cannot depend only on a neural network with static weights; it must include interacting memory modules that serve different cognitive roles.

In practical AGI design, memory integration means that **working memory (WM)** handles immediate reasoning, **episodic memory** stores experiences, **semantic memory** provides general knowledge, and **procedural memory** controls actions and skills. These components

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

must exchange information continuously, forming a loop between perception, memory retrieval, decision making, and learning.

1. Hybrid Memory Architectures

A hybrid memory architecture refers to a system where multiple types of memory are combined into a unified framework. Each memory type contributes a different cognitive function, but they operate under a central control mechanism or cognitive controller.

In such an architecture:

- **Working Memory** stores current task context, intermediate results, and goals.
- **Episodic Memory** provides reference to past events that are similar to the current situation.
- **Semantic Memory** supplies factual and conceptual knowledge required for reasoning.
- **Procedural Memory** executes learned skills or action policies.

These memories are not isolated databases. They are linked through **bidirectional information flow**.

Example of Operation

Consider an AGI robot assembling a new device:

- WM holds the current assembly step.
- Episodic memory retrieves a past experience where a similar device was assembled.
- Semantic memory provides knowledge about component functions.
- Procedural memory executes motor actions to assemble parts.

This cooperative process allows the system to act intelligently in unfamiliar situations by combining past experience, general knowledge, and learned skills.

Architectural Patterns Used

Several computational patterns are used to implement hybrid memory:

- **Memory-augmented neural networks** (MANNs)
- **Graph-based knowledge stores** linked with neural controllers
- **External memory buffers** accessed via attention heads
- **Hierarchical controllers** managing different memory types

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Benefits of Hybrid Memory

Benefit	Description
Better Generalization	Uses knowledge from multiple sources for new tasks
Reduced Forgetting	Long-term storage reduces overwriting of knowledge
Contextual Intelligence	WM and episodic memory provide situational awareness
Continual Learning	New experiences are stored without disturbing old knowledge

Hybrid memory is considered a key requirement for AGI because it resembles how human cognition manages information across time scales.

2. Memory Consolidation Mechanisms

Memory consolidation is the process of transferring information from temporary storage into stable long-term memory. In biological brains, this occurs during sleep and rest. Inspired by this, AGI systems use algorithmic consolidation strategies to prevent loss of learned knowledge.

Without consolidation, neural systems suffer from **catastrophic forgetting**, where new learning overwrites previous learning.

a) Offline Replay

In offline replay, the AGI system reprocesses past experiences when it is not actively performing tasks.

- Stored episodes are replayed through the learning network.
- Reinforces older memories and strengthens neural connections.
- Similar to rehearsal in human memory.

This technique is commonly used in reinforcement learning systems.

b) Generative Replay

Instead of storing all raw experiences, AGI can use generative models to recreate previous data.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- A generative network reconstructs past scenarios.
- Saves memory space while preserving knowledge.
- Useful for lifelong learning systems.

c) Synaptic Consolidation

This technique modifies how learning weights are updated:

- Important weights are protected from large changes.
- Less important connections remain flexible for new learning.
- Methods like Elastic Weight Consolidation (EWC) are examples.

These methods ensure that semantic and procedural memories remain stable over long time periods.

3. Attention-Based Memory Systems

Attention mechanisms are inspired from the human ability to focus only on relevant information. In AGI, attention plays a crucial role in selecting what part of memory should be accessed at any time.

Instead of searching the entire memory store, attention allows **selective memory retrieval**, improving speed and efficiency.

Role of Attention in Memory Integration

- Determines which episodic memory is relevant to the current context.
- Selects semantic knowledge related to the task.
- Updates working memory with only important information.
- Helps procedural memory choose correct action policies.

Applications

- **Transformer-Based AGI Systems**

  Transformers use self-attention to maintain context across long sequences. This acts similar to working memory and semantic retrieval.
- **Adaptive Memory Retrieval in Robotics**

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Robots use attention to recall only task-relevant experiences from episodic memory while navigating dynamic environments.

- **Context-Aware Natural Language Understanding**
  Attention helps language models recall relevant facts, prior dialogue context, and rules of conversation.

CHALLENGES IN COGNITIVE MEMORY DESIGN FOR AGI

- **Scalability:** Memory systems must store massive amounts of information without performance degradation.
- **Catastrophic Forgetting:** Neural networks often overwrite previously learned knowledge.
- **Temporal Representation:** Encoding time and sequence of events is critical for episodic and procedural memory.
- **Integration:** Synchronizing multiple memory systems for coherent cognition is complex.
- **Resource Efficiency:** Balancing memory size, computation, and energy consumption is essential for practical AGI deployment.

EMERGING TRENDS IN COGNITIVE MEMORY SYSTEMS FOR AGI

As AGI research progresses, traditional fixed memory structures are being replaced by **adaptive, intelligent, and self-managing memory frameworks**. These emerging trends focus on making memory not just a storage unit, but an **active participant** in learning, reasoning, and decision-making. Modern approaches aim to make memory systems flexible, interpretable, and capable of operating continuously across diverse tasks and environments.

1. Self-Organizing Memory Networks

Self-organizing memory networks refer to architectures where the memory structure is not fixed. Instead, it evolves automatically depending on task requirements, environmental complexity, and learning history.

In conventional AI systems, memory size, structure, and access patterns are predefined. However, for AGI, such static design is limiting because real-world problems vary widely in complexity and context.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Key Characteristics

- **Dynamic memory allocation:** The system creates new memory slots when needed and removes redundant ones.
- **Adaptive indexing:** Frequently accessed memories are reorganized for faster retrieval.
- **Structural plasticity:** Memory connections rewire themselves based on usage patterns.
- **Context-driven reconfiguration:** Different tasks activate different memory Sub-structures.

These systems are inspired by **neuroplasticity** in the human brain, where neural connections strengthen or weaken based on experience.

Working Principle

When an AGI system encounters a new task:

- It evaluates whether existing memory representations are sufficient.
- If not, new memory nodes or clusters are formed.
- Related memories are grouped into clusters to improve retrieval.
- Rarely used memories are compressed or archived.

This approach allows the system to **optimize memory space** and **reduce retrieval time** without manual redesign.

Advantages

- Efficient use of computational resources
- Faster memory retrieval for relevant tasks
- Scalability across domains
- Reduced redundancy in stored knowledge

Self-organizing memory is especially useful in environments where the AGI system continuously interacts with new data, such as robotics, autonomous agents, and open-world learning systems.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

2. Neuro-Symbolic Memory Models

One limitation of purely neural memory systems is lack of interpretability. Knowledge is stored in distributed weights, making it difficult to explain reasoning. Neuro-symbolic memory models aim to solve this by combining **neural learning** with **symbolic knowledge representation**.

In this model:

- Neural networks learn patterns from data.
- Symbolic structures (graphs, rules, logic expressions) store explicit knowledge.
- Memory retrieval involves both statistical matching and logical reasoning.

Why It Matters for AGI

AGI must not only learn but also **reason and explain**. Neuro-symbolic memory allows:

- Transparent decision-making
- Logical reasoning over stored knowledge
- Better generalization to unseen problems
- Easier debugging and interpretability

Application Examples

- Question answering systems that combine learned language patterns with factual databases
- Robotics systems that use learned perception but rule-based planning
- Scientific discovery agents that generate hypotheses using symbolic rules applied to learned data

This hybrid memory approach is seen as a promising path toward **explainable and trustworthy AGI**.

3. Lifelong Learning Systems

Lifelong learning is the ability of an AGI system to learn continuously from new experiences without forgetting previously learned knowledge. This requires advanced memory mechanisms that can grow, reorganize, and consolidate over time.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Traditional AI systems are trained once and deployed. In contrast, AGI must remain in a **perpetual learning state**.

Core Features

- **Continuous memory update** as new tasks are encountered
- **Replay-based consolidation** to prevent forgetting
- **Meta-learning** to improve how the system learns over time
- **Task-aware memory separation** to avoid interference

Role of Meta-Learning

Meta-learning allows the system to learn how to allocate memory efficiently:

- Determines which information should be stored long-term
- Identifies patterns across tasks for reuse
- Optimizes memory retrieval strategies

Replay-Based Consolidation

As discussed earlier, replay mechanisms help reinforce older knowledge. In lifelong systems, replay is more intelligent:

- Prioritizes important experiences
- Uses compressed or generative representations
- Schedules replay during low-activity periods

Benefits for AGI

- Adaptation across domains without retraining from scratch
- Robust knowledge retention over long periods
- Gradual improvement in learning efficiency
- Ability to handle evolving environments and tasks

Lifelong learning memory systems are essential for AGI agents operating in real-world scenarios such as personal assistants, service robots, or research agents.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

APPLICATIONS OF COGNITIVE MEMORY SYSTEMS IN AGI

- **Autonomous Robotics:** Memory allows robots to learn from experiences and adapt to dynamic environments.
- **Scientific Discovery:** Episodic and semantic memory systems help AGI agents explore hypotheses and recall past experimental results.
- **Natural Language Understanding:** Working and semantic memory enable context aware conversation and comprehension.
- **Decision Support Systems:** Integrating episodic and procedural memory helps AGI make informed, context-sensitive decisions.




Figure 3: Applications of cognitive memory in AGI

CONCLUSION

Cognitive memory systems are fundamental to AGI, enabling learning, reasoning, and adaptive behavior. Integration of working, episodic, semantic, and procedural memory supports human-like intelligence. Advances in hybrid memory architectures, attention mechanisms, and lifelong learning enhance AGI's cognitive capabilities. Future research should focus on scalable, efficient, and interpretable memory systems that emulate the flexibility and robustness of human memory. Optimizing memory consolidation, self-organization, and neuro-symbolic integration will be key in achieving truly general intelligence.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved

REFERENCES

1. Graves, A., Wayne, G., & Danihelka, I. (2014). Neural Turing Machines. *arXiv preprint arXiv:1410.5401*.
2. Santoro, A., et al. (2016). Meta-learning with Memory-Augmented Neural Networks. *ICML*.
3. Hassabis, D., Kumaran, D., Summerfield, C., & Botvinick, M. (2017). Neuroscience-inspired Artificial Intelligence. *Neuron*, 95(2), 245–258.
4. Lake, B., Ullman, T., Tenenbaum, J., & Gershman, S. (2017). Building Machines That Learn and Think like People. *Behavioral and Brain Sciences*, 40.
5. Banino, A., et al. (2018). Vector-based navigation using grid-like representations in artificial agents. *Nature*, 557, 429–433.
6. Zaremba, W., Sutskever, I., & Vinyals, O. (2015). Reinforcement Learning Neural Turing Machines. *arXiv preprint arXiv:1505.00521*.
7. Weston, J., Chopra, S., & Bordes, A. (2014). Memory Networks. *arXiv preprint arXiv:1410.3916*.
8. Schmidhuber, J. (2015). Deep Learning in Neural Networks: An Overview. *Neural Networks*, 61, 85–117.
9. Parisotto, E., & Salakhutdinov, R. (2017). Neural Map: Structured Memory for Deep Reinforcement Learning. *ICLR*.
10. Graves, A., et al. (2016). Hybrid computing using a neural network with dynamic external memory. *Nature*, 538, 471–476.

Page 28-41 © MANTECH PUBLICATIONS 2025. All Rights Reserved