

## *Use of GIS for Solving Space Related Problems in Construction*

### *Industry*

*Dr. Chandraprakash Mandrai<sup>1</sup>, Sunny Kumar<sup>2</sup>*

*Professor<sup>1</sup>, Student<sup>2</sup>*

*Department of Civil Engineering*

*VNS Institute of Engineering & Technology*

*Corresponding Author's Email: - sunnykumar455@gmail.com<sup>2</sup>*

#### *Abstract*

*Geographic Information System (GIS) is a computer-based technology that is widely used to address engineering challenges involving geographical data. Despite its expanding popularity, GIS has yet to fulfil its full potential in the building business. This paper presents a synopsis of recent work on spatial uses of GIS technology in the construction sector. GIS technologies have the capacity to tackle space-related construction sector challenges such as sophisticated visualisation, information integration, route planning, E-commerce, cost calculation, and so on. This study develops and discusses a GIS-based technique for dealing with time and space challenges in construction project scheduling.*

***Keywords:*** *GIS in construction, Construction, Scheduling, Project Management, GIS Technologies*

#### **INTRODUCTION**

GIS is a computer tool that captures, stores, queries, analyses, and displays geographic information. GIS, like any other information system, is a subset of information systems that consists of four components: a computer system, GIS software, a human expert, and data. Spatial

and attribute data management, data presentation, data exploration, data analysis, and modelling are all examples of GIS activities. GIS synchronises geographical and non-spatial data so that both may be queried, analysed, and presented. Spatial data is connected to feature geometry, whereas attribute data

provided in tabular form describes the qualities of individual features in a GIS layer. Each row of the table represents a feature, and each column represents a feature characteristic. The intersection of a column and a row represents the value of a certain feature's characteristic. To represent spatial characteristics, GIS employs vector and raster data models. The vector data model constructs spatial characteristics by using points and their x and y coordinates (points, lines and areas). In the space, the characteristics are handled as separate objects. A grid is used in the raster data model to express spatial variations of features. Each grid cell contains a value that corresponds to a spatial feature typical at that place. Raster data is ideal for representing continuous spatial characteristics [1].

### **GIS in Construction Industry**

GIS systems are used in many domains of civil engineering, including transportation, water resources, facility management, urban planning, construction, and E-business. This section [2] discusses its uses in the building sector.

### **Subsurface Profile**

Camp and Brown [3] proposed using GIS to create a method for producing subsurface profiles from well-log data.

The well-log database was built from a succession of boreholes, and a GIS-based process was utilised to generate a 3D subsurface model. Oloufa et al. [4] emphasised the importance of site inquiry in estimating and planning new building projects, and they proposed using GIS-based approach to create a database for foundations study, design, and construction planning. Surface and subsurface characteristics impact construction methods and equipment selection, which affects project cost and schedule. As a result, Oloufa et al. [4] employed GIS database management capacity to record descriptive soil data and correlate this data with drill sites.

### **Quantity Takeoffs and Construction Cost Estimation**

Cheng and Yang [5] proposed utilising Map/Info for quantity takeoffs and cost estimates. For quantity takeoffs, architectural drawings were separated into several levels known as data layers. The fundamental criteria in GIS-based cost estimations were area and perimeter. Thus, data layers were prepared in AutoCAD as polygons and uploaded to Map/Info as geometric coverage. Coverage yields geometric information about spatial properties such as coordinate, area, perimeter, and spatial connection. In

contrast, the user inserts theme information such as an identity (ID) code, beam number, floor number, and so on. Recently, Bansal and Pal [6] proposed a more broad use of GIS for cost estimate by introducing additional scripts to the GIS environment for various cost estimation activities. This was accomplished using ArcView, which makes advantage of dynamic linking between spatial and attribute data.

### **Materials Layout at Construction Site**

The Material Plan, a GIS-based tool developed by Cheng and Yang [5] integrates quantity takeoffs with material layout planning. The system uses rules of thumb and experience to decide the size and location of material storage area. It assists planner in quantity takeoffs as well as in assessing material layout design. Material Plan developed by using a GIS environment integrates estimates with construction scheduling for dynamic materials requirement plan. Based on the information regarding quantities and locations of materials required in the project, the proposed methodology identifies the suitable site to store construction materials.

### **Construction Site Layout**

The conventional approach to layout temporary facility (TFs) involves designing site layout using sketches, templates and 2D physical model. The developed layout is based upon the incomplete information stored in the different form. Such visual representations of TFs do not yield adequate and descriptive results. As TFs should be located close to their supporting activities to reduce the time for travel, the role of GIS may be explored for this. Cheng and O'Connor [7] developed an automated site layout system called ArcSite using GIS for construction TFs. ArcSite consist of a GIS integrated with DBMS was claimed a new computerized tool to identify suitable area to locate TFs. ArcSite integrate information required to find suitable location for TFs and perform series of complicated spatial operations and database queries to identify optimal site that is difficult to perform manually.

### **Real -Time Schedule Monitoring System**

Cheng and Chen [8] developed an automated schedule monitoring system by using GIS to assist construction managers to control erection process for precast building construction. A case study was taken where structural elements were prefabricated in the manufacturing plant

and transported to job site for installation. Erection of prefabricated structural components is considered a major critical activity for precast building construction.

The schedule for prefabrication and transport of structural elements to job site are developed based on installation schedule. The study suggested that the use of GIS environment improves the real time schedule monitoring system and construction process as well as improves construction efficiency. A study reported by Li et al. [9]-[10] integrates Global Position System (GPS) and GIS technologies to reduce construction waste. GPS and GIS were integrated with construction management system in such a way that managers from the headquarters and construction sites get real time information to control cargoes coming through road to sites, so as to reduce the waste generation on sites.

### **Route-Planning**

Varghese and O'Connor [11] developed a GIS based system in which the information required for route planning can be integrated. Study make use of two technologies: expert system and GIS to develop this tool, expert system attempt to model the human reasoning process through a set of predetermined rules while

GIS provide data display capabilities. In urban areas, obstacles such as existing public utility lines, railways, canals and roads influence routes significantly.

There may be a limited number of feasible crossing points; selection of a suitable route to avoid existing obstacles in a path reduces the risk of damaging the existing utilities. It also minimizes the cost required during construction. Cheng and Chang [12] discussed the development of a GIS based system to automate the process of routing and design of an underground power supply system. The optimal paths for routing are determined using the network analysis of Arc/Info GIS package.

### **Topography Visualization**

GIS is an effective tool to visualize the topographical conditions of construction site.

The modeling of construction site facilitates in construction controlling and planning process. GIS-based visual simulation system (GVSS) developed by Zhong et al. [13] is a tool that offers powerful planning, visualizing and querying capabilities as well as facilitate the detection of logical errors in a model.

## **Spatial Aspects of a Construction Project**

Commercially available scheduling tools such as Primavera and Microsoft Project fail to provide information pertaining to Spatial aspects of a construction project. A methodology using GIS is developed to represent spatial aspects of construction graphically by synchronizing with construction schedule. The spatial aspects are depicted by 3D model developed in AutoCAD and using Microsoft Excel generates construction schedule. Spatial and scheduling information are linked together into a GIS environment. The GIS-based system developed in this study help in understanding the schedule along with its spatial aspects.

## **METHODOLOGY**

The construction schedule, which serves as a roadmap for the effective implementation of the construction project, is created in Microsoft Excel and then imported into ArcGIS [14]. AutoCAD [6] generates the geographical information for the many operations indicated in the construction schedule. The drawings are imported as layers into ArcGIS and may be represented and queried. GIS supports working with AutoCAD drawings; however, to edit or alter AutoCAD drawing layer features or related attribute

table layers, shapefiles must be transformed. Shapefiles are a simple non-topological format for storing geographic feature geometric position and attribute information.

Layers imported from Auto CAD into Arc GIS can be blended together based on the actions established earlier in the Microsoft Excel schedule. As a result, components of a drawing that belong to the same activity but are placed at various points in space are connected together to provide spatial data for each activity. Linking an activity to its schedule entails adding a key field to the schedule and its attribute table.

The field key is shared by two tables (the schedule and the attribute table of distinct components) and is used to relate the spatial aspect of activity to the corresponding activity in the schedule. All entries in the field key must be manually entered and must be unique in both the schedule and attribute tables of an activity. The link between the timetable and the geographical characteristics of the construction operations is depicted in Fig. 1.




Fig. 1 linking the schedule with spatial aspects of the construction activities

## CONCLUSION

This article provides an overview of several spatial uses of GIS in the construction sector. As one of the rapidly expanding sectors used in numerous engineering projects, GIS's full potential in the construction industry has yet to be realised. By integrating geographic and

attribute information in a single environment, GIS improves construction planning and design efficiency. Researchers reported in this field are limited, since attempts to use GIS in the construction sector have not addressed the issue of its implementation in actual practise.

GIS is a useful technique for integrating geographical and non-spatial building project information in a single environment. The technique provided in this study connects the construction schedule with the related geographical features to make the project sequence easier to grasp. This connection facilitates knowledge of the project and aids in the detection of potential difficulties. Non-spatial timetables just express what is constructed 'when,' but GIS schedules transmit what is built 'when and where.'

## REFERENCES

1. K. T. Chang, Introduction to Geographic Information Systems, Tata McGraw-Hill, New Delhi, 2002.
2. M.N. Jeljeli, J.S. Russell, H.W.G. Meyer, and A.P. Vonderohe, "Potential applications of geographic information systems to construction industry." *Journal Construction Engineering and Management*, Vol. 119, no.1, pp. 72-86, March 1993.
3. C.V. Camp, and M.C. Brown, "GIS procedure for developing three- dimensional subsurface profile." *Journal of Computing in Civil Engineering*, Vol. 7, no.3, pp. 296-309, July 1993.
4. A.R. Oloufa, A.A. Eltahan, and C.S. Papacostas, "Integrated GIS for construction site investigation." *Journal Construction Engineering and Management*, Vol. 120, no.1, pp. 211-222, March 1994.
5. M.Y. Cheng, and C.Y. Yang, "GIS-Based cost estimate integrated with material layout planning." *Journal Construction Engineering and Management*, Vol. 127, no. 4, pp. 291-299, Jul./Aug. 2001.
6. V.K. Bansal, and M. Pal, "Potential of geographic information systems in building cost estimation and visualization." *Automation in Construction*, Vol. 16, no.3, pp. 311-322, May 2007.
7. M.Y. Cheng, and J.T. O'Connor, "ArcSite: Enhanced GIS for construction site layout." *Journal Construction Engineering and Management*, Vol. 122, no.4, pp. 329-336, Dec.1996.
8. M.Y. Cheng, and J.C. Chen, "Integrating barcode and GIS for monitoring construction progress." *Automation in Construction*, Vol. 11, pp. 23-33, Jan. 2002.

9. H. Li, C.W. Kong, Y.C. Pang, W.Z. Shi, and L. Yu, "Internet-based geographic information systems system for E-commerce application in construction material procurement." *Journal Construction Engineering and Management*, Vol. 129, no.6, pp. 689-697, Nov./Dec. 2003.
10. H. Li, Z. Chen, L. Yong, and S.C.W. Kong, "Application of integrated GPS and GIS technology for reducing construction waste and improving construction efficiency." *Automation in Construction*, Vol. 14, pp. 323- 331, June 2005.
11. K. Varghese, and J.T. O'Connor, "Routing large vehicles on industrial construction site." *Journal Construction Engineering and Management*, Vol. 121, no.1, pp. 1-12, March1995.
12. M.Y. Cheng, and G.L. Chang, "Automating utility route deign and planning through GIS." *Automation in Construction*, Vol. 10, pp. 507- 516, May 2001.
13. D. Zhong, J. Li, H. Zhu, and L. Song, "Geographic information system based visual simulation methodology and its application in concrete dam construction processes." *Journal Construction Engineering and Management*, Vol. 130, no.5, pp. 742-750, Sep./Oct.2004.
14. P. Aggarwal, and V.K. Bansal, "Spreadsheet-based solution for critical path method." *NICMAR Journal of Construction Management*, Vol. 22, no. 2, pp. 1-5, 2007.