

Multi-Robot Coordination in Reconfigurable Production Lines

R. K. Verma¹, S. Mahajan², P. Dutta³

Associate Professor, Students

Department of Manufacturing Systems

Regional Technical College, Nagpur, India

Email: Rk8verma@yahoo.com¹, Mahajan.s57@gmail.com², duttap47p@rediffmail.com³

Abstract

Modern manufacturing is shifting from fixed mass production toward flexible and customized production systems. Reconfigurable production lines allow rapid change in product type, volume and workflow. In such systems, multiple robots must work together in coordinated manner to perform tasks like assembly, material handling, inspection and packaging. Multi-robot coordination improves productivity and adaptability but also introduces challenges such as task allocation, collision avoidance, communication and real-time control. This paper presents a review of multi-robot coordination approaches in reconfigurable production lines. Different coordination architectures, planning algorithms, communication strategies and control techniques are discussed. Applications in smart factories and Industry 4.0 environments are analyzed. The study also highlights advantages, limitations and future research directions. Results show that cooperative robot systems can significantly increase flexibility and throughput of production lines when proper coordination strategies are applied.

Keywords: *Multi-robot systems, Reconfigurable manufacturing, Production lines, Robot coordination, Smart factories, Task allocation, Industrial automation*

INTRODUCTION

Manufacturing industries are facing increasing demand for product variety, shorter life cycles and mass customization. Traditional fixed production lines are not suitable for such dynamic

requirements. Reconfigurable production lines are designed to change structure, capacity and function quickly according to production needs. Robots play a central role in these systems due to their programmability and precision.

Instead of single robot performing isolated tasks, modern factories deploy multiple robots working cooperatively. Multi-robot coordination allows parallel operations, load sharing and dynamic task execution. It is especially important in reconfigurable lines where layout and workflow change frequently.

However, coordinating several robots in shared workspace is complex. Issues include task distribution, path planning, synchronization, communication delay and safety constraints. Improper coordination can lead to collisions, idle time or inefficiency. Therefore intelligent coordination strategies are required.

This paper reviews state-of-the-art techniques for multi-robot coordination in reconfigurable production lines. Focus is on manufacturing applications such as assembly, handling and inspection.

RECONFIGURABLE PRODUCTION LINES

Reconfigurable manufacturing systems (RMS) represent an advanced paradigm in modern production engineering. Unlike traditional dedicated production lines which are optimized for a single product type, reconfigurable production lines are designed to adapt quickly to changing market demand, product design variation and production volume fluctuation.

This capability is particularly important in present manufacturing scenario where product life cycles are becoming shorter and customization requirements are increasing.

A reconfigurable production line typically consists of modular workstations interconnected through flexible material handling systems such as conveyors or automated guided vehicles. Robots, sensors, controllers and tooling units are designed in modular manner so that they can be rearranged, replaced or upgraded with minimum interruption to production. The key objective of reconfigurable lines is to achieve both high productivity of mass production and flexibility of job shop manufacturing in same system.

In such lines, system configuration can be changed by altering robot programs, replacing end-effectors, rearranging stations or modifying workflow logic. This allows manufacturers to introduce new product variants or change production capacity without building completely new line. Therefore reconfigurable production lines are considered essential component of smart factories and Industry 4.0 manufacturing environments.

Characteristics of Reconfigurable Lines

Reconfigurable production lines possess several defining characteristics that differentiate them from conventional manufacturing systems. These features enable rapid adaptation and efficient operation under changing conditions.

Modular Structure

The most fundamental characteristic of reconfigurable lines is modularity. Each workstation or production unit is designed as independent module with standardized mechanical and control interfaces. Modules may include robot cells, inspection stations, tooling units or handling devices. Because of modular architecture, stations can be added, removed or rearranged easily according to product requirements. This reduces redesign effort and supports quick line reconfiguration.

Scalability in Capacity

Reconfigurable lines allow production capacity to be increased or decreased by adjusting number of stations or robots. For example, additional parallel robot cells can be introduced to increase throughput during high demand period. Similarly, redundant stations can be removed during low production demand to reduce operational cost. This scalability ensures better resource utilization and energy efficiency.

Convertible Functionality

Stations in reconfigurable lines are capable of performing multiple functions by changing tooling or control program. A robot may perform assembly task for one product and inspection task for another simply by replacing end-effector and updating software.

Convertible functionality reduces need for dedicated machines and supports product variety without major hardware changes.

Integrable Subsystems

Reconfigurable production lines are designed with standardized communication and mechanical interfaces so that new subsystems can be integrated easily. Robots, sensors, vision systems, conveyors and controllers from different vendors can be combined in same line. Integration capability is important for gradual system upgrades and technology adoption.

Diagnosable Performance

Modern reconfigurable lines incorporate sensors and monitoring systems to evaluate performance and detect faults. Diagnosability enables quick identification of malfunctioning modules, allowing maintenance without stopping entire line. Condition monitoring, predictive maintenance and digital twin technologies are often used for this purpose. As a result, downtime during reconfiguration or repair is minimized.

These characteristics collectively enable production line to change configuration, capacity or functionality with minimal interruption and cost. Reconfigurable lines therefore provide both flexibility and productivity which are normally conflicting objectives in manufacturing systems.

Role of Robots in Reconfigurable Lines

Industrial robots are key enablers of reconfigurable production lines due to their programmability, precision and versatility. Unlike fixed automation equipment, robots can be reprogrammed for different tasks and trajectories without mechanical redesign. This makes them suitable for dynamic and modular manufacturing environments.

In reconfigurable lines, robots perform wide range of operations depending on production stage and product type.

Assembly Operations

Robots assemble components such as mechanical parts, electronic modules or subassemblies. They can perform screw fastening, insertion, pressing or alignment operations with high repeatability. Multi-robot assembly cells are commonly used for complex products where several parts must be positioned simultaneously. Reprogramming allows same robot to assemble different product variants.

Pick-and-Place Handling

Material handling is one of the most frequent robot tasks in reconfigurable lines. Robots transfer parts between stations, orient components and load/unload machines. Flexible grippers and vision systems enable robots to handle different shapes and sizes. Coordinated pick-and-place by multiple robots increases throughput and supports parallel processing.

Welding or Fastening

In metal fabrication or automotive lines, robots perform welding, riveting or fastening operations. Reconfigurable fixtures and programmable paths allow same robot cell to work on different product geometries. When product design changes, welding trajectory can be updated instead of replacing equipment.

Inspection and Testing

Robots equipped with cameras or sensors inspect products for dimensional accuracy, surface defects or assembly correctness. They can move sensors along complex paths for complete inspection coverage. Reconfigurable lines often integrate inspection robots at different stages to maintain quality despite product variation.

Packaging

At final stage, robots perform sorting, packing and palletizing. Packaging requirements often change with product size or order type, therefore programmable robots provide necessary flexibility. Multiple robots can coordinate to pack items in different patterns or containers.

Because reconfigurable production lines frequently change layout and workflow, robots rarely operate in isolation. Multiple robots may share workspace, exchange parts or collaborate on same product. For example, two robots may hold and assemble a large component simultaneously, or several robots may perform parallel operations on same assembly line. Such interactions require precise synchronization, task allocation and collision avoidance.

Therefore, effective coordination among robots becomes essential to ensure smooth operation, prevent interference and maintain productivity in reconfigurable production lines. Multi-robot coordination strategies discussed in later sections enable robots to adapt to changing configurations while working cooperatively in shared manufacturing environment.

MULTI-ROBOT COORDINATION CONCEPTS

Multi-robot coordination refers to the ability of multiple robotic units to cooperate, synchronize and share resources in order to achieve common manufacturing objectives. In reconfigurable production lines, several robots often operate in shared workspace and interact with same product or material flow. Without proper coordination, robots may interfere with each other, create bottlenecks or remain idle, which reduces overall efficiency of production system.

Coordination involves decision making at different levels such as task assignment, motion planning, timing synchronization and information exchange. Effective coordination ensures that robots perform their operations in correct order, at right time and without collision. It also improves utilization of robots and reduces cycle time in manufacturing processes.

In reconfigurable production lines, coordination becomes more complex because layout, product type and workflow may change frequently. Robots must adapt their interaction strategy according to new configuration. Therefore understanding different types of coordination is important for designing flexible multi-robot manufacturing systems.

Types of Coordination

Multi-robot coordination in production lines can be categorized into several types depending on how robots share tasks and workspace. Each type is suitable for specific manufacturing situations.

1. Cooperative Coordination

In cooperative coordination, two or more robots jointly perform a single task that cannot be completed by one robot alone. Robots physically or functionally interact with same workpiece at same time. This type of coordination is common when handling large, heavy or complex components requiring multiple contact points.

For example, in automotive body assembly, two robots may hold and position large panel while another robot performs welding. Similarly, dual-arm robotic systems may assemble components that require simultaneous alignment and fastening. Cooperative coordination demands precise synchronization of motion and force control so that robots do not apply conflicting actions on part.

Key characteristics of cooperative coordination include:

- Shared manipulation of same object
- Simultaneous motion execution
- Tight synchronization requirement
- High communication between robots

Although cooperative coordination increases capability of system, it also increases control complexity because robots must maintain relative position and timing accuracy.

2. Distributed Coordination

In distributed coordination, each robot performs its own task independently but shares common workspace, tools or resources with other robots. There is no direct physical cooperation on same object, however robots must coordinate to avoid collision and resource conflict.

For instance, in a flexible manufacturing cell, one robot may load parts into machine while another robot unloads finished parts and third robot performs inspection. All robots operate in same area and may access same conveyor or fixture. Therefore scheduling and motion planning must be coordinated.

Characteristics of distributed coordination include:

- Independent task execution
- Shared environment or equipment
- Local decision making with global awareness
- Moderate synchronization requirement

Distributed coordination is widely used in reconfigurable production lines because it provides flexibility and scalability. New robots can be added to system with minimal modification if proper coordination protocols exist.

3. Sequential Coordination

Sequential coordination occurs when robots perform tasks in a predefined order along production sequence. Output of one robot becomes input to next robot. This type resembles traditional assembly line but with robotic stations instead of manual stations.

For example, in electronic assembly line, first robot places component on PCB, second robot solders connections, third robot inspects solder joints and fourth robot performs packaging. Each robot must wait until previous robot finishes its operation before starting next step. Timing synchronization is therefore essential.

Characteristics of sequential coordination include:

- Ordered task execution
- Dependency between robots
- Workflow-based synchronization
- Predictable process flow

Sequential coordination is relatively simple to implement but may create bottlenecks if one robot is slower than others. In reconfigurable lines, sequence may change when product type changes, requiring flexible scheduling.

4. Parallel Coordination

In parallel coordination, multiple robots perform similar or different tasks simultaneously on same or different products to increase throughput. Parallelism is especially useful in high-volume manufacturing where cycle time must be minimized.

For example, several pick-and-place robots may simultaneously load components onto conveyor, or multiple assembly robots may work on different sections of same product concurrently. Parallel coordination distributes workload among robots, reducing processing time per unit.

Characteristics of parallel coordination include:

- Simultaneous operation of robots
- Workload sharing
- Increased productivity
- Need for collision avoidance

Parallel coordination requires efficient spatial planning because robots often operate close to each other. Proper allocation of workspace zones and synchronized trajectories are necessary to prevent interference.

Table 1: Coordination Types in Production Lines

Coordination Type	Description	Example
Cooperative	Robots share same task	Dual-arm assembly
Distributed	Independent tasks in shared area	Multi-station handling
Sequential	Tasks in order	Assembly line stages
Parallel	Same task simultaneously	Multiple pick robots

COORDINATION ARCHITECTURES

Coordination architecture defines how robots communicate and make decisions. Three main architectures are used in manufacturing.

Centralized Coordination

A central controller assigns tasks and plans paths for all robots. Robots act as executors.

Advantages:

- Global optimization
- Easier monitoring
- Predictable behavior

Limitations:

- Single point failure
- Limited scalability
- Communication load

Centralized control suits small or medium production cells.

Decentralized Coordination

Each robot has local controller and makes decisions independently using shared information.

Advantages:

- High scalability
- Fault tolerance
- Flexible adaptation

Limitations:

- Complex algorithms
- Possible conflicts

This architecture is suitable for large reconfigurable lines.

Hybrid Coordination

Combination of centralized planning and local autonomy. High-level decisions are centralized while low-level actions are local.

Hybrid architecture is common in Industry 4.0 smart factories.




Figure 1: Multi-Robot Coordination Architectures

TASK ALLOCATION IN MULTI-ROBOT PRODUCTION

Task allocation determines which robot performs which operation. In reconfigurable lines, tasks change frequently so dynamic allocation is required.

Static Task Allocation

Tasks are pre-assigned before production starts. Suitable for stable lines but not flexible.

Dynamic Task Allocation

Robots receive tasks during operation based on availability and workload. Improves adaptability.

Market-Based Allocation

Robots bid for tasks based on cost or time. Controller assigns to best robot. Widely used in flexible manufacturing.

Table 2: Task Allocation Methods

Method	Characteristics	Suitability
Static	Predefined	Fixed lines
Dynamic	Real-time	Reconfigurable
Market-based	Cost optimization	Multi-robot
Priority-based	Urgent tasks first	Assembly

PATH PLANNING AND COLLISION AVOIDANCE

In shared workspace, robots must move without collision. Reconfigurable lines increase complexity because layout changes.

Offline Path Planning

Paths computed before operation using CAD models. Works when environment static.

Online Path Planning

Robots adjust paths in real-time using sensors. Needed in dynamic production lines.

Multi-Robot Collision Avoidance

Methods include:

- Time scheduling of motions
- Velocity coordination
- Safe zones
- Predictive trajectory planning

Real-time coordination reduces idle time and improves safety.

COMMUNICATION IN MULTI-ROBOT SYSTEMS

Communication enables robots to share state, position and task information.

Wired Communication

Industrial Ethernet ensures reliable and fast data exchange. Used in structured production cells.

Wireless Communication

Wi-Fi or 5G allows flexible layout reconfiguration. Important for mobile robots.

Communication Challenges

- Latency
- Packet loss
- Synchronization errors

Reliable communication is essential for coordinated motion.

CONTROL STRATEGIES FOR COORDINATION

Control strategies ensure robots follow assigned tasks and maintain synchronization.

Leader-Follower Control

One robot acts leader and others follow trajectory. Used in cooperative manipulation.

Behavior-Based Control

Robots react to environment and other robots using simple rules.

Distributed Control

Each robot computes control based on local data and shared info.

AI-Based Coordination Control

Machine learning and reinforcement learning enable adaptive coordination in changing production lines.

APPLICATIONS IN RECONFIGURABLE PRODUCTION LINES

Multi-robot coordination is applied in many manufacturing sectors.

Assembly Lines

Multiple robots assemble different parts simultaneously or cooperatively. Improves speed and precision.

Material Handling

Robots transport parts between stations. Coordinated routing reduces congestion.

Inspection Systems

Robots inspect products from different angles concurrently.

Flexible Manufacturing Cells

Cells can be reconfigured for new products by updating robot coordination programs.

Table 3: Industrial Applications

Industry	Application	Coordination Type
Automotive	Body assembly	Cooperative
Electronics	PCB handling	Parallel
Packaging	Sorting	Distributed
Aerospace	Component positioning	Leader-follower

BENEFITS OF MULTI-ROBOT COORDINATION

Proper coordination in reconfigurable lines provides several advantages:

- Increased productivity
- Reduced cycle time
- Improved flexibility
- Higher equipment utilization
- Adaptability to new products
- Reduced human intervention

Multi-robot systems also allow redundancy: if one robot fails others can compensate.

CHALLENGES IN RECONFIGURABLE MULTI-ROBOT SYSTEMS

Despite benefits, several challenges remain.

Dynamic Environment

Frequent layout changes require fast re-planning.

Real-Time Synchronization

Robots must maintain timing accuracy to avoid conflicts.

Scalability

Coordination complexity increases with robot number.

Safety

Human-robot coexistence needs safe coordination.

Communication Reliability

Wireless networks may cause delays.

FUTURE TRENDS

Research is moving toward intelligent and autonomous coordination.

AI-Driven Coordination

Learning algorithms optimize task allocation and path planning automatically.

Digital Twin Integration

Virtual models simulate robot coordination before deployment.

Swarm Robotics in Manufacturing

Large numbers of small robots cooperate like swarm systems.

Human-Robot-Multi-Robot Collaboration

Humans and multiple robots working together in flexible production cells.

DISCUSSION

Multi-robot coordination is key enabler of reconfigurable manufacturing. Traditional centralized control is insufficient for highly dynamic production lines. Distributed and hybrid

architectures provide better scalability and robustness. Real-time sensing and communication technologies support adaptive coordination.

Task allocation and path planning are major research areas. Market-based and AI-based approaches show promising performance in dynamic environments. However industrial adoption requires reliability, safety certification and standardization.

Integration with Industry 4.0 technologies such as IoT, digital twin and cyber-physical systems will further enhance coordination capabilities. Future factories will rely heavily on teams of robots working cooperatively in modular production systems.

CONCLUSION

Reconfigurable production lines demand flexible and adaptive automation solutions. Multi-robot coordination enables robots to cooperate efficiently in such dynamic manufacturing environments. This paper reviewed coordination architectures, task allocation methods, path planning strategies, communication systems and control techniques for multi-robot production lines. Applications across industries demonstrate significant improvements in productivity and flexibility. However challenges remain in scalability, safety and real-time adaptability.

Future research should focus on AI-based coordination, digital twin integration and human-robot multi-robot collaboration. Effective coordination strategies will be essential for next generation smart factories and mass-customized production systems.

REFERENCES

1. Koren, Y., Heisel, U., Jovane, F., et al. "Reconfigurable Manufacturing Systems." CIRP Annals, 1999.
2. Parker, L. E. "Alliance: An Architecture for Fault Tolerant Multi-Robot Cooperation." IEEE Transactions on Robotics, 1998.
3. Gerkey, B., Mataric, M. "Multi-Robot Task Allocation: A Review." Autonomous Robots, 2004.
4. Cao, Y., Fukunaga, A., Kahng, A. "Cooperative Mobile Robotics: Antecedents and Directions." Autonomous Robots, 1997.

5. Kruger, J., Lien, T., Verl, A. "Cooperation of Human and Machines in Assembly Lines." CIRP Annals, 2009.
6. Wang, L., Törngren, M., Onori, M. "Current Status and Advancement of Cyber-Physical Systems in Manufacturing." Journal of Manufacturing Systems, 2015.
7. Leitão, P. "Agent-Based Distributed Manufacturing Control." Engineering Applications of AI, 2009.
8. Chen, B., et al. "Multi-Robot Coordination in Intelligent Manufacturing Systems." Robotics and Computer-Integrated Manufacturing, 2018.
9. Villani, V., et al. "Survey on Human-Robot Collaboration in Industrial Settings." Mechatronics, 2018.
10. Zhong, R. Y., Xu, X., Klotz, E., Newman, S. T. "Intelligent Manufacturing in the Context of Industry 4.0." Engineering, 2017.