MANTECH Publications

International Journal of Robotics and Autonomous Systems
Volume 11, Issue 1, January-June 2026
ISSN: 3107-7382 (Online)

Reactive Obstacle Avoidance for Mobile Robots Using Artificial Potential Fields

Sivakumar R. Natarajan[1], Lavanya S. Gopalakrishnan[2]

ABSTRACT

A mobile robot moving through an environment must avoid the obstacles it encounters, and while a path can be planned in advance when the environment is known, a robot often needs to react to obstacles as it senses them, steering around them on the fly; the artificial potential field method provides a simple and elegant means of doing so. This study examines reactive obstacle avoidance using artificial potential fields and the well-known difficulty of local minima that attends it. The method treats the goal as exerting an attractive pull on the robot and each obstacle as exerting a repulsive push, the robot moving at each instant in the direction of the combined force, and a robot was navigated from a start to a goal among obstacles under this scheme. The robot reached the goal by a smooth path that bent away from each obstacle as it approached, the repulsive push from the obstacles steering it clear while the attractive pull drew it onward, the whole behaviour emerging simply from the sum of the forces without any path being planned in advance. The method was computationally light and reacted naturally to the obstacles, which makes it attractive for real-time avoidance, but it is known to suffer from local minima, configurations where the attractive and repulsive forces cancel and the robot halts short of the goal, for instance directly before a large obstacle or in a concave one. The study shows that artificial potential fields provide effective and lightweight reactive obstacle avoidance, well suited to steering around obstacles in real time, while cautioning that the local-minimum problem must be addressed for reliable navigation, and it discusses the forces involved and the means of escaping local minima.

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

KEYWORDS: *Obstacle avoidance, Artificial potential fields, Reactive navigation, Mobile robots, Local minima, Attractive force, Repulsive force, Real-time navigation, Autonomous robots*

INTRODUCTION

A mobile robot moving through its environment must avoid colliding with the obstacles around it. When the environment is fully known in advance, a collision-free path can be planned before the robot sets out; but often the robot does not have a complete map, or the environment changes, and it must instead react to obstacles as its sensors detect them, steering around them as it goes (10). This reactive obstacle avoidance must be quick, since the robot must respond to obstacles in real time as it moves, and it must produce sensible motion that keeps the robot clear of obstacles while progressing toward its goal.

The artificial potential field method, introduced for exactly this purpose, provides a simple and elegant means of reactive avoidance (1). It works by an intuitive analogy: the goal is imagined to attract the robot, as if pulling it toward itself, while each obstacle is imagined to repel the robot, as if pushing it away. At each instant the robot feels the sum of these attractive and repulsive influences as a combined force, and it moves in the direction of that force. The result is that the robot is drawn toward the goal but pushed away from obstacles as it nears them, steering around them naturally, and this behaviour emerges from the forces alone, without any path being computed in advance.

The method is valued for its simplicity and speed, but it is well known to have a characteristic weakness: local minima, places where the attractive and repulsive forces happen to cancel, leaving no net force, so that the robot stops short of the goal even though it has not arrived (2). This paper examines reactive obstacle avoidance using artificial potential fields and this difficulty of local minima. A robot is navigated from a start to a goal among obstacles under the potential field scheme, and its behaviour is observed. The aim is to demonstrate the effectiveness and lightness of the method, to bring out the local-minimum problem, and to discuss the forces involved and the means of escaping local minima.

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

LITERATURE REVIEW

The artificial potential field method has been studied extensively since it was introduced for real-time obstacle avoidance (1), and the literature establishes both its appeal and its limitations. Its appeal lies in its simplicity and speed: the robot's motion is computed from a simple sum of forces, attractive from the goal and repulsive from the obstacles, which is quick enough for real-time control and produces smooth, sensible avoidance behaviour without planning a path (10). This makes it well suited to reacting to obstacles as they are sensed.

The Method and Its Limitations

The literature describes the method and its known difficulties:

- The goal exerts an attractive force and each obstacle a repulsive force; the robot moves along their sum (1).
- The method is computationally light and reacts in real time, producing smooth avoidance.
- Its chief weakness is local minima, where forces cancel and the robot halts short of the goal (2).
- Remedies include modified potential functions, navigation functions free of local minima, and alternative reactive schemes (4, 5, 6).

A recurring theme is that potential fields give effective and lightweight reactive avoidance but require measures to handle local minima for reliable navigation.

The local-minimum problem is the most studied limitation: because the robot moves only according to the local sum of forces, it can reach a configuration where the attractive and repulsive forces exactly oppose and cancel, leaving it stuck short of the goal, as can happen directly in front of a large obstacle or within a concave one (2). The literature offers several remedies: potential functions designed to reduce the occurrence of minima (4); navigation functions constructed to have no local minima other than the goal, guaranteeing arrival in suitable spaces (5); and alternative reactive methods, such as those that steer toward gaps between obstacles or that account for the robot's dynamics (3, 6). Standard texts set the method in the wider context of reactive navigation (9, 10), and related approaches build histograms of obstacle directions to choose a heading (3).

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

RESEARCH GAP

Although the potential field method is well studied, a concise demonstration that navigates a robot to a goal among obstacles under the method, showing the smooth force-driven avoidance it produces, while explaining the local-minimum problem, remains useful as a clear illustration. There is therefore value in a study that shows the emergent avoidance behaviour and relates both its strengths and its local-minimum weakness to the forces involved.

OBJECTIVES

The objectives of this study are:

- To navigate a mobile robot from a start to a goal among obstacles using the artificial potential field method.
- To observe the avoidance behaviour produced by the attractive and repulsive forces.
- To bring out the local-minimum problem that can leave the robot stuck short of the goal.
- To discuss the forces involved and the means of escaping local minima.

METHODOLOGY

1. The Potential Field

The artificial potential field method was applied to navigate a mobile robot from a start to a goal among obst

acles (1). The goal exerted an attractive force drawing the robot toward it, and each obstacle exerted a repulsive force pushing the robot away, the repulsion growing stronger as the robot approached the obstacle and acting only within a limited range. At each step the robot moved in the direction of the combined force, the sum of the attraction and the repulsions. The forces are summarised in Table 1.

Table 1: Forces in the artificial potential field

Force	Source and effect

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

Force	Source and effect
Attractive force	From the goal, draws the robot toward it
Repulsive force	From each obstacle, pushes the robot away
Range of repulsion	Acts only within a limited distance of an obstacle
Robot motion	Along the sum of attractive and repulsive forces

2. Evaluation

The robot was navigated from the start to the goal under the potential field, and its path was observed: whether it reached the goal, how it behaved as it approached each obstacle, and the smoothness and clearance of its path. The behaviour was related to the forces acting, and the conditions, under which the method can fail through local minima, where the forces cancel, were considered, so that both the strengths and the limitation of the method could be assessed.

RESULTS AND FINDINGS

The robot reached the goal by a smooth path that avoided the obstacles, as shown in Figure 1. As the robot approached each obstacle, the repulsive force from that obstacle grew and pushed it aside, bending its path away from the obstacle, while the attractive force from the goal continued to draw it onward, so that the path curved smoothly around each obstacle and then resumed toward the goal. This avoidance behaviour emerged entirely from the sum of the forces at each instant, with no path planned in advance, illustrating the simplicity and elegance of the method (1).

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved




Figure 1: Robot path navigating among obstacles under the artificial potential field

The method was computationally light, the robot's motion being computed from a simple sum of forces at each step; fast enough for real-time reaction, and it produced natural, smooth avoidance with good clearance from the obstacles. These qualities make it attractive for steering around obstacles in real time. The method is known, however, to suffer from local minima: at certain configurations the attractive and repulsive forces cancel, leaving no net force, and the robot then halts short of the goal, as can occur directly before a large obstacle or within a concave one (2). In the present navigation, no such minimum was encountered, but the possibility is inherent in the method. The behaviour is summarised in Table 2.

Table 2: Behaviour of the potential field navigation

Aspect	Observation
Goal reached	Yes, by a smooth path
Behaviour near obstacles	Path bends away as repulsion grows
Computational cost	Low; a sum of forces each step
Known limitation	Local minima where forces cancel

DISCUSSION

The results show that artificial potential fields provide effective and lightweight reactive obstacle avoidance. The strength of the method is that sensible avoidance behaviour emerges

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

from a very simple rule: the robot need only compute, at each instant, the attractive force toward the goal and the repulsive forces from the obstacles it senses, and move along their sum (1). This requires little computation and no advance planning, so it is fast enough for real-time control and reacts naturally to obstacles as they are encountered, bending the robot's path smoothly around them. These qualities make the method well suited to reactive avoidance, especially where the environment is not fully known beforehand or changes as the robot moves (10).

The local-minimum problem is the price of this simplicity and the chief caution in using the method. Because the robot follows only the local sum of forces, with no view of the wider environment, it can be led into a configuration where the attractive and repulsive forces exactly cancel; there it feels no net force and stops, even though it has not reached the goal (2). Such minima arise predictably in certain situations, such as directly between the goal and a large obstacle, where the push from the obstacle balances the pull toward the goal, or inside a concave obstacle that surrounds the robot with repulsion. The robot is then trapped, and the basic method offers no way out, which makes it unreliable for general navigation unless the problem is addressed.

Several means of addressing local minima exist, and they define how the method is made reliable in practice. Potential functions can be designed to reduce the occurrence of minima (4), and navigation functions can be constructed that have no local minima other than the goal, guaranteeing arrival in suitable environments, at the cost of greater complexity (5). Alternatively, the robot can detect when it is stuck and take deliberate action to escape, such as following the boundary of an obstacle until it can resume, or other reactive schemes can be used that are less prone to trapping, such as steering toward gaps between obstacles or accounting for the robot's motion (3, 6). The practical conclusion is that artificial potential fields are an effective and efficient basis for reactive obstacle avoidance, well suited to real-time steering around obstacles, provided the local-minimum problem is handled by one of these means; the main caveats are that the basic method can become trapped and that the behaviour depends on the choice of forces and their parameters.

LIMITATIONS

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

The following limitations apply to this study:

- The basic method can become trapped in local minima, which must be addressed for reliable navigation.
- The behaviour depends on the choice of attractive and repulsive forces and their parameters.
- The demonstration used a particular arrangement of obstacles in which no local minimum arose.
- The study considered reactive avoidance and not the robot's detailed dynamics or sensing of obstacles.

FUTURE SCOPE

Future work could extend the present study as follows:

- Implementation and comparison of methods for escaping local minima, including navigation functions and boundary-following.
- Evaluation in environments, such as concave obstacles, where local minima are likely.
- Combination of reactive potential fields with global planning to gain both safety and completeness.
- Inclusion of the robot's dynamics and real sensing of obstacles.
- Extension to dynamic environments with moving obstacles.

CONCLUSION

Reactive obstacle avoidance using artificial potential fields, and the difficulty of local minima that attends it, were examined by navigating a robot from a start to a goal among obstacles under the method. The robot reached the goal by a smooth path that bent away from each obstacle as the repulsive force grew while the attractive force drew it onward, the avoidance behaviour emerging simply from the sum of the forces without any advance planning, and the method proved computationally light and naturally reactive. The study shows that artificial

Page 20-28 © MANTECH PUBLICATIONS 2026. All Rights Reserved

potential fields provide effective and lightweight reactive obstacle avoidance, well suited to steering around obstacles in real time, while cautioning that the local-minimum problem, where the forces cancel and the robot halts short of the goal, must be addressed by modified potentials, navigation functions, or escape behaviours for reliable navigation, with the behaviour depending on the choice of forces and their parameters.

REFERENCES

1. Khatib, O. (1986). Real-time obstacle avoidance for manipulators and mobile robots. *The International Journal of Robotics Research*, 5(1), 90–98.
2. Koren, Y., & Borenstein, J. (1991). Potential field methods and their inherent limitations for mobile robot navigation. *Proceedings of the IEEE International Conference on Robotics and Automation*, 1398–1404.
3. Borenstein, J., & Koren, Y. (1991). The vector field histogram: Fast obstacle avoidance for mobile robots. *IEEE Transactions on Robotics and Automation*, 7(3), 278–288.
4. Ge, S. S., & Cui, Y. J. (2000). New potential functions for mobile robot path planning. *IEEE Transactions on Robotics and Automation*, 16(5), 615–620.
5. Rimon, E., & Koditschek, D. E. (1992). Exact robot navigation using artificial potential functions. *IEEE Transactions on Robotics and Automation*, 8(5), 501–518.
6. Fox, D., Burgard, W., & Thrun, S. (1997). The dynamic window approach to collision avoidance. *IEEE Robotics & Automation Magazine*, 4(1), 23–33.
7. Warren, C. W. (1989). Global path planning using artificial potential fields. *Proceedings of the IEEE International Conference on Robotics and Automation*, 316–321.
8. Hwang, Y. K., & Ahuja, N. (1992). A potential field approach to path planning. *IEEE Transactions on Robotics and Automation*, 8(1), 23–32.
9. Latombe, J. C. (1991). *Robot motion planning*. Kluwer Academic Publishers.
10. Siegwart, R., Nourbakhsh, I. R., & Scaramuzza, D. (2011). *Introduction to autonomous mobile robots* (2nd ed.). MIT Press.

***Author for Correspondence**
Sivakumar R. Natarajan
E-mail: siva76natarajan@yahoo.com

[1]Associate Professor, Department of Mechanical Engineering, Christian College of Engineering, Erode, Tamil Nadu
[2]Assistant Professor, Department of Robotics and Automation, Christian College of