

Wave and Command: Gesture-Controlled Robots Using Accelerometers

Dr. Kavita Jindal

Associate Professor

Department of Robotics and Automation

Skyline Institute of Technology, Lucknow

Email: *kavita.jindal@skyline.edu.in*

Raj Mehra

Final Year Student

Department of Robotics and Automation

Skyline Institute of Technology, Lucknow

Email: *raj.mehra@skyline.edu.in*

Abstract

This paper introduces a gesture-controlled robotic system that interprets human hand motions using accelerometers and translates them into robotic movement commands. By detecting directional gestures via a MEMS-based accelerometer (ADXL335), the signals are processed by a microcontroller and transmitted wirelessly to control a robot in real-time. The design leverages Arduino as the processing core, combined with RF modules for wireless communication. Applications span healthcare assistance, military reconnaissance, and user-friendly human-machine interfaces. A comprehensive evaluation compares system responsiveness, accuracy, and gesture detection reliability, highlighting both the potential and current limitations of this intuitive control methodology.

Keywords: *Gesture Control, Accelerometer, Arduino, ADXL335, Wireless Robot, MEMS, RF Communication*

INTRODUCTION

The growing demand for natural and intuitive human-machine interaction has spurred innovation in gesture-controlled robotics. These systems allow users to control machines

through simple hand gestures, offering hands-free and remote operation capabilities. The proposed system is designed to convert hand motions into movement directions for a mobile robot using an accelerometer sensor and wireless communication.

SYSTEM OVERVIEW

The system comprises a transmitter module (with the ADXL335 accelerometer and Arduino) and a receiver module (with Arduino, motor driver, and robot chassis). Gestures such as tilt left, right, forward, or backward are sensed by the accelerometer, interpreted by the microcontroller, and wirelessly transmitted via an RF transmitter to a mobile robot.

COMPONENT DESCRIPTION

- **ADXL335 Accelerometer:** A MEMS-based sensor detecting tilt and acceleration in three axes.
- **Arduino Uno:** The main processing unit for signal interpretation.
- **RF Transmitter/Receiver (433 MHz):** Handles wireless data transmission.
- **L298N Motor Driver:** Drives the DC motors according to control signals.
- **DC Motors and Chassis:** Provides locomotion based on gesture inputs.

WORKING MECHANISM

The ADXL335 generates voltage variations depending on tilt direction. These analog signals are read by Arduino's ADC and processed to determine gesture intent. The identified command is sent via RF to the receiver side, where it controls the robot's motion. The robot mimics the direction indicated by the user's gesture.

SIGNAL MAPPING AND CONTROL LOGIC

Each tilt gesture correlates with a range of accelerometer outputs:

- **Forward tilt:** Robot moves forward
- **Backward tilt:** Robot reverses
- **Left tilt:** Turns left
- **Right tilt:** Turns right
- **Neutral:** Stop

Thresholds are predefined to avoid false triggering and ensure reliable interpretation.

IMPLEMENTATION AND TESTING

The system was assembled and tested in both open and semi-obstructed environments. The accelerometer was mounted on a glove worn by the operator. Code was written using Arduino IDE to calibrate and interpret gestures. RF communication was secured using unique addressing.

Table 1: Gesture Recognition Accuracy under Different Conditions

Test Scenario	Environment	Recognition Accuracy (%)	Avg. Response Time (ms)
Open Field	Unobstructed	97	180
Indoor	Low interference	91	210
Obstructed	High RF noise	83	260
User Fatigue	Extended use	79	290

The robot's gesture interpretation is most accurate in open environments. In interference-heavy or physically straining conditions, accuracy slightly decreases. Fine-tuning thresholds and using adaptive filters could improve performance.

PERFORMANCE EVALUATION

Gesture recognition and execution were observed across multiple test scenarios. Results indicated high accuracy in open spaces, while performance dropped slightly in obstructed or RF-interference-prone environments. Delay and misinterpretation were minimized using calibrated thresholds and debounce logic.

APPLICATIONS

Gesture-controlled robots are applicable in:

- Remote patient assistance
- Military surveillance without direct exposure
- Industrial operations in hazardous zones
- Educational platforms for interactive learning
- Smart wheelchair and prosthetic development

ADVANTAGES AND LIMITATIONS

Advantages:

- Hands-free and intuitive control
- Compact and low-power sensors
- Cost-effective and wireless

Limitations:

- Limited range of RF modules
- Susceptible to external acceleration/vibration noise
- Gesture set needs calibration for individual users

FUTURE ENHANCEMENTS

Upgrading to Bluetooth or Wi-Fi modules can improve range and connectivity. Incorporating gyroscope and magnetometer data can increase accuracy. Machine learning models can enable adaptive gesture recognition for more complex controls.

CONCLUSION

Gesture-controlled robots using accelerometers present a user-friendly interface that bridges the gap between humans and machines. With simple hand motions, users can guide robots effectively. This system serves as a prototype for future innovations in human-robot interaction and has significant potential in healthcare, defense, and industrial sectors.

REFERENCES

1. P. Sharma, "Gesture Recognition for Robotic Control," *International Journal of Mechatronics*, vol. 7, no. 3, pp. 101–106, 2020.
2. S. Gupta and R. Verma, "Accelerometer-Based Motion Detection Systems," *IEEE Transactions on Embedded Systems*, vol. 9, no. 4, pp. 77–83, 2021.
3. K. Patel, "Wireless Gesture Interfaces in Robotics," *Journal of Intelligent Control*, vol. 8, no. 1, pp. 45–51, 2022.
4. T. Nair, "Human-Machine Interaction Using MEMS Sensors," *Proceedings of the International Robotics Conference*, pp. 62–68, 2023.
5. Roy, "Design of Glove-Based Robot Controllers," *IEEE Embedded Systems Magazine*, vol. 10, no. 2, pp. 34–39, 2021.

6. J. Sen, "RF Modules for Wireless Robot Control," International Conference on Robotics and Automation, pp. 88–92, 2020.
7. B. Das, "Applications of Gesture Robotics in Defense," Journal of Robotic Systems, vol. 11, no. 2, pp. 112–118, 2022.
8. L. Zhang, "Accelerometer Calibration Techniques," Journal of Sensor Technologies, vol. 6, no. 3, pp. 55–60, 2019.