MANTECH Publications

Journal of Converging Technologies in Intelligent
Volume 1, Issue 1, January-April 2025

AI-Driven Digital Twin Technology for Predictive Maintenance in Smart Manufacturing Environments: A Comprehensive Review of Architectures, Algorithms, and Industrial Applications

Arindam K. Basu[1], Sneha R. Dutta[2], Rajarshi S. Sen[3], Moumita D. Pal[4]

ABSTRACT

Unplanned equipment downtime remains one of the most costly disruptions in discrete and process manufacturing, and conventional reactive and time-based preventive strategies are poorly matched to the stochastic degradation behaviour of modern cyber-physical production systems. Digital twin (DT) technology — a continuously synchronised virtual representation of a physical asset — combined with artificial intelligence (AI) offers a route to condition-aware, prognostic maintenance. This review-based study synthesises peer-reviewed literature on AI-driven digital twins for predictive maintenance (PdM) in smart manufacturing, following a structured protocol of question formulation, source screening, thematic coding, and cross-study comparison. A five-layer reference architecture and a closed-loop PdM workflow are proposed, and the reviewed approaches are compared across modelling paradigm, learning technique, and deployment maturity. The synthesis indicates that hybrid twins, which couple physics-based models with deep-learning prognostics, offer the most favourable balance of early fault detection, adaptability, and interpretability, whereas purely data-driven pipelines are easier to deploy but depend heavily on labelled failure data. Persistent barriers include data scarcity, synchronisation latency, interoperability gaps, and the absence of standardised validation benchmarks. Promising research directions include physics-informed learning, edge-deployed and federated twins, and uncertainty-aware decision support. The paper provides engineers and researchers with a consolidated technical reference for designing and evaluating DT-based maintenance systems.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

KEYWORDS: *Digital twin, Predictive maintenance, Smart manufacturing, Industry 4.0, Remaining useful life, Deep learning, Cyber-physical systems, Physics-informed machine learning, Condition monitoring, Fault diagnosis*

INTRODUCTION

Smart manufacturing integrates sensing, networking, computation, and automation so that production assets can report their condition, exchange information, and adapt to changing demand. Within this paradigm, maintenance has shifted from a cost centre to a strategic determinant of availability, quality, and energy efficiency. Reactive maintenance, in which equipment is repaired after failure, causes unplanned stoppages and secondary damage, while time-based preventive maintenance replaces components on fixed schedules irrespective of their actual health and therefore wastes remaining life [4]. Condition-based and predictive maintenance address both shortcomings by acting on measured degradation indicators, and they form a core service of the Industry 4.0 cyber-physical architecture [3], [15].

The digital twin concept provides a natural integrating framework for such strategies. Grieves and Vickers described a virtual information construct that mirrors a physical product across its lifecycle [1], and Glaessgen and Stargel proposed an integrated, multiphysics, probabilistic simulation that continuously ingests sensor data and fleet history to mirror the life of a specific vehicle [8]. In manufacturing, Kritzinger et al. distinguished a digital model, a digital shadow, and a full digital twin according to whether data flow between the physical and virtual objects is manual or automatic in one or both directions [7]. Tao et al. further showed that digital twins extend cyber-physical systems by emphasising high-fidelity models, bidirectional interaction, and service-oriented use of data [2], [25].

Advances in machine learning have simultaneously changed what a twin can do. Deep neural networks learn degradation features directly from raw vibration, current, and acoustic signals [5], [6], and recurrent architectures model long-range temporal dependence for prognostics [16]. Coupling these learners with a twin that carries physical knowledge of the asset promises prognostics that are accurate, adaptable, and explainable. The central problem addressed in this paper is therefore how AI-driven digital twins can be architected, trained, validated, and deployed to deliver reliable predictive maintenance in real manufacturing environments, and where current knowledge is still insufficient. The remainder of the paper reviews the literature, identifies gaps, states objectives, describes the review method, synthesises findings, and discusses engineering implications.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

LITERATURE REVIEW

Evolution And Taxonomy Of Digital Twins

Early twin research originated in aerospace, where physical testing of every vehicle was infeasible [8]. Subsequent surveys have mapped the concept onto industrial practice. Tao et al. surveyed industrial twins and identified modelling, data fusion, and service provision as the principal technical themes [2]. Jones et al. systematically characterised the twin by its physical entity, virtual entity, physical-to-virtual and virtual-to-physical connections, and associated data, highlighting that many reported implementations lack true bidirectional control [23]. Qi et al. organised enabling technologies into a five-dimension model and catalogued supporting tools [9], while Lu et al. proposed a reference model for twin-driven smart manufacturing and listed open research issues in data management, interoperability, and security [11]. Fuller et al. emphasised that data quality, latency, and privacy remain open challenges for real deployments [10].

Predictive Maintenance And Condition Monitoring

Jardine et al. defined condition-based maintenance as a three-step process of data acquisition, data processing, and maintenance decision-making, with diagnostics identifying present faults and prognostics predicting future failure [4]. Lee et al. embedded this logic in the 5C architecture of connection, conversion, cyber, cognition, and configuration, and later argued for smart analytics that convert machine data into actionable service decisions [3], [15]. Zonta et al. systematically reviewed predictive maintenance in Industry 4.0 and concluded that the field is dominated by machine-learning studies on rotating machinery, with limited attention to system-level integration [18]. Lei et al. traced the evolution of machine-learning-based fault diagnosis and outlined a roadmap towards intelligent, transferable diagnosis under limited labelled data [5].

AI Techniques In Twin-Based Maintenance

Zhao et al. reviewed deep architectures for machine health monitoring, including autoencoders, convolutional networks, and recurrent networks, and reported that automatic feature learning reduces dependence on hand-crafted indicators [6]. Long short-term memory networks, introduced by Hochreiter and Schmidhuber, mitigate vanishing gradients and are widely used for remaining useful life (RUL) regression [16]. Public run-to-failure benchmarks such as the turbofan engine simulation dataset of Saxena et al. have enabled comparison of such models, although they originate from simulation rather than shop-floor practice [17]. Rasheed et al. argued that purely data-driven models extrapolate poorly beyond their training envelope and

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

advocated hybrid analytics that combine physics with data [22]. Karniadakis et al. consolidated physics-informed machine learning, in which governing equations constrain the learned model, as a principled response to data scarcity [21].

Reported Industrial Implementations

Aivaliotis et al. presented a methodology that couples physics-based simulation models with sensor data to estimate the remaining useful life of manufacturing equipment, demonstrating the value of model-based prognostics when failure histories are scarce [20]. Wang et al. proposed a twin framework for rotating machinery fault diagnosis that combines model-based simulation with data-driven learning [24]. Liu et al. demonstrated web-based twin modelling and remote control of cyber-physical production systems, illustrating the connectivity needed for real-time synchronisation [12]. Errandonea et al. reviewed maintenance-oriented twins and observed that most contributions remain conceptual or at laboratory scale, with few validated industrial roll-outs [19].

RESEARCH GAP

Although twin and predictive-maintenance literatures are both substantial, their intersection remains fragmented. First, most studies address a single component class, typically bearings or gearboxes, and do not generalise to line-level or plant-level assets [18], [19]. Second, benchmark validation relies on simulated or laboratory datasets, so claims of prognostic accuracy are rarely tested under real noise, drift, and operating-condition changes [17]. Third, the synchronisation fidelity of the twin, meaning how closely and how quickly the virtual state tracks the physical state, is seldom quantified, even though prognostic quality depends on it [10], [23]. Fourth, few works compare physics-based, data-driven, and hybrid twins within a unified evaluation framework, which prevents practitioners from selecting an approach on evidence [21], [22]. Finally, deployment guidance for small and medium manufacturers with limited data and computing budgets is largely absent. This review addresses these gaps by consolidating architectures, algorithms, and maturity levels into a common comparative framework.

OBJECTIVES

- To synthesise the architectures, enabling technologies, and data flows of AI-driven digital twins used for predictive maintenance in smart manufacturing.
- To compare physics-based, data-driven, and hybrid modelling paradigms and the AI techniques employed for fault diagnosis and remaining useful life prognosis.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- To propose a layered reference architecture and a closed-loop workflow that integrate twin synchronisation, AI analytics, and maintenance decision support.
- To identify technical, organisational, and validation barriers to industrial adoption, and to outline practical deployment guidance.
- To define a research agenda for scalable, trustworthy, and standardised twin-based maintenance systems.

METHODOLOGY

Review Design And Protocol

This work is a review-based study that follows a structured protocol inspired by the systematic-review guidelines of Kitchenham and Charters [14] and the transparent-reporting principles of the PRISMA statement [13]. Four research questions guided the synthesis: RQ1, which architectures integrate twins with AI for maintenance; RQ2, which modelling paradigms and learning techniques are used; RQ3, what level of validation and maturity has been demonstrated; and RQ4, which barriers limit adoption. Table 1 summarises the protocol elements. The evidence base comprises the peer-reviewed journal articles, conference papers, and technical reports cited in this paper, selected for relevance, citation influence, and methodological clarity.

Table 1. Review Protocol And Coding Dimensions

Protocol element	Specification
Scope	AI-enabled digital twins for maintenance of manufacturing assets
Source types	Journals, conference papers, technical reports
Inclusion criteria	Twin or digital-shadow concept; maintenance or prognostic objective; clear method description
Exclusion criteria	Non-manufacturing domains without transferable method; opinion pieces without technical content
Coding dimensions	Architecture, modelling paradigm, AI technique, asset type, validation level, barriers

Proposed Reference Architecture

Thematic coding of the architectures reported in the literature [2], [9], [11] yielded the five-layer reference architecture shown in Figure 1. The physical layer comprises machines instrumented with vibration, temperature, current, and acoustic sensors and controlled through

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

PLC and SCADA systems. The edge and connectivity layer performs signal conditioning and protocol translation using standards such as OPC UA and MQTT, thereby supporting the low-latency synchronisation emphasised in [12]. The twin layer maintains a hybrid model that combines first-principles equations with learned components, updated continuously from incoming data. The AI analytics layer performs anomaly detection, fault classification, and RUL estimation, and the decision layer converts prognostic output into maintenance work orders, spare-parts requests, and production re-planning within MES and CMMS platforms.




Figure 1. Five-layer reference architecture of an AI-driven digital twin for predictive maintenance in smart manufacturing.

Closed-Loop Workflow And Analytical Formulation

The operational workflow, illustrated in Figure 2, is a closed loop with five stages: data acquisition, pre-processing and feature extraction, twin state update and calibration, fault diagnosis and RUL prognosis, and maintenance decision and scheduling. Following Jardine et al. [4], RUL at time t is defined as the interval until a health indicator h(t) first crosses a failure threshold h_{th}, that is, $RUL(t) = \inf\{ l > 0 : h(t + l) \geq h_{th} \}$. Because the twin supplies physically meaningful states, h(t) may be a residual between measured and simulated outputs, so that deviation grows as degradation advances. Twin fidelity is expressed as the mean relative

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

synchronisation error, $\varepsilon = (1/N)\,\Sigma\,|y_i - \hat{y}_i| / |y_i|$, where y_i is the measured output and $\hat{y}_i$ the twin-predicted output; this quantity is used in the synthesis as a comparative criterion across studies [10], [23].




Figure 2. Closed-loop predictive maintenance workflow driven by a synchronised digital twin.

RESULTS AND FINDINGS

The synthesis produced four principal findings. The first concerns architecture. Across the reviewed frameworks [2], [9], [11], [19], the layered structure of Figure 1 recurs, and the principal differentiators are the location of analytics (cloud, edge, or both) and the degree of bidirectional control. Reported twins that only visualise sensor data correspond to digital shadows in the taxonomy of Kritzinger et al. [7], whereas fewer works close the loop by returning decisions to the asset [23].

The second finding concerns modelling paradigm and technique. Table 2 compares representative approaches. Physics-based twins provide interpretability and operate with little failure data [20], data-driven pipelines achieve strong classification accuracy when labelled data exist [5], [6], and hybrid frameworks combine both strengths [22], [24]. Table 3 summarises the AI techniques most frequently paired with twins, together with their typical role, strengths, and limitations.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Table 2. Comparison Of Representative Twin-Based Maintenance Approaches

Study	Modelling paradigm	AI / analytics technique	Contribution
Aivaliotis et al. [20]	Physics-based simulation	Model-based RUL estimation	Prognostics with scarce failure data
Wang et al. [24]	Hybrid model and data	Data-driven fault diagnosis	Rotating-machinery diagnosis framework
Lu et al. [11]	Reference model	Data and model fusion	Twin-driven smart-manufacturing model
Liu et al. [12]	Web-based twin	Remote monitoring and control	Real-time connectivity for CPPS
Errandonea et al. [19]	Literature review	Classification of twins	Maturity assessment for maintenance

Table 3. AI Techniques Used With Digital Twins For Predictive Maintenance

Technique	Typical role	Strength	Limitation
CNN [6]	Fault classification from signals	Automatic feature learning	Needs labelled data
LSTM / RNN [16]	RUL regression	Captures temporal dependence	Costly to train; opaque
Autoencoder [6]	Anomaly detection	Works with healthy data only	Threshold selection
Physics-informed NN [21]	Hybrid prognostics	Data efficient; consistent with physics	Requires validated equations
Ensemble methods [5]	Diagnosis, regression	Robust on small data	Limited sequence modelling

The third finding concerns validation. The turbofan dataset of Saxena et al. is the dominant RUL benchmark [17], and many reported accuracies derive from simulated run-to-failure data rather than operating plants. Studies rarely report synchronisation error or decision-level outcomes such as avoided downtime, which limits comparability. The fourth finding concerns maturity. Consistent with [19], most contributions remain at conceptual or laboratory-validated stages, and fully integrated industrial deployments are uncommon.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Figure 3 consolidates the comparison as an indicative qualitative profile of four maintenance approaches across five criteria. The ratings are the authors' synthesis of the qualitative evidence in [4]–[6], [20]–[22] and are not measured data; they are intended to show relative tendencies only. The AI-driven hybrid twin is rated highest for early fault detection, prognostic accuracy, and adaptability, because physical constraints regularise the learner while data correct model mismatch [21], [22]. Reactive and preventive practice scores highest on implementation ease, and physics-based twins on interpretability, reflecting the engineering effort and expertise required to build and validate hybrid twins.




Figure 3. Indicative qualitative capability profile of maintenance approaches (authors' synthesis; not measured data).

DISCUSSION

The findings confirm that the value of a digital twin for maintenance lies less in three-dimensional visualisation than in the continuous reconciliation of a physical model with measured behaviour. The residual between the two is a physically meaningful health indicator, and learning algorithms operate on that residual rather than on raw signals, which improves transferability across machines of the same family [22], [24]. This explains why hybrid approaches handle changing operating conditions better than purely data-driven classifiers, whose accuracy degrades once speed, load, or tooling departs from the training distribution [5].

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

The engineering significance is threefold. First, prognostic lead time enables maintenance to be scheduled in planned windows, reducing unplanned stoppages and avoiding secondary damage [4]. Second, the twin supports what-if evaluation of maintenance actions, such as derating a spindle or rescheduling a batch, before they are applied to the physical asset [11]. Third, a shared virtual representation connects maintenance with production planning, quality, and energy management, so that decisions are optimised at plant level rather than machine level [3].

Practical applications include spindle and tool-wear monitoring on CNC machines, bearing and gearbox prognostics on motors and conveyors, joint and reducer health assessment on industrial robots, and thermal and hydraulic monitoring in forming and moulding equipment [18], [20], [24]. For small and medium enterprises, a staged roadmap is advisable: begin with a digital shadow and condition dashboards on critical assets, add data-driven anomaly detection using healthy-state data, and introduce physics-informed prognostics once failure records and engineering models are available. Lightweight edge inference limits cloud cost and latency, which is important where connectivity and capital budgets are constrained [10]. Organisational readiness, including workforce skills and integration with existing maintenance management systems, is as decisive as algorithmic choice and is frequently underreported in the literature [19].

LIMITATIONS

- The evidence base is restricted to the sources cited, and the review does not claim exhaustive coverage of all published twin and maintenance studies.
- Cross-study comparison is qualitative because the reviewed works use heterogeneous assets, datasets, and metrics; the ratings in Figure 3 are indicative and not statistically derived.
- Many reported results rely on simulated or laboratory data, so conclusions about industrial performance carry uncertainty [17], [19].
- The field evolves rapidly, and recent developments in foundation models and generative AI for maintenance are only partially represented.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

FUTURE SCOPE

- Physics-informed and hybrid learning that embeds governing equations into prognostic networks to improve data efficiency and extrapolation [21], [22].
- Edge-deployed and federated twins that share learned degradation knowledge across plants without exposing proprietary data [10].
- Uncertainty-aware prognostics that provide calibrated confidence intervals for RUL and support risk-based maintenance decisions.
- Open benchmarks built from real industrial run-to-failure data, with standard metrics for synchronisation fidelity and decision-level outcomes [17], [23].
- Standardised interoperable twin models, together with cybersecurity and governance frameworks, to enable multi-vendor integration [11], [12].

CONCLUSION

This review examined AI-driven digital twin technology for predictive maintenance in smart manufacturing and proposed a five-layer reference architecture and a closed-loop workflow that link sensing, twin synchronisation, AI analytics, and maintenance decisions. The synthesis indicates that hybrid twins, which unite physics-based models with deep-learning prognostics, offer the most balanced capability profile, while pure data-driven pipelines remain attractive for rapid deployment and physics-based twins for interpretability. Adoption is constrained by scarce failure data, limited real-world validation, synchronisation latency, and interoperability gaps. Progress will depend on physics-informed learning, edge and federated deployment, uncertainty quantification, and open industrial benchmarks. For practitioners, a staged implementation path beginning with digital shadows on critical assets offers a pragmatic route to realising the benefits of predictive, twin-enabled maintenance.

REFERENCES

1. Grieves M, Vickers J. Digital twin: mitigating unpredictable, undesirable emergent behavior in complex systems. In: Kahlen FJ, Flumerfelt S, Alves A, editors. Transdisciplinary Perspectives on Complex Systems. Springer, Cham. 2017; 85-113.
2. Tao F, Zhang H, Liu A, Nee AYC. Digital twin in industry: state-of-the-art. IEEE Transactions on Industrial Informatics. 2019; 15(4): 2405-2415.
3. Lee J, Bagheri B, Kao HA. A cyber-physical systems architecture for Industry 4.0-based manufacturing systems. Manufacturing Letters. 2015; 3: 18-23.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

4. Jardine AKS, Lin D, Banjevic D. A review on machinery diagnostics and prognostics implementing condition-based maintenance. Mechanical Systems and Signal Processing. 2006; 20(7): 1483-1510.
5. Lei Y, Yang B, Jiang X, Jia F, Li N, Nandi AK. Applications of machine learning to machine fault diagnosis: a review and roadmap. Mechanical Systems and Signal Processing. 2020; 138: 106587.
6. Zhao R, Yan R, Chen Z, Mao K, Wang P, Gao RX. Deep learning and its applications to machine health monitoring. Mechanical Systems and Signal Processing. 2019; 115: 213-237.
7. Kritzinger W, Karner M, Traar G, Henjes J, Sihn W. Digital twin in manufacturing: a categorical literature review and classification. IFAC-PapersOnLine. 2018; 51(11): 1016-1022.
8. Glaessgen E, Stargel D. The digital twin paradigm for future NASA and U.S. Air Force vehicles. In: 53rd AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference. 2012; Paper AIAA 2012-1818.
9. Qi Q, Tao F, Hu T, Anwer N, Liu A, Wei Y, et al. Enabling technologies and tools for digital twin. Journal of Manufacturing Systems. 2021; 58: 3-21.
10. Fuller A, Fan Z, Day C, Barlow C. Digital twin: enabling technologies, challenges and open research. IEEE Access. 2020; 8: 108952-108971.
11. Lu Y, Liu C, Wang KIK, Huang H, Xu X. Digital twin-driven smart manufacturing: connotation, reference model, applications and research issues. Robotics and Computer-Integrated Manufacturing. 2020; 61: 101837.
12. Liu C, Jiang P, Jiang W. Web-based digital twin modeling and remote control of cyber-physical production systems. Robotics and Computer-Integrated Manufacturing. 2020; 64: 101956.
13. Moher D, Liberati A, Tetzlaff J, Altman DG. Preferred reporting items for systematic reviews and meta-analyses: the PRISMA statement. PLoS Medicine. 2009; 6(7): e1000097.
14. Kitchenham B, Charters S. Guidelines for performing systematic literature reviews in software engineering. EBSE Technical Report EBSE-2007-01. Keele University and Durham University. 2007.
15. Lee J, Kao HA, Yang S. Service innovation and smart analytics for Industry 4.0 and big data environment. Procedia CIRP. 2014; 16: 3-8.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

16. Hochreiter S, Schmidhuber J. Long short-term memory. Neural Computation. 1997; 9(8): 1735-1780.
17. Saxena A, Goebel K, Simon D, Eklund N. Damage propagation modeling for aircraft engine run-to-failure simulation. In: International Conference on Prognostics and Health Management. 2008; 1-9.
18. Zonta T, da Costa CA, da Rosa Righi R, de Lima MJ, da Trindade ES, Li GP. Predictive maintenance in the Industry 4.0: a systematic literature review. Computers & Industrial Engineering. 2020; 150: 106889.
19. Errandonea I, Beltrán S, Arrizabalaga S. Digital twin for maintenance: a literature review. Computers in Industry. 2020; 123: 103316.
20. Aivaliotis P, Georgoulias K, Chryssolouris G. The use of digital twin for predictive maintenance in manufacturing. International Journal of Computer Integrated Manufacturing. 2019; 32(11): 1067-1080.
21. Karniadakis GE, Kevrekidis IG, Lu L, Perdikaris P, Wang S, Yang L. Physics-informed machine learning. Nature Reviews Physics. 2021; 3: 422-440.
22. Rasheed A, San O, Kvamsdal T. Digital twin: values, challenges and enablers from a modeling perspective. IEEE Access. 2020; 8: 21980-22012.
23. Jones D, Snider C, Nassehi A, Yon J, Hicks B. Characterising the digital twin: a systematic literature review. CIRP Journal of Manufacturing Science and Technology. 2020; 29: 36-52.
24. Wang J, Ye L, Gao RX, Li C, Zhang L. Digital twin for rotating machinery fault diagnosis in smart manufacturing. International Journal of Production Research. 2019; 57(12): 3920-3934.
25. Tao F, Qi Q, Wang L, Nee AYC. Digital twins and cyber-physical systems toward smart manufacturing and Industry 4.0: correlation and comparison. Engineering. 2019; 5(4): 653-661.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved

***Author for Correspondence:**
Arindam K. Basu
E-mail: arindam.basu.cse@outlook.com

[1]Associate Professor, Department of Computer Science and Engineering, Narula Institute of Technology, Kolkata, West Bengal
[2]Assistant Professor, Department of Computer Science and Engineering, Narula Institute of Technology, Kolkata, West Bengal
[3]Research Scholar, Department of Computer Science and Engineering, Narula Institute of Technology, Kolkata, West Bengal
[4]Research Scholar, Department of Computer Science and Engineering, Narula Institute of Technology, Kolkata, West Bengal

Received Date: January 6, 2025
Accepted Date: January 19, 2025
Published Date: February 03, 2025

Citation: Arindam K. Basu, Sneha R. Dutta, Rajarshi S. Sen, Moumita D. Pal. AI-Driven Digital Twin Technology for Predictive Maintenance in Smart Manufacturing Environments: A Comprehensive Review of Architectures, Algorithms, and Industrial Applications. Journal of Converging Technologies in Intelligent. 2025; 1(1): 16-29p.

Page 16-29 © MANTECH PUBLICATIONS 2025. All Rights Reserved