

A Review of the Production and Performance Evaluation of Biodiesel Using Various Techniques

Ajay Rai, Gunjan Tiwari

Assistant Professor

Department of Mechanical Engineering

Radharaman Institute of Technology & Science

Corresponding Author's E-mail: gunjan3894367@gmail.com

Abstract

As petroleum supplies become scarcer, there is a pressing need to find an alternate fuel to meet the world's energy demands. Biodiesel is a standout among the finest available options for meeting the world's energy needs. Over 350 oil-bearing yields were identified, with just a few being investigated as possible diesel engine elective fills. The experiment was carried out using different oils and their mixtures with diesel. The majority of the researchers said that short engine experiments using vegetable oils as fills were encouraging, but that long-term experimental results revealed increased carbon development and oil tainting was causing engine failure. They agreed that vegetable oils, either synthetically changed or blended with diesel, might be used to predict engine failure. It was found that biodiesel's burning characteristics are similar to diesel's, and that blends have a shorter I delay, a higher I temperature, a higher I weight, and a greater pinnacle warmth emission. The engine power output was found to be comparable to diesel fuel. It was also discovered that base catalysts are more empathetic than acid catalysts.

Keywords: petroleum supplies, Biodiesel, Acid Catalysts, Vegetable Oils

INTRODUCTION

As the world's supply of petroleum derivatives depletes, a new alternative fuel

must be discovered to meet the world's energy demands. Biodiesel is a standout among the most accessible options for

meeting the world's energy need. Oil companies play an important role in contemporary development, transportation, and agriculture, as well as meeting a variety of other human requirements. These abilities, however, are becoming increasingly limited and depleting as usage grows in all directions. Furthermore, its use is causing environmental problems in society. As a result, the researchers are on the lookout for elective energizers. India imports more than 80% of its gasoline and spends a significant amount of foreign currency for it.

Because of the exhausting notion of non-renewable energy source assets, biodiesel is gaining in importance as an enticing fuel. The purpose of the trans-esterification technique is to reduce the oil's thickness. Vegetable oil's main drawback is its high thickness and low unpredictability, which results in poor diesel engine igniting. Trans-esterification is a method for expelling glycerides and consolidating vegetable oil esters with liquor. This process reduces the thickness to a level comparable to that of diesel, resulting in better burning. When compared to diesel, biodiesel emits less pollutants throughout the whole range of air-fuel proportion. Biodiesel may be produced using a variety of techniques, including ultrasonic

cavitation, hydrodynamic cavitation, microwave illumination, reaction surface innovation, and a two-step reaction process. Different types of ignition chambers were subjected to tests. It has been observed that circular burning chambers produce better results than other types of ignition chambers. Rapeseed oil, sunflower oil, palm oil, and soybean oil were among the crude and processed vegetable oils tested by the researchers.

PRODUCTION OF BIODIESEL

Different techniques for producing biodiesel from various biofuels had been developed by scientists and researchers. This article contains a review of these approaches. Many researchers stated that the generation of biodiesel increased when a catalyst was included in the process.

To make biodiesel, Ahn et al. used a two-step reaction method. Using this method, canola methyl ester (CME), rapeseed methyl ester (RME), linseed methyl ester (LME), beef acid ester (BTE), and sunflower methyl ester (SME) are combined in a cluster reactor with catalysts such as sodium hydroxide, potassium hydroxide, and sodium methoxide. Cvengro and Povaz proposed making biodiesel using two-stage low-temperature trans-esterification of cold

pressed rapeseed oil with methanol at temperatures up to 70°C. Masaru et al. developed a dissolvable free reaction framework for synthesising methyl esters from plant oil and methanol using an enzymatic method. Uosukainen et al. presented a factual and exploratory framework to examine the connection of procedural variables in enzymatic transesterification about the same time. The researchers also looked at the alcoholysis of the methyl ester of rapeseed oil (biodiesel). Fangrui and Hanna conducted a study on biodiesel production. Ikwuagwu et al. investigated how to make biodiesel using elastic seed oil. The effect of three head variables, namely the molar proportion of methanol to oil and the catalyst quantity. Crabbe et al. studied the effect of reaction temperature on the yield of acid catalysed methyl ester (biodiesel) production from unprocessed palm oil.

Shieh et al. used reaction surface innovation to improve soybean biodiesel production. According to Zhang et al., the acid catalysed method including waste cooking oil has been shown to be more versatile than the soluble base catalysed procedure with waste cooking oil. Kojima et al. investigated the production of unsaturated acid methyl ester (FAME) from waste enacted blanching earth

discarded by the raw petroleum refining industry, using a petroleum derivative as a dissolvable in the esterification of triglycerides.

Tashtoush et al. conducted an experimental research on the evaluation and optimization of waste animal acid to biodiesel conversion. Biodiesel production from mahua (*Madhuca indica*) oil with high free unsaturated acids was investigated by Ghadge and Raheman. Van Gerpen discussed the effects of reaction time and temperature on the quality and quantity of esters. The most fundamental fuel quality characteristic is thought to be a trade-off between reaction time and temperature as reaction fulfilment. Xu et al. presented a model to depict the reaction energy of biodiesel production.

Biodiesel production from high free unsaturated acid elastic seed oil was studied by Ramadhas et al. To convert the high free unsaturated acid oils to monoesters, they devised a two-step transesterification process. The molar proportion, amount of catalyst, reaction temperature, and reaction term broke down are the major elements that impact the procedure's transformation efficiency. Karmee and Chadha used transesterification in the presence of potassium

hydroxide as a catalyst to produce biodiesel from *Pongamia pinnata*.

EMISSIONS FROM BIODIESEL

Carbon monoxide, carbon dioxide, nitrogen oxides, sulphur oxides, and smoke are all emitted by biodiesel. A brief review of the contaminations conveyed by biodiesel has been completed. In a single cylinder engine, Barsic and Humke investigated the effects of mixing shelled nut oil and sunflower oil with diesel fuel. When compared to 100% diesel fuel, they discovered that adding vegetable oil to the mix increased the amount of carbon stored on the injector tip. They discovered that vegetable oil fuel blends had a lower mass-based warming incentive than diesel. Hemmerlein et al. investigated exhaust emissions and sturdiness properties using faultless rapeseed oil as a fuel.

Carbon monoxide, nitrogen oxides (NOX), and smoke emissions were slightly lower for soybean ester than diesel, according to Scholl and Sorenson, while HC outflow was half that of diesel. The influence of exhaust gas distribution on diesel engine emissions was investigated by Ladommatos et al. They saw a significant reduction in NOX emissions at the expense of increased particle and unburned hydrocarbon emissions. Desantes et al.

tested a rapeseed oil methyl ester and diesel combination in a solitary chamber diesel engine. They discovered that when the channel air temperature was increased from encompassing to encompassing, carbon monoxide, NOX, and smoke emissions were significantly reduced. In a single chamber direct injection engine, Yoshimoto et al. investigated the outflow characteristics of used frying oil and a 30 percent water emulsion. Altin et al. investigated the use of methyl esters of sunflower oil, cottonseed oil, soybean oil, and corn oil as fuel in a single chamber direct injection diesel engine.

Sidhu et al. discussed the results of research centre examinations of molecule formation from four unique optional diesel fills, namely, compressed petroleum gas (CNG), dimethyl ether (DME), biodiesel, and diesel, in the temperature range of 800–1200 8C at weights of 24 atm. With warmed mustard oil as fuel, carbon monoxide emissions were higher at all loads at all velocities, according to Niemi et al. The inventors reasoned that preheating the oil decreased pollutants. Approximately the same time. Bari et al. investigated the effects of preheating crude palm oil on diesel engine emissions.

With the adoption of hydrogen, Senthil Kumar et al. noticed a reduction in smoke, hydrocarbon, and carbon monoxide emissions. In any event, increased burning rates resulted in increased NOX emissions. Particulate matter, carbon monoxide, hydrocarbon, and nitrogen oxide emissions were all investigated by Kalligeros et al. Carbon monoxide, carbon dioxide, oxides of nitrogen, and sulphur dioxide emissions decreased by 59 percent, 8.6 percent, 32 percent, and 57 percent, respectively, according to Dorado et al., and smoke emissions were minimal. They hypothesised that the methyl ester of olive oil may be used as a source of energy.

PERFORMANCE OF BIODIESEL

The exhaust gas assisted in the transformation of rapeseed methyl ester, which decreased CI engine emissions. The use of catalytic exhaust gas to create hydrogen-rich gas to assist fuel the transformation of rapeseed methyl ester had been investigated cautiously as a way to provide the expected hydrogen to reduce biodiesel outflows. Suryawanshi and Deshpande investigated the effects of exhaust gas distribution and impediment injection time on pongamia methyl ester-fueled diesel engines. They found that injection time hindrance and exhaust gas dispersion reduced nitrogen oxide

emissions when compared to typical circumstances.

Labeckas and Slavinskis et al. examined the emissions characteristics of a four-stroke, four-chamber, direct injection, usually suctioned diesel engine when operating on slick rapeseed methyl ester (RPE) and its 5%, 10%, 20%, and 35% blends with diesel fuel. They discovered that when methyl ester was compared to diesel, carbon monoxide, hydrocarbon, and obvious emissions decreased but nitrogen oxide emissions increased.

Narayana Reddy and Ramesh investigated the effects of CI engine injection time, injection ratio, and air whirl level on the performance of a CI engine running on jatropha oil. The designers hypothesised that accelerating the injection timing and increasing the injector-opening weight would considerably reduce hydrocarbon and smoke emissions.

CONCLUSION

Even though there are over 300 oil-bearing crops, only a handful are suitable for biodiesel production, such as rapeseed, palm, sunflower, and jatropha. It has been discovered that biodiesel has similar burning properties to diesel and that base catalyst outperforms acid catalyst. When

using a vegetable oil/diesel combination, the engine performance was average since the heavy oil produced injector coking and polluted the greasing up oil. The results of the testing using refined oil mixtures showed a significant improvement in performance. When compared to diesel, unburned hydrocarbon emissions from the engine were found to be higher on all fuel blends. When compared to diesel, the emission of nitrogen oxides from the engine was found to be greater on all fuel blends.

REFERENCES

1. Scholl KW, Sorenson SC. Combustion of soybean oil methyl ester in a direct injection diesel engine. SAE paper 930934.
2. Ladommatos N, Abdelhalim SM, Zhao H, Hu Z., The effects of carbon dioxide in exhaust gas recirculation on diesel engine emissions, *Journal of Automobile Engineering* 1998, 212: 25–42p.
3. Kojima Seiji, Du Dongning, Sato Masayasu, Park Enoch Y. Efficient production of fatty acid methyl ester from waste activated bleaching earth using diesel oil as organic solvent. *Journal of Bioscience and Bioengineering* 2004, 98: 420–4p.
4. Cvengro J, Povaz AF. Production and treatment of rapeseed oil methyl ester as alternative fuels for diesel engines, *Bio resource Technology* 1996; 55: 145–50p.
5. Kaieda Masaru, Samukawa Taichi, Matsumoto Takeshi, Ban Kazuhiro, Kondo Akihiko, Shimada Yuji, et al. Biodiesel fuel production from plant oil catalyzed by *Rhizopus oryzae* lipase in a water-containing system without an organic solvent. *Journal of Bioscience and Bioengineering* 1999; 88:627–31p.
6. Ahn E, Koncar M, Mittelbach M, Man R. A low-waste process for the production of biodiesel. *Separation Science and Technology* 1995; 30:2021–33.
7. Uosukainen E, La`msa` M, Linko Y, Linko P, Leisola M. Optimization of enzymatic transesterification of rapeseed oil ester using response surface and principal component methodology. *Enzyme and Microbial Technology* 1999; 25:236–43p.
8. Ma Fangrui, Hanna Milford A. Biodiesel production: a review. *Bio resource Technology* 1999; 70: 1-15p.

9. Ikwuagwu OE, Ononogbu IC, Njoku OU. Production of biodiesel using rubber [*Hevea brasiliensis* (Kunth Muell.)] seed oil. *Industrial Crops and Products* 2000, 12: 57–62p.
10. Crabbe Edward, Nolasco-Hipolito Cirilo, Kobayashi Genta, Sonomoto Kenji, Ishizaki Ayaaki. Biodiesel production from crude palm oil and evaluation of butanol extraction and fuel properties. *Process Biochemistry*.