MANTECH Publications

Journal of Ceramics and Concrete Technology
Volume 4 Issue 2
ISSN: 2457-0826 (Online)

# *The Study of Precast Concrete Connections*

***Ankit Katiyar, ChandreshKumar Jha***
*Student, Assistant Professor***
*Department ofCivil Engineering*
*Rama University, Mandhana Kanpur, UP, India.*
***Corresponding author's email id:****ankit.iitm222@gmail.com,ck.jha@rediffmail.com*
***DOI:*** *http://doi.org/10.5281/zenodo.3366017*

***Abstract***

*Outlines and discusses necessities for connections in formed concrete buildings, and shows examples from completed structures wherever these necessities are met. A time-proven hypothesis explaining shear behavior at concrete to steel and concrete to concrete interfaces is bestowed. Examples illustrate beam to column connections exploitation this hypothesis. Suggestions for additional study are printed.*

*Though the formed concrete structural systems are being wide used worldwide, Earthquakes are natural disasters that have caused loads of infrastructural injury and loss to human lives. within the past earthquakes, the cost effective formed structural systems had not performed well.*

*The failure of the formed structures was attributed to the poor performance of connections. Connections type the weakest link within the formed concrete structure. For the past four decades although loads of analysis has been dispensed on the behavior of formed structures, a whole understanding of the behavior of formed beam-column connections to lateral loading has not been field demand skills and talents so much on the far side the development engineering and should be a balance amid advanced technology and trends, management, practice abalones and economy.*

 Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

*The specimens were classified into 3groups with 2 numbers in every cluster. they're sort I connections - Bolt and Rod connections, sort II connections: Cleat Angle and Stiffened Cleat Connections and sort III connections: fastener Connections. the kind I association consisted of 2 connection details (i) formed connection exploitation JBolt (PC-JB) and (ii) formed connection using rod (PC-TR). II association consisted of 3 connection details (i) formed connection exploitation Cleat Angle (PC-CL) (ii) formed connection using cleat angle and single filler (PC-SS) (iii) formed connection using cleat angle and Double filler (PC-DS). the kind III association consisted of 2 connection details (i) formed connection exploitation fastener bar (PC-DW) and (ii) formed connection using fastener bar and Cleat Angle (PC-DWCL). The formed concrete beam and column close to the joint were additionally elaborated with confinement reinforcement. All the sixteen specimens were tested beneath constant axial load on the higher finish of the column and with cyclic load*

*The main objective of the study was associate analyze the various particularization of joints in an exterior formed concrete beam-column joint subject to reverse cyclic.*

***Keywords:****Beam, Column, Connections, Continuity, Design, Diaphragm, Precast concrete, Shear-friction hypothesis, Shear strength.*

## INTRODUCTION

Precast could be a standard building system supported parts and connections. Some kind of a formed association is required between every created precast unit. Demands for formed association varieties vary among completely different precast merchandise, native building conditions and restrictions, and masses on the structure. Typically each country has its own system for formed connections. There are many pre-tested association varieties for formed floor merchandise, and seismic and support connections.

Precast connections guarantee safety and sturdiness of a formed building. They carry the predefined masses in several building structures and resist hearth and water. Industrially created formed


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

connections are quick and simple to put in despite what the precast product.

Pre casting is nice for manufacturing massive numbers of identical parts. Let's say we have a tendency to build an inexpensive public housing with3,000 identical residences. We have a tendency to use Pre casting to supply wall slabs and floor slabs for all residences. So carry them into place and connect them.

***1. Formed affiliation style***

Typically formed affiliations will be finished associate industrially made connection half, wet affiliation, bolt, or weld affiliation. In formed affiliation style the key variables are strength, volume changes, ductility, sturdiness as well as hearth and corrosion, simplicity in production, installation and maintenance, temporary loading conditions, economy and look.

Precast buildings suit well for decent, cold and conjointly unstable areas, once the particular native needs are taken under consideration in affiliation style. If coming up with a building for a unstable space, it's counseled to involve unstable affiliation style consultants into the method.

***2. Formed floor connections***

There are many pre-tested connections for hollow-core block floors. Hollow-core slabs are ordinarily put in on synthetic rubber strips, which will even be used as a part of the ultimate affiliation. Synthetic rubber strips guarantee a homogenous bearing of floors.

Connections at longitudinal joints are used between the perimeters of the hollow-core floor unit and beams or walls running parallel with the ground. Their main perform is to transfer horizontal shear on the formed units.

***Specific formed affiliation sample drawings will be found for.***

*HC block on rectangular Beam

*HC slab on concrete wall, wall-to-wall affiliation

*HC block on Sandwich wall

*HC block on wall corbel

***3. Formed connections for sandwich walls***

Connecting loops, ties and fixing sockets are common safety solutions, once building with sandwich walls.

Connecting loops connect the vertical joints of formed wall panels to every alternative. They’re single-wire loops,


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

which might be applied on wall-to-column joints in addition. Connecting loops are simple to put in by gap the wall cowl, bending the loops to the in operation position and connecting them to reinforcement.

Ties connect a facade associated an inner panel of a sandwich wall along. They're a connecting reinforcement of the wall as well as outer, inner and diagonal bars forming a lattice-type of ties. Outer and inner bars will be either traditional or stainless-steel, whereas diagonal bars are continuously of stainless-steel.

Fixing sockets are used for attaching and fixing objects to formed concrete like guard rails, lighting, etc. Their main perform is to hold axial load.

***4 Shaped affiliation vogue***

Typically shaped affiliations are through with associate industrially created affiliation 0.5, wet affiliation, bolt, or weld affiliation. In shaped affiliation vogue the key variables are strength, volume changes, ductility, strength in conjunction with hearth and corrosion, simplicity in production, installation and maintenance, temporary loading conditions, economy and appearance.

Precast buildings suit well for good, cold and collectively unstable areas, once the actual native wants are taken into thought in affiliation vogue. If turning out with a building for an unstable house, it's recommended to involve unstable affiliation vogue specialists into the strategy.

Here are several pre-tested connections for hollow-core block floors. Hollow-core slabs are sometimes place in on rubber strips, which can even be used as a locality of the last word affiliation rubber strips guarantee the same bearing of floors.

Connections at longitudinal joints are used between the edges of the hollow-core floor unit and beams or walls running parallel with the bottom. Their main operate is to transfer horizontal shear on the shaped units.

***Specific shaped affiliation sample drawings are found for...***

*HC block on rectangular Beam

*HC slab on concrete wall, wall-to-wall affiliation

*HC block on Sandwich wall

*HC block on wall corbel


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

***5. Shaped connections for sandwich walls***

Connecting loops, ties and fixing sockets are common safety solutions, once building with sandwich walls.

Connecting loops connect the vertical joints of shaped wall panels to each different. They're single-wire loops, which could be applied on wall-to-column joints still. Connecting loops are easy to place in by gap the wall cowl, bending the loops to the operational position and connecting them to reinforcement.

Ties connect a facade and associate inner panel of a sandwich wall onthey're a connecting reinforcement of the wall in conjunction with outer, inner and diagonal bars forming a lattice-type of ties. Outer and inner bars are either ancient or stainless-steel, whereas diagonal bars are endlessly of stainless-steel.

Fixing sockets are used for attaching and fixing objects to shaped concrete like guard rails, lighting, etc. Their main operate is to carry axial load.

***6.Joints of the outer layer of the sandwich wall***

Main variables of a top quality formed wall are ventilation in sandwich structures, water resistance and outlook. Most of the former wall issues are caused by the joint deformations within the outer layer of facades and sandwich walls thanks to temperature and wetness variation.

The right use of wall joints is important to forestall these downside. Sensible wall joint material withstands stress caused by thermal movement within the units, star ultraviolet and infrared light, external air temperature and impurities.

Joints ought to be designed therefore, that they forestall rain getting into between formed unit and also the insulation.

The key in a very property wall joint construction is provision of solid and sleek adhesion surface for the jointing mass within the edges of the wall units. By dynamical surface material, texture or color at the joints, it's doable to create surfaces, wherever junctions are seen as a natural elements of the facades.

***Aim of analysis (Abstract)-***

Concrete that is created in mill condition so transported to web site is termed formed concrete. The weather like columns, footings, beams, etc. are created in mill as per the specified dimensions and transported to web site for construction. The formed concrete is transported to the


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

development web site, upraised and positioned at the preset place. Concrete parts are factory-made in a very controlled casting surroundings and have it's easier to regulate combine, placement and activity. Quality are often controlled and maintained simply. Parts are often forged prior to and control till the hour you would like them, thereby saves time. Formed concrete may be a cheaper sort of construction if giant structures are to be made.

**BRIEF LITERATURE SURVEY**

Precast concrete may be a construction product, created by casting concrete in a very reusable mold or "form" that is then cured in a very controlled surroundings and transported to the development web site for installation. There are differing types of formed concrete forming systems for subject area applications that take issue in size, function, and price.

Usage of formed parts eliminates or extremely reduces the necessity for typical formworks and props. They additionally lower the generation of wastage and checks different environmental hazards. They more offer a secure operating platform to the staff. formed product are factory-made in a very casting space wherever important factors like temperature, mix design, and baring time are often closely checked and controlled, that ensures that the standard of formed product is best than that of cast-in-situ concrete.

Moreover, it saves a substantial total of cash through eliminating rectification work. What is more, thanks to factory-controlled surroundings, completely different mixtures of colors and textures are often applied simply to the subject area or structural items. a massive vary of sizes and shapes of formed elements are often made, providing flexibility and recent look to the structures. These are the benefits of mistreatment formed concrete.

Precast concrete is primarily employed in the development of buildings with repetitive styles and parts, like colleges and residences. It provides architects with AN exciting medium whereas coming up with facades for a large vary of buildings, like aid facilities, looking malls, business buildings, and stadiums.

***• Planned analysis work***

Pre casting may be done at a casting yard, in or close to the positioning, or during a industrial plant. A key facet of decisive whether or not to use web site or industrial plant pre casting are the transport prices.


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

Industrial plant work offers superior quality for obvious reasons, thus if there's an industrial plant getting ready to the positioning, it is smart to use it.

If a pre casting yard is to be created, house should be arranged out for the subsequent activities:

Storing the raw materials, like cement, aggregate, sand, admixtures, water, reinforcement bars, and steel or ply board sheets for formwork

- A formwork creating and maintenance yard
- A concrete compounding plant
- A steel reinforcement yard to create rebar cages to be placed within the concrete
- A casting space
- A solidification space
- A stacking space for finished elements

For infrastructure comes, a casting yard is formed on a chunk of open land within the town. It's necessary that this be set close to a serious road, because the formed components may be terribly giant or serious, and can't be taken through slender roads.

***Precast concrete elements may be connected during a range of ways:***

1. They'll be latched along so as to try to do this, steel connectors are embedded within the concrete at the time of casting.

2. They'll be grouted or concreted along during this methodology, loops of steel reinforcement are left projected out of the formed concrete members. 2 members are placed in position, and reinforcement is rib between the loops. Recent concrete is then poured around this reinforcement, during a house left for this purpose.

***Downside Statement:***

Typically formed affiliations may be through with Associate in Nursing industrially made connection half, wet affiliation, bolt, or weld affiliation. In formed affiliation style the key variables are strength, volume changes, ductility, sturdiness together with fireplace and corrosion, simplicity in production, installation and maintenance, temporary loading conditions, economy and look.

Precast buildings suit well for decent, cold and conjointly sensual areas, once the particular native necessities are taken into consideration in affiliation style. If coming


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

up with a building for a sensual space, it's suggested to involve sensual affiliation style specialists into the method.

Here are many pre-tested connections for hollow-core block floors. Hollow-core slabs are ordinarily put in on synthetic rubber strips that may even be used as a part of the ultimate affiliation. Synthetic rubber strips guarantee a consistent bearing of floors.

Connections at longitudinal joints are used between the perimeters of the hollow-core floor unit and beams or walls running parallel with the ground. Their main perform is to transfer horizontal shear on the formed units.

***Methodology/ coming up with of labor***

SQRIM may be a full formed concrete technique that eliminates cast-in-place (CIP) concrete on the building's main structural parts like the columns, beams, and therefore the beam-column joint core. In SQRIM, the beam and beam-column joint core are fictitious as one formed component. These parts are vertically put in within the construction web site. Grouted mechanical sleeves are wont to be part of the formed parts. To emulate associate RC structure, grout is injected into the joints and into the holes to stiffly connect the formed parts. The benefits of SQRIM application are: shorter construction amount, prime quality formed parts, elimination of formworks and temporary supports, and savings on labor. Since 2003, SQRIM has been applied to forty building comes in Japan.

Developed from SQRIM, SQRIM-H is additionally full formed concrete technique that eliminates cast-in-place (CIP) concrete and has an equivalent characteristics and blessings of SQRIM. Grouted mechanical sleeves are wont to connect the formed parts. In SQRIM-H, the beams are often fictitious severally from the beam-column joint core and are merely formed compared to the SQRIM's single beam and beam-column joint core component. Thus, beams are simply put in by slippery horizontally (indicates the "H") to affix with the column. The tactic are often applied to any building with sophisticated form and structural framing. SQRIM-H has been applied to eight building comes since 2008.

The I-SQRIM is specially supposed for the overseas (international) market and was applied for the primary time in an exceedingly organic compound plant rack in Asian country. The first style of the rack was typical formed that still needed cast-


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

in-place (CIP) concrete to stiffly connect the precast parts. The first style was modified with the appliance of SQRIM technique. This includes dynamic the first lap reinforcement to mechanical joint, L-shaped hook anchor reinforcements to mechanical finish anchors, and to stiffly connect the formed parts grout injection was applied rather than CIP. Since CIP concrete is additionally eliminated in I-SQRIM, it achieves an equivalent characteristics and blessings of SQRIM.

Production of formed parts has been exhausted casting yard. Moulds of adequate stiffness have been used and put in as per issued GFC drawings.

***The sequence of activities concerned within the production of formed parts is as follows:***

1. Mould cleanup and preparation
2. Shuttering / collecting the mould elements
3. Fixing of re-bars / cast-in-fittings
4. Pre-concrete check
5. Concreting
6. Curing
7. Remolding
8. Final review
9. Stacking

**ENVIRONMENTAL AND EXPERIMENTAL**

Precast construction methodology is recently developed method, still heaps of researches happening to boost its applications. Here few comparisons created with typical construction system by finding out the positioning work and analyzing the activities.

1. formed construction methodology is only supported shear wall construct and thence the standard floor doesn't contain any form of columns however in typical, columns are should to construct twelve floors of a tower.

2. Formed construction method meted out at web site as production of components alongside concurrent erection of the prepared elements that significantly saves the time of construction wherever as in typical, block work and natural action consume a lot of time to finish.

3. Block work is restricted to only one to 1.2m height per day to take care of correct alignment whereas; formed components don't have any such restrictions.


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

4. In typical methodology, block work should proceed more with correct natural action and additionally application need curing amount for adequate association and to realize strength; however in formed methodology, no such intense natural action needed as a result of, the most and final natural action done at casting yard solely to attain most strength.

5. Application work is obligatory in typical whereas formed methodology doesn't need any kind of plastering work.

6. For slabs, shuttering work, reinforcement works consume longer in typical method; however in formed, slabs additionally get factory-made in yard itself.

7. All elements of a structure can't be mounted with formed elements; at few necessary locations block work is important in precast construction additionally.

8. In formed methodology, block ought to proceed more with screed of sure thickness to supply Necessary electrical passages; whereas typical system contains the electrical conduit works in traditional block shuttering work itself.

9. No alterations in style are potential in formed construction; however in typical, any quite alterations are created with none drawback.

10. Higher internal control may be potential with formed construction however because the floor level will increase, in typical system it's terribly tough to take care of smart quality.

11. Formed construction system needs virtually 0.5 the quantity of total man power that needed for typical system.

12. Construction activities occur at a quicker rate in formed compared to traditional system.

13. Formed construction provides higher alignment of structural components than the standard one.

## CONCLUSION

- It is fake financial system to abandon the accurate curing program for all concrete substance formed also on site or in factory process.


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved

- 2-most precast concrete producer make use of some sort of curing organization that is suitable to their manufacture regime.

- 3-most toughened concrete constructors disburse scant look upon to this significant step in realizing the filled possible of a intended concrete and consequently cooperation the intend of the arrangement underconstruction.

- The use of prefabrication and preassembly is estimated to have almost doubled in the last 15 years, increasing86%

- The utilize of precast concrete construction can considerably decrease the quantity of construction dissipate generate on manufacturesites.

- Decrease adverse environmental collision onsites.

- Improve excellence control of concretingeffort.

- Decrease the quantity of site manual labor.

- Boost employeeprotection.

**REFERENCES**

I. formed CONSTRUCTION METHODOLOGY IN housing industry

II. S.S. Chandra, Rehabilitation of Buildings, International Journal of applied science analysis.

III. web and Wikipedia

**Cite this Article As**

Ankit Katiyar, ChandreshKumar Jha (2019) **The Study of Precast Concrete Connections** "Journal of Ceramics and Concrete Technology" ISSN: 2457-0826 (Online) 4(2), 11 -12

http://doi.org/10.5281/zenodo.336601


Page 11-21 © MANTECH PUBLICATIONS 2019. All Rights Reserved