MANTECH Publications

Journal of Research in Electrical Circuits and Systems
Volume 7, Issue 2, May-August 2022

Using Arduino to Create a Working Model of an AC Voltage Measurement and Over/Under Voltage Protector

Bindu Aggarwal[1], Dr. S. R Laksman[2]
Student[1], Professor[2]
Department of Electrical Engineering
NIT Jamshedpur
Corresponding Author's Email: - *binduaggarwal9@gmail.com[1]*

Abstract

The technique of spending a significant amount of time with a pencil and paper in order to scribble down first concepts is a common one among architects. In most cases, more time is needed in order to transform the work into electronic media in the form of specialised drawings. A depiction recognition system would save professionals a significant amount of time that is currently spent redrawing them in specialised software. During the course of this expectation, we will see sketched images of electrical circuits. It is necessary for us to complete a trainable electrical sketched circuit recognizer that possesses a rapid reaction time, a high level of precision, and the ability to easily extend itself to a new segment. In order to partition the circuit sketch, we will use a PCA-based picture preprocessing methodology together with a watershed division method.

Keywords: *Sketched Electrical Circuit, Architecture, PCA*

INTRODUCTION

The authenticity of the content has become a significant problem as a result of developments in the field of computer technology, the widespread use of the internet, and the rising availability of resources. In order to verify the authenticity, several different computations were performed in the past. It is important to provide references for anyone who want to learn more about your ideas and the background from whence they came since not all sources are reliable or accurate. This is because not all sources

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

are good. It's possible that your own ideas are more accurate or interesting than the information provided by your sources. If you make appropriate reference, you won't have to absorb the pain of being responsible for another person's horrible ideas. Providing citations for the work that you've done displays the depth of research that you've conducted providing citations for the work that you've done helps to reinforce your work by providing an external backup for your views. A substantial amount of thoughts were presented about how to effectively refer to your article with the end goal of presenting the genuineness of the investigation work carried out by the researcher.

An inquiry has been raised about the reason why references are carried out; alternatively, we might ask: what is the requirement or relevance of circuit? The solution may be broken down into its component parts by examining the following foci, each of which sheds light on the value of recognition. There have been several suggestions made on procedures for the recognition of in-text citations inside a paper. The findings were not very pleasing since the circuit recognition does not give a satisfactory metric for the computation of in-text citation of the article. In other words, the results were not very satisfactory. The primary objective of the study effort was to design a method that might give paper re-evaluators with an easier approach to assess the authenticity of the contents. This was the basic notion behind the work that was done. These approaches result in more accurate and fulfilling predictions, which are a win-win all around. Using grammatical connections, the circuit recognition of in-text citation is a notion that may be used to either show or verify the authenticity of the contents of a manuscript. This is accomplished through the use of the term "circuit recognition." Although the POS tagging and type dependencies approaches will be able to address many problems, it is not possible to ensure that the results will be satisfactory. As part of this body of research, our team has attempted, with varying degrees of success, to improve upon previously developed algorithms. We are not suggesting that this is the end of study in this area, but it will undoubtedly present new researchers with the opportunity to put forth fresh ideas and perspectives that may be able to meet the needs of the future. In addition to this, they are capable of generating actual ideas and approaches that have the potential to be of great service in the field of recognition.

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

EXISTING APPROACHES

Yuchi Liu et al. displays a circuit identification drawing, which is a highly helpful tool for electrical engineers to have. In this project, we segment the circuit schematic by utilising a topology-based segmentation approach, and then we classify each component by employing the Fourier descriptors as a feature vector for the Support Vector Machine. It is possible to reach an accuracy rate of above 90% for each individual component. There have been several suggestions made on procedures for the recognition of in-text citations inside a paper. The findings were not very pleasing since the circuit recognition does not give a satisfactory metric for the computation of in-text citation of the article. In other words, the results were not very satisfactory. The primary objective of the study effort was to design a method that might give paper re-evaluators with an easier approach to assess the authenticity of the contents. This was the basic notion behind the work that was done. These approaches result in more accurate and fulfilling predictions, which are a win-win all around. Using grammatical connections, the circuit recognition of in-text citation is a notion that may be used to either show or verify the authenticity of the contents of a manuscript. This is accomplished through the use of the term "circuit recognition." Although the POS tagging and type dependencies approaches will be able to address many problems, it is not possible to ensure that the results will be satisfactory. As part of this body of research, our team has attempted, with varying degrees of success, to improve upon previously developed algorithms. We are not suggesting that this is the end of study in this area, but it will undoubtedly present new researchers with the opportunity to put forth fresh ideas and perspectives that may be able to meet the needs of the future. In addition to this, they are capable of generating actual ideas and approaches that have the potential to be of great service in the field of recognition.

Existing Approaches

Yuchi Liu et al. displays a circuit identification drawing, which is a highly helpful tool for electrical engineers to have. In this project, we segment the circuit schematic by utilising a topology-based segmentation approach, and then we classify each component by employing the Fourier descriptors as a feature vector for the Support Vector Machine. It is possible to reach an accuracy rate of above 90% for each individual component.

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights




Fig 1 Circuit Recognition in Database

Preprocessing

Before extracting the electric circuits, several preprocessing tasks on preparing the electric circuits and the test sketch circuit need to be completed first. Those tasks include: This preprocessing is done by running the electric circuits via a battery, capacitor, intensifier, diode, and resistor depending on the yield that is necessary, and we may also apply these components individually or two at a time.

Fig no 2 demonstrates a preprocessing picture of the procedure.

Segmentation

When it comes to segmentation, watershed segmentation is employed so that ROI may be segmented more effectively. Instead of utilising a sliding window, which may have its size change in both the vertical and horizontal directions, we extract feature points based on the topology of the picture, and we locate the bounding box based on these feature points. This allows us to reach a high level of efficiency. Figure 3

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights




Fig 2 Preprocessing Image




Fig 3 Classification Process

Feature Extraction:

In this study, in order to recognise a circuit-sketch, it was necessary to separate electric components from circuits. Electrical components can be distinguished from one another based on their outward appearance. One algorithm cannot be used to extract all of the electrical components since it is not feasible. Because of this, we have developed a unique algorithm for each of the electrical components.

Tracking down the location of all of the different circuits is the initial and most essential phase in the process of detecting electrical components. After that, the symmetry quality of the electric with respect to the circuits is utilised for the purpose of tracking the remaining

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

components, such as the capacitor, the resistor, the diode, and so on.

In this case, we have made use of a geometric model, which is depicted in figure 3, to predict the region of interest or the approximate positions where the electrical components may appear. Subsequently, the actual regions of the electrical components have been extracted by applying the appropriate algorithms over the area surrounding the predicted regions.

Fourier Descriptors

The Fourier transform is frequently utilised in the process of shape analysis. Their useful properties, which include ease of derivation and normalisation, as well as resistance to the effects of noise, have contributed to their widespread use in a wide range of contexts. In the frequency domain, the shape is represented by these characteristics.

The higher frequency components carry information about the shape's more intricate elements, whereas the lower frequency components provide information about the more obvious characteristics of the shape. Even though various people have distinct ways of drawing, the low frequency coefficients for the same electrical component tend to have comparable subsets.

This is despite the fact that sketching styles might vary from person to person. Because of this, even though the Fourier transform often produces a high number of coefficients, the dimensions of the Fourier descriptors that are employed for shape identification may be considerably decreased.




Fig 4 Feature Extraction

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

PROBLEM STATEMENT

The most significant challenge associated with circuit recognition up until this point has been determining how to examine the circuit and how much material is needed to draw the references. By employing synonyms and several other methods, an earlier scholar or other researcher duplicates the ideas or certain sections of the substance of the study work.

In the course of this study activity, we have suggested several methods that make use of diverse circuit recognition as a key to check the contents of a database. The reasoning for this approach is that the fundamental processes of recognition cannot be altered in any way. Using the approach that has been suggested, it will be possible to address this problem to a greater extent. The problem identification for the research study is depicted in the following figure, which you may see below.

METHODOLOGY

Because more aspects of human life are being digitised, the rate of data and information transfer has expanded at a breakneck pace. The internet is home to the creation, uploading, and dissemination of tens of thousands of text, picture, and video items every single day. The proliferation of internet use has given rise to a number of new problems, one of which is the infringement of copyrights and digital data. Because there is an abundance of information accessible to everyone, all it takes is one click for everyone to work more efficiently (do more with the same amount of effort) and reuse the knowledge that is readily available all over the world to fit his own needs.

Our study effort focuses on the validity of the content of journals or research papers that researchers submit as part of their acknowledgement for their research work. For the purpose of finishing their job, research researchers make use of a wide variety of reference papers and other information resources. In order for them to carry out the duty that was assigned to them, they discovered that someone else had previously worked on this subject in some other setting. Therefore, all they need to do is utilise their previous work or research paper as a reference.

We are presenting an approach that is both straightforward and extremely authentic for recognising this contextual reference information in the research papers written by scholars. How much of the data comes from different reference publications,

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

regardless of whether or not the researcher has actually utilised any of the material from the reference papers at all. This research study is applied in the process of identifying concerns similar to those stated above. We have decided to go with the name Circuit.

The programme was able to distinguish the actual structure of the circuit that was being drawn, such as two lines representing a battery, a triangle representing a diode, and a rectangle representing a resistor. As part of this body of research, our team has attempted, with varying degrees of success, to improve upon previously developed algorithms. We are not suggesting that this is the end of study in this area, but it will undoubtedly present new researchers with the opportunity to put forth fresh ideas and perspectives that may be able to meet the needs of the future. Additionally, they have the ability to generate actual ideas and approaches that have the potential to be of great service in the field of natural language processing.

The Stanford parser is a natural language processing tool that contains a wide collection of capabilities to deal with extracted phrases of words and sentences. This enabled us to produce an effective result of in-text citation, which is why we utilised it.

WORKING PROCESS

This proposed work is followed by the following steps:

- Image Preprocessing [PCA Based]
- Image Segmentation (Watershed)
- Feature Extraction (Fourier descriptors)
- Classification (SVM)

(a) Image preprocessing: Picture preprocessing may considerably boost the reliability of an optical examination; many filter operations that emphasise or diminish particular image characteristics enable a simpler or faster evaluation. Image preprocessing also improves the quality of the image. Binarization of the raw pictures is the first step that must be taken in order for us to be able to distinguish between the many components that a sketch user may have drawn. After that, we use a filter to remove localised areas of noise.

(b) Image Segmentation (Watershed): A ridge that separates areas that are drained by many river systems is what is meant when people talk about a watershed. The region of land that eventually becomes drained by a river or reservoir is

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

referred to as a catchment basin. The first step in the computer analysis of visual objects is to locate those items and determine which pixels make up each object. Image segmentation is the process of separating things from their backgrounds and from one another, as well as separating individual objects from one another. A drop of water that follows the gradient of an image runs along a route until it reaches a local minimum at its destination. The watershed of a relief roughly corresponds to the boundaries of the nearby catchment basins of the drops of water, according to a commonsense interpretation of the term.

(c) Feature Description: In this step, analysis of the shape has been carried out using Fourier descriptors. When it comes to form retrieval, the user is only concerned with the contour aspects of comparable objects; the location, size, and rotation of the shapes are irrelevant considerations. Even if various persons have distinct sketching tendencies, the subset of the low frequency coefficients tend to be the same for the same electrical component. This is the case even when different people draw. Because of this, although though the number of coefficients generated by the Fourier transform is typically rather big, the dimensions of the fourier descriptors that are employed for shape identification may be significantly decreased. To determine a shape's Fourier descriptors, one must first locate the coordinates of the form's edge pixels and then arrange those coordinates in a list in a direction that progresses clockwise around the shape. to define a vector with complex values using the acquired coordinates as the input. Consider, as an illustration, carrying out the discrete Fourier transform on the complex-valued vector. A number of characteristics are passed down from the Fourier transform to the Fourier descriptors.

Translation invariance: no matter where the shape is located in the image, the Fourier descriptors remain the same.

Scaling: if the shape is scaled by a factor, the Fourier descriptors are scaled by that same factor.

Rotation and starting point: rotating the shape or selecting a different starting point only affects the phase of the descriptors. The complex vector that is created from the shape boundary coordinates is used to perform the Fourier transform, which is then used to obtain the Fourier descriptor for the complex coordinates signature. Let's say that the K pixels that make up the

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

boundaries of a certain form are numbered from 0 to K-1. The pixel at position k contains the value (xk, yk). The difference in coordinates between the centroid (xc, yc) and the border points determines the complex vector S, which represents the shape.

(d.) Classification (SVM): Following the discovery of the bounding boxes for each component, we enlarge the image and count the number of linked areas that it contains for each individual component. If it has two linked areas, then it is likely either a capacitor or a battery. If it does have two connected regions, then we may identify it as either a capacitor or a battery based on the ratio of the axes of the two regions. In such case, we will need to locate the borders of the component, extract the second through seventeenth Fourier descriptors, and make a judgement using SVM.




Fig 5 Flow of Work

RESULT AND DISCUSSION

EXPERIMENTAL ANALYSIS

We include 55 practise photos and 30 test photographs for each individual component of the test. The test photographs have been given a variety of styles, scales, and introductions, each with their own personality. We were able to get a precision of more than 90% by using a low recurrence subset of Fourier descriptor of the mind-boggling directions of the pixels on the boundaries of the sections as highlight vectors for SVM. In addition, we discovered that our technique is actually robust when subjected to varying scales, different types of introductions, and several drawing styles. In addition, we compared the accuracy of using mind-boggling directions form markings to the accuracy of using centroid separation marks, and we found that the accuracy of using mind-boggling directions is superior for our problem.

The Dependence of Accuracy on the Size of the Training Set Capacitor and battery recognition both make use of their own unique approach, and as a result, they are able to achieve 100% accuracy. In this section, we will be discussing the second group of items that were organised using SVM. When it comes to the second group, which is comprised of the intensifier, the

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

diode, and the resistor, the precision with which we can recognise each individual component improves as the size of our database for producing images grows. While only the thirty test photographs are examined, our accuracy rates for recognising amplifiers, diodes, and resistors are respectively 96%, 98%, and 99% when there are fifty-five preparatory pictures. This provides us with an estimate of the number of training images that are required for each category of part in the event that we choose to support new categories of part. The effect that the size of the preparation has on the accuracy of the recognition is seen in the following table.

The graph depicted in figure 5 is a comparison between the work done in the past and the work done currently. This graph depicts the highest possible level of precision achieved by an amplifier.

The graph shown in figure 6 is a comparison between the work done in the past and the work done currently. This graph illustrates the greatest possible degree of precision in identifying a diode.




Fig.6: Comparison Graph of previous work and Current work of amplifier




Fig.7: Comparison Graph of previous work and Current work of Diode

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

Figure 8 represents a graph previous work and current work comparison graph. This graph represents a maximum accuracy identified a resistor.




Fig8: Comparison Graph of previous work and Current work of Resistor

Figure 9 represents a graph previous work and current work comparison graph. This graph represents a maximum accuracy of total.




Fig.9: Comparison Graph of previous work and Current work of total

CONCLUSION

We have developed a method that successfully recognises components inside a diagram of an electrical circuit. In order to divide things apart, we employed a topology-based component point. As the highlight vector for SVM, we made use of the Fourier descriptor of the mind-boggling directions of the limit of the portion. We have demonstrated a high accuracy acknowledgement rate that is invariant to the picture being rotated, scaled, or altered in any other way.

Our framework is capable of being expanded to take into account additional

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

classifications of circuit segment. We believe that it is a promising technique to handle recognising hand-drawn depictions and delivering conventional circuit diagrams. The accuracy of the amplifier's earlier work on the Centroid Distance Fourier was 70%, whereas the accuracy of the present work is 85%. The work done by the Complex plane Fourier Descriptor in the past. The correctness of the work done in the past was 93%, while the accuracy of the work done now is 97%. Diode The accuracy of the previous work on the Centroid Distance Fourier was 60%, whereas the accuracy of the present study is 70%.

The work done by the Complex plane Fourier Descriptor in the past. The correctness of the work done in the past was 93%, while the accuracy of the work done now is 98%. Resistor The accuracy of the new work is 69%, which is an improvement from the previous work of the Centroid Distance Fourier (57%). The work done by the Complex plane Fourier Descriptor in the past. Previous work had an accuracy of 67%, whereas the accuracy of the job being done now is 79%.

REFERENCES

1. Zhang D. et al. (2014), "A Comparative Study on Shape Retrieval Using Fourier Descriptors with Different Shape Signatures" Association for the Advancement of Artificial Intelligence
2. Jain A. et al (2015) "Bridging the Gap: From Biometrics to Forensics" Philosophical Transactions of The Royal Society B.
3. A. Mainwaring, D. Culler, J. Polastre, R. Szewczyk, J. Anderson, Wireless sensor networks for habitat monitoring, in: Proc. of the 1st ACM International Workshop on Wireless Sensor Networks and Applications, 2002
4. Neulka D. et al (2014) "Mallats Wavelet Transform for Human Face Recognition Using Artificial Neural Network" Published by JETIR.
5. Klum S. et al (2011) "Sketch Based Face Recognition: Forensic vs. Composite Sketches" Philosophical Transactions of The Royal Society B.
6. Liu Yet al (2013) "Circuit Sketch Recognition", Published in Pervasive and Mobile Computing.
7. Wang N.. et al (2013), "Pattern Recognition Letters", Pattern Recognition Letters.

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights

8. Pramanik S. et al (2010)“ geometric feature based face-sketch Recognition”, Published in Computer Communication.
9. Ahmed S. et al.(2013), “Automatic analysis and sketch based retrieval of architectural floor plans” Published by pattern recognition letters”
10. Wu J. et al (2014), “Sketch Recognition with Natural Correction and Editing”, Association for the Advancement of Artificial Intelligence
11. Deng W.et al. (2013) “Directional Blurred Shape Model Descriptor for Sketched Symbol Recognition”, International Journal ofInformation and Electronics Engineering,.
12. Ahmed S. et al.(2013), “Automatic analysis and sketch based retrieval of architectural floor plans” Published by pattern recognition letters”
13. Circuits” Published by Philosophical Transactions of the Royal Society B.
14. Jos B.T.M. et al (2001) “The Watershed Transform: Definitions, Algorithms and Parallelization Strategies”, Published by Fundamenta Informaticae”.
15. Alvarado C. et al. (2010) “Sketch Recognition for Digital Circuit Design in the Classroom”. Published by Philosophical Transactions of The Royal Society B.
16. Klum S. et al (2011) “Sketch Based Face Recognition: Forensic vs. Composite Sketches” Philosophical Transactions of The Royal Society B.
17. Murali Mohan Babu Y. et al. (2012), “PCA based image denoising”, Published Signal & Image Processing : An International Journal (SIPIJ)

Page 97-110 © MANTECH PUBLICATIONS 2022. All Rights