

Design and Calculations of an Auto-Regulating Solar Dryer for Variety Seedlings Production

Rohan Rastogi¹, Abhishek Sharma², Brijesh Kumar³

Assistant Professor¹, Student^{2,3}

Department of Mechanical Engineering

Genba Sopanrao Moze Institute of Technology

Corresponding Author's Email: -abhi_coll1@gmail.com

Abstract

The use of solar dryers is a sustainable and efficient solution for preserving crops and seeds, especially in areas with abundant sunshine. The design of an auto-regulating solar dryer for variety seedlings production involves considerations and calculations for optimizing its performance. This research paper presents an overview of the key factors to consider in designing a solar dryer for seedlings production, including the selection of materials, thermal insulation, ventilation, and temperature control. Furthermore, the paper outlines the calculations involved in determining the optimal size of the dryer, the required airflow rate, and the time required to dry the seedlings. The results of this research can be used to guide the design and construction of an efficient and effective auto-regulating solar dryer for seedlings production.

Keywords: *Auto-regulating solar dryer, variety seedlings, drying, temperature control, ventilation, thermal insulation, calculations.*

INTRODUCTION

Seedlings are essential for the cultivation of crops and play a critical role in ensuring food security. However, the preservation of seedlings is a significant challenge, especially in areas with high humidity or precipitation. The use of solar dryers is an

effective solution for preserving seedlings, as they offer a sustainable and low-cost method of drying crops. The design of a solar dryer for seedlings production requires careful consideration and calculation to optimize its performance.

Materials:

The selection of materials is critical in the design of a solar dryer for seedlings production. The materials used should be durable, lightweight, and resistant to moisture and heat. Common materials used in the construction of solar dryers include plywood, aluminum, and polycarbonate. The choice of material affects the efficiency of the dryer, as it impacts the absorption, transmission, and reflection of solar radiation. For example, aluminum is a good choice for the frame of the dryer, as it is lightweight, durable, and has high reflectivity. Polycarbonate is a good choice for the covering material, as it is transparent, lightweight, and has good thermal insulation properties.

Thermal insulation:

Thermal insulation is another key consideration in the design of a solar dryer for seedlings production. The dryer should be well-insulated to minimize heat loss and maximize efficiency. The use of insulating materials such as polyurethane foam or fiberglass can help to reduce heat loss and maintain a constant temperature within the dryer. The insulation should be applied to the walls, floor, and roof of the dryer.

Ventilation:

Ventilation is essential in the design of a solar dryer for seedlings production, as it helps to regulate the airflow and maintain a constant temperature. The dryer should be designed with vents that allow for the circulation of air, while also preventing the entry of dust or insects. The design of the vents should be optimized to minimize heat loss and maximize airflow. The vents should be placed in such a way as to promote natural convection and airflow within the dryer.

Temperature control:

Temperature control is a critical consideration in the design of a solar dryer for seedlings production. The dryer should be equipped with a thermostat or other temperature control mechanism that can regulate the temperature within the dryer. The temperature control mechanism should be designed to maintain a constant temperature within the dryer, which is optimal for drying seedlings. A simple thermostat can be used to control the temperature, but more advanced temperature control systems may be required for larger dryers or in areas with extreme weather conditions.

Calculations:

The design of a solar dryer for seedlings production requires several calculations to determine the optimal size of the dryer, the required airflow rate, and the time required to dry the seedlings. The following calculations are necessary:

Calculation of the size of the dryer:

The size of the dryer is determined by the amount of seedlings to be dried and the available solar radiation. The size of the dryer can be calculated using the following formula:

Size of the dryer = Amount of seedlings x
Drying time x Solar radiation x Safety
factor

Calculation of the required airflow rate:

The airflow rate is determined by the size of the dryer and the rate of moisture removal. The required airflow rate can be calculated using the following formula:

Airflow rate = (Size of the dryer x
Moisture removal rate) / Drying time

The moisture removal rate is the rate at which moisture is removed from the seedlings during the drying process.

Calculation of the time required to dry the seedlings:

The time required to dry the seedlings is determined by the moisture content of the seedlings and the available solar radiation. The time required to dry the seedlings can be calculated using the following formula:

Drying time = (Initial moisture content -
Final moisture content) / Moisture removal
rate x Solar radiation

The initial moisture content is the moisture content of the seedlings before drying, and the final moisture content is the desired moisture content after drying.

CONCLUSION

The design of an auto-regulating solar dryer for variety seedlings production requires careful consideration of several factors, including materials selection, thermal insulation, ventilation, and temperature control. The calculations involved in determining the optimal size of the dryer, the required airflow rate, and the time required to dry the seedlings are crucial in optimizing the performance of the dryer. By following the guidelines and calculations presented in this research paper, it is possible to design and construct an efficient and effective auto-regulating solar dryer for seedlings production. Such

a dryer can contribute to sustainable agriculture practices, promote food security, and support the livelihoods of farmers in areas with abundant sunshine.

REFERENCES

1. Omolayo, R., Ogunlade, A., & Olayanju, T. (2020). Development and performance evaluation of a solar dryer for chilli pepper. *Journal of Agricultural Engineering and Technology*, 28(4), 151-161.
2. Demir, H., & Yaldiz, O. (2017). Design and testing of a solar dryer for fruit and vegetable drying. *Drying Technology*, 35(6), 726-736.
3. Esakkimuthu, S., Dhamodharan, D., & Vijayan, S. (2016). Design, fabrication and performance analysis of a solar dryer for spices. *Journal of Food Science and Technology*, 53(4), 1924-1932.
4. Tiwari, G. N., & Singh, H. N. (2019). Development and performance evaluation of an improved solar dryer with thermal energy storage for drying of fruits and vegetables. *Journal of Food Science and Technology*, 56(9), 4053-4063.
5. Yang, Y., Zhang, H., Jiang, H., & Gao, Z. (2019). A numerical study on the thermal performance of a solar greenhouse dryer for tea leaves. *Energy Conversion and Management*, 181, 469-481.