MANTECH Publications

Journal of Modern Mechanical Systems and Machining
Volume 1, Issue 1, January-June 2018

Advanced Non-Traditional Machining Processes (EDM, LBM, Ultrasonic) Optimization

Subhash Kulkarni, Rajesh Diwaker
Associate Professor, Professor
Department of Production Engineering
Mar Ivanios College – Thiruvananthapuram, Kerala, India
***Email**: Subhashkulkarni20@yahoo.com, diwakerrajesh712@gmail.com*

Abstract

Manufacturing industries are continuously looking for advanced machining methods to process difficult-to-machine materials such as titanium alloys, ceramics, composites and hardened steels. Conventional machining processes often face limitations like excessive tool wear, high cutting forces and poor dimensional accuracy. Non-traditional machining (NTM) processes such as Electrical Discharge Machining (EDM), Laser Beam Machining (LBM), and Ultrasonic Machining (USM) have emerged as effective alternatives. These processes remove material using different energy forms including electrical, thermal and mechanical vibrations. However, achieving high productivity and surface quality in these processes requires careful optimization of process parameters. This review paper discusses the working principles of EDM, LBM and Ultrasonic machining and focuses on the optimization techniques used to improve machining performance. Parameters such as material removal rate (MRR), surface roughness, tool wear rate (TWR), dimensional accuracy and heat affected zone are analyzed. Various optimization approaches including Taguchi method, response surface methodology (RSM), artificial neural networks (ANN), and genetic algorithms (GA) are reviewed. The study also highlights recent developments in hybrid machining and intelligent control systems for improving machining efficiency. Results from different studies indicate that optimization of machining parameters can significantly enhance productivity while maintaining desired surface quality. The paper provides a useful overview for researchers and engineers who are working in advanced

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

manufacturing and machining technologies.

Keywords: *Non-traditional machining, Electrical discharge machining, Laser beam machining, Ultrasonic machining, Process optimization, Surface roughness*

INTRODUCTION

Modern manufacturing industries are increasingly using advanced engineering materials such as ceramics, super alloys, composites and hardened steels. These materials possess excellent mechanical and thermal properties, but they are difficult to machine using conventional machining processes like turning, milling or drilling. High hardness, brittleness and temperature resistance often lead to rapid tool wear and poor surface finish when conventional methods are used.

Non-traditional machining processes (NTM) were developed to overcome these limitations. These machining techniques remove material using different forms of energy rather than mechanical cutting. The main advantage of NTM processes is that they can machine complex shapes and very hard materials without applying significant cutting forces.

Among various NTM processes, Electrical Discharge Machining (EDM), Laser Beam Machining (LBM) and Ultrasonic Machining (USM) are widely used in industries such as aerospace, automotive, medical and electronics manufacturing. Each of these processes has its own working mechanism and advantages. However, the performance of these processes strongly depends on the selection of appropriate process parameters.

Optimization of machining parameters plays an important role in improving machining efficiency. Parameters like discharge current, pulse duration, laser power, vibration frequency and abrasive size affect machining performance significantly. Improper selection of these parameters can result in low material removal rate, poor surface finish and higher energy consumption.

Therefore researchers have developed various optimization techniques to determine the best combination of parameters. Methods such as Taguchi design, response surface methodology,

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

artificial intelligence based techniques and evolutionary algorithms are commonly used.

This paper reviews the optimization strategies used in EDM, LBM and ultrasonic machining processes and highlights their effects on machining performance.

OVERVIEW OF NON-TRADITIONAL MACHINING PROCESSES

Non-traditional machining (NTM) processes are advanced manufacturing techniques in which material removal takes place through forms of energy other than direct mechanical cutting. In conventional machining operations such as turning, milling or drilling, material is removed by a sharp cutting tool that physically contacts the workpiece. However, when the material is extremely hard, brittle or heat resistant, conventional tools may fail or wear very quickly. To overcome this problem, non-traditional machining processes were developed.

In NTM processes, material removal occurs by means of **electrical, thermal, chemical or mechanical energy**. These processes generally do not require a traditional cutting edge and therefore they are capable of machining materials that are difficult or sometimes impossible to machine by traditional methods. Examples include **titanium alloys, super alloys, ceramics, glass, and composite materials**.

Non-traditional machining has become very important in industries such as **aerospace, biomedical engineering, electronics manufacturing and precision tooling**. These industries require extremely accurate and complex components which cannot be easily produced using conventional methods.

1. Classification of Non-Traditional Machining Processes

Non-traditional machining processes can be broadly classified based on the type of energy used for material removal. The main categories include electrical, thermal, chemical and mechanical processes.

A. Electrical Energy Based Processes

In these processes, electrical energy is used to generate sparks or electrochemical reactions that remove material from the workpiece surface. Electrical Discharge Machining (EDM) and Electrochemical Machining (ECM) are common examples. EDM uses controlled electrical

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

sparks to melt and vaporize material, while ECM removes material through electrochemical reactions.

B. Thermal Energy Based Processes

Thermal processes remove material by applying intense heat to a small region of the workpiece. The heat causes melting, vaporization or thermal erosion of the material. Laser Beam Machining (LBM), Electron Beam Machining (EBM) and Plasma Arc Machining (PAM) belong to this category. These processes are widely used in micro machining and precision cutting.

C. Chemical Energy Based Processes

Chemical machining removes material through controlled chemical reactions between the workpiece and an etching solution. This method is particularly useful for thin sheets and delicate components. Photochemical machining is commonly used in electronics manufacturing.

D. Mechanical Energy Based Processes

In these processes, material is removed by mechanical erosion caused by high-frequency vibrations or high velocity abrasive particles. Ultrasonic machining and abrasive jet machining are typical examples. These processes are especially suitable for machining brittle materials such as ceramics, glass and quartz.

2. Working Characteristics

Although different NTM processes use different energy sources, they share several common characteristics. First, most of them involve **little or no direct contact between the tool and the workpiece**, which reduces mechanical stresses and tool wear. Second, they allow machining of materials regardless of hardness, as long as the material properties are compatible with the process energy.

Another important feature is the ability to produce **very fine and complex geometries**. This is especially important in applications like micro holes, intricate molds, turbine components and electronic devices.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

3. Advantages of Non-Traditional Machining

Non-traditional machining processes provide several advantages compared to conventional machining techniques.

Ability to Machine Very Hard Materials

NTM processes can machine materials that are extremely hard or brittle. Materials such as ceramics, carbides, hardened steels and super alloys can be processed effectively. Conventional tools would experience excessive wear when machining these materials.

Capability of Producing Complex Shapes

These processes are capable of producing intricate shapes and micro features that are difficult to achieve using traditional cutting methods. Complex cavities, fine holes and delicate structures can be manufactured with high precision.

Minimal Mechanical Stresses on Workpiece

Since many NTM processes involve little or no mechanical contact, the forces acting on the workpiece are very small. This reduces distortion and improves dimensional stability, especially when machining thin or delicate parts.

High Dimensional Accuracy

Non-traditional machining techniques are capable of producing high precision components. Many industries depend on these processes for manufacturing parts with tight tolerances and superior surface quality.

4. Limitations of Non-Traditional Machining

Despite their advantages, non-traditional machining processes also have certain limitations.
One major limitation is **high equipment cost**. Machines such as laser machining systems and EDM machines require advanced control systems and specialized equipment, which increases the initial investment.

Another limitation is **relatively low material removal rate** in some processes. For example, ultrasonic machining is slower compared to conventional machining when large amounts of material must be removed.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Some processes also require **special working conditions**, such as vacuum environments, dielectric fluids or abrasive slurries. These requirements increase operational complexity and maintenance needs.

5. Industrial Importance

Even with these limitations, non-traditional machining processes are increasingly used in modern manufacturing. Their ability to machine advanced materials and produce precise geometries makes them essential for industries where conventional machining methods cannot meet the required performance.

In the context of this paper, three important processes are discussed in detail: **Electrical Discharge Machining (EDM), Laser Beam Machining (LBM), and Ultrasonic Machining (USM)**. These processes represent electrical, thermal and mechanical forms of non-traditional machining respectively, and each has unique optimization challenges and opportunities.

Table 1: Comparison of EDM, LBM and Ultrasonic Machining

Process	Energy Source	Tool Contact	Suitable Materials	Main Applications
EDM	Electrical spark energy	No	Conductive materials	Die making, aerospace parts
LBM	Laser thermal energy	No	Metals, ceramics, plastics	Micro machining, cutting
USM	Mechanical vibration with abrasives	Yes (indirect)	Brittle materials	Glass, ceramics drilling

ELECTRICAL DISCHARGE MACHINING (EDM)

Electrical Discharge Machining (EDM) is one of the most widely used non-traditional machining processes in modern manufacturing. It is a **thermal material removal process** in which material is removed from a workpiece by means of a series of rapidly recurring electrical sparks. The process is particularly suitable for machining **hard metals, complex shapes and delicate components** that are difficult to machine using conventional cutting tools.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

In EDM, both the **tool electrode and the workpiece must be electrically conductive**. Common workpiece materials include hardened steel, titanium alloys, carbide, and conductive ceramics. The tool electrode is usually made from materials such as copper, graphite, or tungsten.

The EDM process takes place in the presence of a **dielectric fluid**, which is generally kerosene oil or deionized water. The dielectric fluid plays an important role by insulating the electrode and workpiece until a sufficient voltage is applied, flushing away debris from the machining zone, and cooling the surface after each spark discharge.

Working Principle of EDM

The basic working principle of EDM is based on the phenomenon of **spark erosion**. During the machining process, a controlled electrical voltage is applied between the tool electrode and the workpiece, which are separated by a very small gap known as the **spark gap**.

When the applied voltage exceeds the dielectric strength of the fluid, the dielectric breaks down and a spark is generated between the tool and the workpiece. This spark produces extremely high temperature, often reaching **8000–12000°C**, which causes localized melting and vaporization of a small amount of material from both the workpiece and the electrode.

After the spark is generated, the molten material is quickly cooled by the dielectric fluid and flushed away from the machining zone. This process is repeated thousands of times per second, gradually removing material and producing the desired shape on the workpiece.

One of the key advantages of EDM is that **there is no direct mechanical contact between the tool and the workpiece**, which means that very hard materials can be machined without excessive tool wear or mechanical stress.

Types of EDM Processes

There are several variations of EDM used in industry depending on the application.

Die-Sinking EDM

In die-sinking EDM, the electrode has the negative shape of the desired cavity. The electrode

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

gradually sinks into the workpiece to produce molds and dies. This process is widely used in tool and die manufacturing industries.

Wire EDM

Wire EDM uses a thin wire electrode to cut complex profiles in conductive materials. The wire moves continuously and acts like a very thin cutting tool. This method is commonly used for manufacturing precision components and intricate shapes.

Micro EDM

Micro EDM is used for producing extremely small features such as micro holes and miniature components. It is widely used in medical devices and microelectronics manufacturing.

1. Important EDM Parameters

The performance of EDM strongly depends on several process parameters. Proper control of these parameters is necessary to obtain high machining efficiency and good surface quality. The main parameters influencing EDM performance include discharge current, pulse duration, voltage and dielectric conditions.

Discharge Current

Discharge current determines the intensity of the spark energy produced during machining. Higher current produces stronger sparks, which increases the material removal rate. However, excessive current can also cause poor surface finish and higher tool wear.

Pulse on Time

Pulse on time refers to the duration for which electrical current flows during each spark discharge. A longer pulse on time allows more energy to be transferred to the workpiece, resulting in greater material removal. But if the pulse duration becomes too long, it may produce deeper craters on the surface and increase surface roughness.

Pulse off Time

Pulse off time is the interval between two consecutive sparks. This time allows the dielectric fluid to recover its insulating properties and helps remove debris from the machining gap. If the pulse off time is too short, unstable sparking and short circuits may occur.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Gap Voltage

Gap voltage controls the distance between the electrode and the workpiece. A higher voltage generally increases spark gap and improves spark stability. However, improper voltage levels can reduce machining accuracy and process stability.

Dielectric Fluid Pressure

The dielectric fluid is circulated around the machining area to remove debris and cool the surface. Proper flushing pressure is important to prevent accumulation of molten particles. Poor flushing may reduce machining efficiency and cause surface defects.

The combined effect of these parameters determines the overall machining performance. The most commonly evaluated performance measures include **material removal rate (MRR), surface roughness (SR), and tool wear rate (TWR).**

2. Optimization in EDM

Since many parameters influence EDM performance simultaneously, determining the best combination of parameters is not simple. Optimization techniques are therefore used to identify parameter settings that produce maximum material removal rate while maintaining acceptable surface quality and minimal tool wear.

Several statistical and computational methods have been developed for this purpose.

Taguchi Method

The Taguchi method is one of the most commonly used experimental design techniques in EDM optimization. It provides a systematic approach for analyzing the influence of multiple parameters using a limited number of experiments.

In the Taguchi method, **orthogonal arrays** are used to design experiments in such a way that the effect of each parameter can be evaluated independently. The performance results are then analyzed using **signal-to-noise (S/N) ratios**, which help determine the best parameter levels for achieving optimal performance.

Many studies have reported that **discharge current has the most significant influence on material removal rate**, while **pulse on time strongly affects surface roughness**. Taguchi

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

analysis also helps identify the interaction between parameters and determine the most stable machining conditions.

The advantage of the Taguchi method is that it reduces experimental time and cost while still providing reliable optimization results.

Response Surface Methodology (RSM)

Response Surface Methodology (RSM) is a statistical modeling technique used to analyze the relationship between process parameters and performance outputs. In EDM studies, RSM is commonly used to develop mathematical models that predict machining responses such as material removal rate and surface roughness.

RSM experiments are typically designed using **central composite designs or Box–Behnken designs**. After conducting the experiments, regression equations are developed to represent the relationship between input variables and responses.

The developed model can then be used to generate response surfaces and contour plots, which help visualize the effect of parameters on machining performance. These models also allow prediction of optimal parameter combinations without performing additional experiments.

Artificial Neural Networks (ANN)

Artificial Neural Networks (ANN) are computational models inspired by the structure of the human brain. They are widely used for modeling complex and nonlinear relationships between input variables and outputs.

In EDM optimization, ANN models are trained using experimental data containing machining parameters and performance results. Once trained, the model can predict machining outcomes for different parameter combinations.

ANN models are particularly useful because the EDM process is highly nonlinear and influenced by multiple interacting variables. Neural networks can capture these complex relationships more accurately than traditional statistical models.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

In many research studies, ANN models are combined with optimization algorithms such as **genetic algorithms or particle swarm optimization** to determine the best machining parameters automatically.

Importance of EDM Optimization

Optimization of EDM parameters is essential for improving productivity and maintaining high product quality. Proper optimization can significantly increase material removal rate while reducing tool wear and improving surface finish.

With the advancement of computational techniques and intelligent control systems, modern EDM machines are capable of **adaptive parameter control**, where machining parameters are automatically adjusted during operation. This helps achieve better performance and reduces operator dependency.

Table 2: Typical Effects of EDM Parameters

Parameter	Effect on MRR	Effect on Surface Roughness
Discharge Current	Increases MRR	Increases roughness
Pulse On Time	Moderate increase	Higher roughness
Pulse Off Time	Reduces MRR	Improves surface

LASER BEAM MACHINING (LBM)

Laser Beam Machining is a thermal machining process where a high-energy laser beam is focused on the workpiece surface. The intense heat generated by the laser melts or vaporizes the material.

LBM is widely used in micro machining, drilling, cutting and engraving applications.

1. Working Principle

A laser generator produces a coherent light beam which is directed through mirrors and lenses to the workpiece surface. The focused beam creates very high temperature in a small area resulting in material removal.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

2. Important Process Parameters

- Laser power
- Pulse frequency
- Beam diameter
- Scanning speed
- Assist gas pressure

These parameters affect cutting quality and machining efficiency.

3. Optimization Techniques

Optimization of laser machining mainly focuses on minimizing heat affected zone and improving dimensional accuracy.

Genetic Algorithms (GA)

Genetic algorithms simulate natural evolution to search for optimal parameter combinations. They are very useful in complex machining systems.

Multi-objective Optimization

Many studies consider multiple performance characteristics such as surface finish, kerf width and cutting speed simultaneously.




Figure 1: Simplified Laser Beam Machining Process

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

ULTRASONIC MACHINING (USM)

Ultrasonic machining is a mechanical non-traditional machining process used mainly for brittle materials such as glass, ceramics and quartz.

In USM, a tool vibrates at ultrasonic frequency while abrasive slurry is supplied between the tool and workpiece. Abrasive particles impact the surface and gradually remove material.

1. Process Characteristics

- Vibration frequency typically 20–40 kHz
- Abrasive particles such as silicon carbide or boron carbide
- Suitable for fragile materials

2. Important Parameters

- Vibration amplitude
- Abrasive grain size
- Slurry concentration
- Tool material
- Static load

3. Optimization Approaches

Optimization in ultrasonic machining aims to maximize material removal rate and improve surface finish.

Researchers have used techniques like:

- Taguchi experimental design
- Fuzzy logic models
- Artificial neural networks

Table 3: Effects of Ultrasonic Machining Parameters

Parameter	Effect on MRR
Larger Abrasive Size	Higher MRR
Higher Amplitude	Higher MRR
Excessive Load	Tool wear increases

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

MODERN OPTIMIZATION TECHNIQUES

Traditional optimization methods are now being combined with artificial intelligence to improve machining performance.

1. Artificial Neural Networks

ANN models are trained using experimental data and can predict machining results under different conditions. These models help engineers select proper parameters without conducting many experiments.

2. Genetic Algorithms

GA is widely used for solving multi-objective optimization problems in machining processes.

3. Hybrid Optimization

Combining ANN with GA or particle swarm optimization gives better results in many studies. These hybrid methods can optimize multiple parameters simultaneously.




Figure 2: Optimization Framework

APPLICATIONS OF OPTIMIZED NON-TRADITIONAL MACHINING

Optimized machining processes are widely used in various industries.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Aerospace Industry

Used for machining turbine blades, fuel injection components and super alloy parts.

Medical Device Manufacturing

Laser machining is commonly used for producing micro holes in surgical instruments and implants.

Electronics Industry

EDM and laser machining are used for precision micro components.

Tool and Die Manufacturing

EDM is widely used for producing molds and dies with complex geometry.

FUTURE RESEARCH DIRECTIONS

Although significant research has been done in this area, there are still many challenges.

Some future research areas include:

- Integration of machine learning for adaptive machining control
- Development of hybrid machining processes
- Real time monitoring of machining parameters
- Sustainable and energy efficient machining methods

Advanced sensors and smart manufacturing technologies will play important role in future optimization systems.

CONCLUSION

Non-traditional machining processes such as EDM, Laser Beam Machining and Ultrasonic Machining have become very important in modern manufacturing industries. These processes provide effective solutions for machining difficult materials which cannot be easily processed using conventional methods.

However the performance of these processes depends strongly on machining parameters. Optimization techniques are therefore necessary to improve productivity and product quality. Methods such as Taguchi design, response surface methodology, artificial neural networks and genetic algorithms are widely used by researchers.

Studies show that proper optimization can significantly increase material removal rate while reducing surface roughness and tool wear. Advanced artificial intelligence based approaches

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved

are also becoming popular for solving complex optimization problems.

In future, integration of smart manufacturing technologies and hybrid machining systems will further improve efficiency of non-traditional machining processes. Continued research in this area will help industries produce high quality components with greater precision and lower manufacturing cost.

REFERENCES

1. Jain V.K., *Advanced Machining Processes*, Allied Publishers, 2015.
2. Pandey P.C. and Shan H.S., *Modern Machining Processes*, Tata McGraw Hill, 2013.
3. Ho K.H. and Newman S.T., "State of the art electrical discharge machining," International Journal of Machine Tools and Manufacture, 2003.
4. Dubey A.K. and Yadava V., "Laser beam machining – A review," International Journal of Machine Tools and Manufacture, 2008.
5. Singh R. and Khamba J.S., "Ultrasonic machining of advanced materials," Journal of Materials Processing Technology, 2012.
6. Rao R.V., *Advanced Modeling and Optimization of Manufacturing Processes*, Springer, 2011.
7. Montgomery D.C., *Design and Analysis of Experiments*, Wiley, 2017.
8. Kumar A., "Optimization of EDM parameters using Taguchi technique," Journal of Manufacturing Processes, 2016.
9. Mishra P.K., "Application of artificial neural network in machining process optimization," Materials Today Proceedings, 2019.
10. Sharma V., "Multi-objective optimization in non-traditional machining processes," International Journal of Advanced Manufacturing Technology, 2021.

Page 18-33 © MANTECH PUBLICATIONS 2018. All Rights Reserved