MANTECH Publications

Journal of Modern Mechanical Systems and Machining
Volume 1, Issue 2, July-December 2018

Collaborative Robotics (Cobots) in Machining Cells

Rajan K. Patil[1], Meena S. Chaudhary[2]
Associate Professor, Assistant Professor
Department of Robotics and Intelligent Manufacturing
Maharaja's College – Ernakulam, Kerala, India
Email: *Rajanpatilk1k@yahoo.com[1], meenaschaudhary21@rediffmail.com[2]*

Abstract

Modern manufacturing industries are moving towards automation and intelligent production systems. In recent years, collaborative robots, also known as cobots, have become an important technology in machining cells. Unlike traditional industrial robots, cobots are designed to work safely together with human operators in a shared workspace. These robots assist workers in tasks such as machine loading and unloading, part handling, inspection and assembly operations. The integration of cobots in machining cells helps to increase productivity, improve product quality and reduce operator fatigue. Small and medium scale industries especially benefit from cobots because they are relatively easy to program and require less space compared to traditional robotic systems. This paper presents a review on collaborative robotics in machining environments. The study discusses the concept of cobots, their architecture, major components and applications in machining cells. Advantages and limitations of cobot systems are also explained. Further, the role of sensors, vision systems and safety mechanisms used in collaborative robots is discussed. Finally, future trends and challenges in cobot based machining systems are highlighted. The review indicates that collaborative robotics will play a very important role in the next generation smart manufacturing systems.

Keywords: *Collaborative robots, machining automation, cobots, human-robot collaboration, smart manufacturing, industrial robotics*

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

INTRODUCTION

Manufacturing industries are continuously adopting advanced technologies in order to increase productivity and maintain competitiveness in global markets. Automation has been one of the most important developments in modern manufacturing systems. Traditionally, industrial robots have been used for tasks such as welding, painting and assembly operations. However, these robots generally operate in isolated environments because of safety concerns. Human workers and robots usually cannot share the same workspace.

In recent years, collaborative robotics has emerged as a new approach to industrial automation. Collaborative robots, commonly called cobots, are specially designed robots that can safely work together with humans in a shared workspace. These robots are equipped with sensors, vision systems and advanced control algorithms that allow them to detect human presence and adjust their movements accordingly.

Machining cells are widely used in manufacturing industries for operations such as turning, milling, drilling and grinding. These cells often require repetitive tasks like loading raw material, unloading finished parts, part inspection and tool replacement. Such activities can be time consuming and physically demanding for workers. The introduction of cobots in machining cells helps to automate these tasks while still keeping human operators involved in the production process.

Another important reason for the adoption of collaborative robots is the increasing shortage of skilled labor in many industries. Cobots assist operators by performing repetitive work and allowing workers to focus on more complex tasks such as programming, quality inspection and process planning.

This paper presents a review of collaborative robotics technology and its application in machining cells. The main aim is to discuss the structure, operation and benefits of cobots in modern manufacturing systems.

CONCEPT OF COLLABORATIVE ROBOTICS

Collaborative robotics refers to a modern approach in industrial automation where robots and human workers operate together in the same workspace. Unlike traditional industrial robots

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

that usually work behind safety fences or cages, collaborative robots are specially designed to safely interact with humans. These robots assist workers in performing different tasks while maintaining a safe and controlled working environment. The main goal of collaborative robotics is to combine the accuracy, speed and repeatability of robots with the intelligence, flexibility and decision-making ability of human operators.

In conventional robotic systems, safety barriers are necessary because industrial robots move with high speed and force. If a human enters the robot working area accidentally, it can cause serious injury. Because of this reason, traditional robots are normally isolated from workers. However, collaborative robots are built with advanced safety mechanisms that allow them to operate close to human workers without the need for large safety cages. This makes them suitable for flexible manufacturing environments where humans and machines must cooperate with each other.

The idea of collaborative robots was introduced during the 1990s by researchers who wanted to develop robots that could physically assist humans instead of replacing them. The term “cobot” was first used to describe robots that share tasks with humans in a cooperative manner. Since then, cobot technology has developed rapidly due to improvements in sensors, computing systems and control algorithms.

Collaborative robots generally have lightweight mechanical structures and rounded edges to reduce the risk of injury during accidental contact. Many cobots are designed using aluminum or composite materials so that the total weight of the robot is relatively low. In addition, their motors are programmed to limit the amount of force and torque that can be applied during operation. If the robot detects unusual resistance or collision, the system automatically stops or slows down the movement.

One of the important characteristics of collaborative robotics is force sensing capability. Many cobots are equipped with force and torque sensors placed at the robot joints or at the end effector. These sensors continuously monitor the interaction forces between the robot and its environment. When unexpected contact occurs, the control system quickly responds by stopping the robot motion or reducing its speed. This feature ensures safe collaboration between human workers and robotic systems.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Another important feature of cobots is ease of programming. Traditional industrial robots often require complex programming languages and specialized engineers to configure them. In contrast, collaborative robots are designed with user-friendly programming interfaces. Operators can simply move the robot arm manually to demonstrate the desired motion. The robot records these movements and stores them as part of the program. This process is known as “teach-by-demonstration” or “hand guiding”. Because of this feature, even workers with limited programming knowledge can operate cobots efficiently.

Collaborative robotics also supports flexible manufacturing systems. In many industries, production requirements change frequently due to customized products or varying demand. Cobots can be quickly reprogrammed and redeployed for different tasks such as part handling, machine tending, packaging or inspection. This flexibility makes them highly suitable for small and medium scale manufacturing companies where production volumes may not justify large automated systems.

Human–robot collaboration can occur in different forms depending on the level of interaction between the worker and the robot. In some cases, humans and robots work on separate parts of the same task but within the same workspace. In other situations, both may directly cooperate to complete a shared operation. For example, a worker may position a component while the robot performs tightening or assembly tasks.

Another advantage of collaborative robotics is improved ergonomics for workers. Many manufacturing operations involve repetitive or physically demanding tasks such as lifting heavy parts or performing continuous loading and unloading of machines. Cobots can handle these repetitive tasks, reducing worker fatigue and risk of musculoskeletal injuries. As a result, human workers can focus on more skilled activities such as supervision, inspection and decision making.

Collaborative robots are currently used in a wide range of industrial sectors. In machining cells, cobots assist in loading and unloading parts from CNC machines. In electronics manufacturing, they help assemble delicate components with high precision. In packaging industries, cobots perform sorting and packing operations. They are also used for quality inspection, welding assistance and laboratory automation.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

With continuous developments in artificial intelligence, machine vision and sensor technology, collaborative robotics is becoming more capable and intelligent. Future cobots are expected to learn from human behavior, adapt to changing working conditions and perform more complex tasks in manufacturing environments.

STRUCTURE OF A MACHINING CELL WITH COBOTS

A machining cell is a small manufacturing unit where different machines and supporting equipment are arranged together to perform specific production tasks. Normally, a machining cell includes machine tools such as CNC milling machines, turning centers or drilling machines along with supporting systems like material handling devices and control units. The main objective of a machining cell is to improve productivity by organizing machines and processes in an efficient manner.

When collaborative robots (cobots) are integrated into machining cells, the structure of the cell becomes more flexible and automated. Cobots work alongside human operators and machine tools to perform repetitive or physically demanding tasks such as loading raw materials, unloading finished components and transferring parts between machines. This integration helps to reduce idle time of machines and increases the overall production efficiency.

A typical cobot-based machining cell consists of several important components which work together in a coordinated way. These components include machine tools, collaborative robots, material storage units, sensing systems and a central control system.

1. Machine Tools

Machine tools are the primary equipment in a machining cell. These machines perform the actual material removal operations required to produce finished components. Examples include CNC lathes, milling machines, drilling machines and grinding machines.

In a cobot-based machining cell, the machine tool usually operates automatically once the workpiece is properly loaded. The collaborative robot places the raw material into the machine fixture or chuck and starts the machining cycle. After the machining process is completed, the robot removes the finished component and places it in a designated storage location. This reduces the need for manual handling and allows the machine to operate continuously.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

2. Collaborative Robot

The collaborative robot is one of the most important elements in the machining cell. It acts as a material handling system that interacts directly with the machine tool and the human operator. Cobots are usually installed near the machine tool so that they can easily reach the loading and unloading area.

The robot arm moves with multiple degrees of freedom, allowing it to pick up workpieces from trays or conveyors and place them accurately in the machine tool. In many cases, the robot is equipped with grippers or vacuum suction cups that hold the workpiece securely during handling.

Because cobots are designed for safe human interaction, operators can work close to the robot without the need for protective cages. This allows a compact and efficient cell layout.

3. Material Storage and Feeding System

Material storage systems are used to store raw materials and finished components within the machining cell. These systems may include trays, pallets, racks or conveyor belts. The collaborative robot picks raw parts from the storage unit and delivers them to the machine tool. After machining is completed, the robot transfers the finished parts to another tray or container. In advanced systems, automated conveyors may transport parts to other machining stations or inspection areas.

Efficient material handling systems are important for maintaining smooth production flow in machining cells.

4. Vision and Sensing Systems

Vision systems and sensors are often integrated into cobot-based machining cells to improve accuracy and reliability. Cameras and image processing software can identify the orientation and position of parts before the robot picks them up.

For example, if components are randomly placed in a tray, the vision system detects their exact location and guides the robot to pick them correctly. Sensors can also detect the presence of parts, check alignment and monitor machine status.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

These sensing technologies help to reduce errors and improve the automation level of the machining cell.

5. Control and Communication System

The control system coordinates the operation of all components within the machining cell. It ensures that the collaborative robot, machine tools and other devices work in synchronization. The control unit receives signals from sensors and sends commands to both the robot and the machine tool. For example, once the robot loads a workpiece into the machine, the control system starts the machining cycle. After machining is finished, the system signals the robot to remove the part.

Modern machining cells often use industrial communication networks to allow real time data exchange between machines, robots and monitoring systems.

6. Human Operator Interface

Even though machining cells are highly automated, human operators still play an important role. Workers supervise the operation, load raw material trays, inspect finished parts and handle maintenance activities.

Cobots are designed to assist human workers rather than replace them. Operators can easily interact with the robot, modify programs or guide the robot arm manually to teach new tasks.




Figure 1: Typical Collaborative Machining Cell Layout

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Table: 1

Component	Function
CNC Machine	Performs machining operations
Collaborative Robot	Handles part loading/unloading
Vision System	Identifies parts and orientation
Safety Sensors	Detect human presence
Control System	Coordinates machine and robot

MAJOR COMPONENTS OF COLLABORATIVE ROBOTS

Collaborative robots are designed with a combination of mechanical structures, electronic devices and intelligent control systems. These components work together to enable safe interaction between robots and human operators. Unlike traditional industrial robots, cobots are developed with special attention to safety, flexibility and ease of use. Each component of the robot plays an important role in achieving accurate motion, safe operation and efficient task performance.

A typical collaborative robot system includes a robot manipulator, sensors, a control system and end effectors. In addition to these main elements, other supporting components such as actuators, communication interfaces and safety systems are also used to improve the overall performance of the robot.

1. Robot Manipulator

The robot manipulator is the main mechanical structure of a collaborative robot. It is often referred to as the robotic arm because it performs movements similar to a human arm. The manipulator consists of several rigid links connected by joints. These joints allow rotational or linear motion, which gives the robot the ability to move in different directions.

Most collaborative robots have between four and seven degrees of freedom. A higher number of degrees of freedom allows the robot to perform more flexible and complex movements. For example, the robot can reach around obstacles, adjust the orientation of tools or access different locations within the workspace.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

The manipulator is usually made of lightweight materials such as aluminum alloys or advanced composite materials. These materials help to reduce the overall weight of the robot while maintaining sufficient strength and stiffness. Lightweight construction is very important in collaborative robots because it reduces the impact force if accidental contact occurs with a human worker.

Another important feature of the manipulator is smooth and compact design. Cobots generally have rounded edges and enclosed joints to avoid sharp surfaces that could cause injury. Electric motors placed inside the joints provide the required motion for the robot arm. These motors are carefully controlled to maintain precise positioning and smooth movement.

The manipulator allows the collaborative robot to perform a wide range of tasks such as picking and placing objects, loading machine tools, assembling components and performing inspection operations.

2. Sensors

Sensors are one of the most critical components of collaborative robots. They enable the robot to perceive its surroundings and interact safely with humans and objects. In collaborative environments, sensors continuously monitor the robot's position, motion and external forces.

Force and torque sensors are widely used in cobots. These sensors measure the forces acting on the robot joints or end effector. If the robot comes into contact with a human or an unexpected object, the sensor immediately detects the force change. The control system then stops the robot or reduces its speed to prevent injury.

Proximity sensors are also used to detect nearby objects or human presence. These sensors help the robot maintain a safe distance from workers. In some systems, the robot automatically slows down when a person approaches the workspace.

Vision cameras are another important sensing device used in collaborative robotics. Vision systems allow the robot to identify objects, determine their orientation and guide the robot during part handling operations. Image processing software analyzes camera data and provides information to the robot controller.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Position encoders are installed in robot joints to measure the exact position and movement of each joint. These sensors ensure accurate motion control and precise positioning of the robot arm. Without these sensors, the robot would not be able to maintain consistent accuracy during operations.

All these sensors together provide real time information to the robot control system, allowing the robot to respond quickly to changes in its environment.

3. Control System

The control system acts as the central processing unit or "brain" of the collaborative robot. It receives signals from sensors, processes the data and sends commands to the robot actuators. The control system ensures that the robot moves accurately and performs tasks according to programmed instructions.

Modern cobot controllers use advanced algorithms for motion planning, trajectory control and safety monitoring. These algorithms calculate the required joint movements to achieve the desired position and orientation of the robot arm.

The control system also manages the speed and force of the robot. Since collaborative robots operate close to human workers, their speed and power must be carefully regulated. If abnormal conditions are detected, such as unexpected contact or excessive force, the controller immediately stops the robot motion.

Another important function of the control system is communication with other machines and devices in the manufacturing cell. The robot controller can exchange data with CNC machines, sensors and monitoring systems through industrial communication networks. This allows coordinated operation between the robot and other equipment.

Many collaborative robots are designed with user-friendly interfaces, such as touch screens or graphical programming environments. These interfaces allow operators to easily program tasks, adjust parameters and monitor robot performance.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

4. End Effectors

End effectors are tools or devices attached to the end of the robot manipulator. They act as the "hand" of the robot and enable it to interact with objects in the workspace. The design of the end effector depends on the type of task the robot is required to perform.

Grippers are the most commonly used end effectors in collaborative robotics. They are used to grasp and hold objects securely during handling operations. Grippers can be mechanical, pneumatic or electric depending on the application.

Vacuum suction cups are also widely used for handling flat or lightweight objects. These devices use suction force to hold components without applying excessive mechanical pressure. In machining cells, robotic grippers are commonly used to pick up raw materials and place them into machine tools. After machining is completed, the robot uses the gripper to remove the finished part and transfer it to a storage tray.

Other types of end effectors include welding torches, screwdrivers, polishing tools and inspection probes. By changing the end effector, the same collaborative robot can perform multiple tasks within the manufacturing process.

APPLICATIONS OF COBOTS IN MACHINING CELLS

Collaborative robots are widely used in different tasks within machining environments.

1. Machine Tending

Machine tending refers to loading raw materials into machine tools and unloading finished parts. This is one of the most common applications of cobots in machining cells.

The robot picks up a workpiece, places it in the machine chuck and starts the machining cycle. After machining is completed, the robot removes the finished component and loads a new part.

2. Part Inspection

Cobots can also assist in quality inspection processes. Vision systems and sensors are integrated with the robot to check dimensions, surface finish and presence of defects.

The robot positions the part in front of cameras or measurement devices for inspection.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

3. Assembly Operations

Some machining cells include secondary assembly operations. Collaborative robots can perform tasks such as inserting fasteners, placing small components and tightening screws.

4. Tool Handling

In certain advanced machining systems, cobots are used to assist in tool replacement and tool management operations. This helps in reducing machine downtime.

ADVANTAGES OF USING COBOTS IN MACHINING CELLS

Collaborative robots offer several advantages compared to traditional automation systems.

Table: 2

Advantage	Description
Improved Safety	Sensors and control systems allow safe human interaction
Higher Productivity	Machines can operate continuously with less idle time
Flexibility	Easy reprogramming for different tasks
Reduced Labor Fatigue	Robots handle repetitive operations
Compact Design	Cobots require less floor space

Another important advantage is lower implementation cost compared to traditional industrial robots. Many small and medium manufacturing companies are adopting cobots because they are easier to install and operate.

CHALLENGES AND LIMITATIONS

Although collaborative robotics provides many benefits, there are also some limitations.
One challenge is the relatively lower payload capacity of cobots compared to conventional industrial robots. Heavy machining parts may require stronger robotic systems.

Another limitation is the slower operational speed. In order to maintain safety, cobots often move at reduced speeds when humans are nearby.

Programming and integration of cobots with existing machines may also require technical

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

expertise. Additionally, safety certification and compliance with international standards can increase system cost.

SAFETY MECHANISMS IN COLLABORATIVE ROBOTS

Safety is one of the most important aspects of collaborative robotics. Various safety techniques are used to ensure that human workers are protected during operation.

Some common safety mechanisms include:

1. **Power and Force Limiting** – Limits the force generated by the robot to avoid injuries.
2. **Speed and Separation Monitoring** – Robot slows down when humans are detected nearby.
3. **Hand Guiding** – Allows operators to manually guide the robot for programming.
4. **Emergency Stop Systems** – Immediately stop robot motion in case of danger.

These mechanisms are defined in international standards such as ISO 10218 and ISO/TS 15066 for collaborative robot safety.

FUTURE TRENDS IN COLLABORATIVE MACHINING SYSTEMS

Collaborative robotics technology is continuously evolving with new innovations.
Some future developments include:

- Integration with Artificial Intelligence for adaptive learning
- Advanced vision systems for complex part recognition
- Cloud based monitoring and control
- Integration with digital twin technology
- Autonomous decision making in machining processes

These technologies will allow cobots to perform more complex tasks and improve the overall efficiency of manufacturing systems.

DISCUSSION

The use of collaborative robots in machining cells represents an important step toward smart manufacturing. Unlike traditional automation systems, cobots create a balanced environment where both humans and machines contribute to the production process.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Human operators provide decision making ability and adaptability, while robots offer precision, repeatability and endurance. The combination of these capabilities results in improved productivity and quality.

Industries such as automotive, aerospace and electronics manufacturing are already using cobots in machining and assembly processes. In addition, small and medium enterprises are also adopting collaborative robots because of their flexibility and relatively lower cost.

However, successful implementation requires careful planning. Factors such as workspace design, safety measures, robot programming and operator training must be considered.

CONCLUSION

Collaborative robotics has become a promising technology in modern manufacturing systems. Cobots allow safe interaction between humans and robots, which makes them suitable for many industrial applications including machining cells.

The integration of cobots in machining environments improves productivity, reduces manual labor and increases process flexibility. These robots assist operators in tasks such as machine tending, inspection, assembly and material handling.

Although there are some challenges such as limited payload capacity and slower speeds, ongoing research and technological advancements are expected to overcome these limitations. In the future, collaborative robots combined with artificial intelligence, digital twins and smart sensors will create highly efficient and intelligent machining systems.

Overall, collaborative robotics will play a significant role in the development of next generation manufacturing technologies.

REFERENCES

1. P. Corke, *Robotics, Vision and Control*, Springer, 2017.
2. B. Siciliano and O. Khatib, *Springer Handbook of Robotics*, Springer, 2016.
3. M. Peshkin and J. Edward, “Collaborative robots in industrial environments,” *Industrial Robot Journal*, 2018.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved

4. S. Haddadin, A. Albu-Schäffer and G. Hirzinger, "Requirements for safe robots," *International Journal of Robotics Research*, 2017.
5. R. Kumar and D. Patel, "Automation in CNC machining cells," *Journal of Manufacturing Systems*, 2019.
6. Gupta and P. Sharma, "Human robot collaboration in smart manufacturing," *Manufacturing Technology Review*, 2020.
7. J. Kruger, T. Lien and A. Verl, "Cooperation of human and machines in assembly lines," *CIRP Annals*, 2019.
8. S. Bogue, "Growth of collaborative robots in industry," *Industrial Robot: An International Journal*, 2018.
9. M. Rahman and K. Lee, "Applications of cobots in manufacturing," *International Journal of Advanced Manufacturing Technology*, 2021.
10. L. Wang, Y. Zhang and J. Gao, "Smart factories and collaborative automation," *Procedia Manufacturing*, 2020.

Page 102-116 © MANTECH PUBLICATIONS 2018. All Rights Reserved