MANTECH Publications

Journal of Product Design, Quality Engineering & Technology
Volume 11, Issue 2, May-August 2026
SSN: 3139-2008 (Online)

Lifecycle-Based Eco-Design Framework Using Circular Economy Principles to Enhance Product Reliability and Manufacturing Quality

Sachin Oberoi[1], Hema Naidu[2]

ABSTRACT

The rapid acceleration of industrial production and shortened product lifecycles have intensified resource depletion and environmental degradation, forcing a paradigm shift toward sustainable manufacturing. Conventional eco-design approaches often treat environmental sustainability, product reliability, and manufacturing quality as competing objectives, leading to compromised structural integrity, premature component failure, or elevated end-of-life waste. This paper proposes a novel, comprehensive Lifecycle-Based Eco-Design Framework that seamlessly integrates Circular Economy (CE) principles into the early design, material selection, and manufacturing stages to concurrently enhance product reliability and manufacturing quality. The framework employs a closed-loop topology combining Design for Disassembly (DfD), Design for Remanufacturing (DfR), Failure Mode and Effects Analysis embedded with environmental impact scoring (Eco-FMEA), and sensor-driven quality control feedback loops. A multi-objective optimization model utilizing a Genetic Algorithm (GA) is introduced to balance material circularity index (MCI), mean time between failures (MTBF), total carbon footprint, and manufacturing process yield. Experimental and simulation-based validation conducted on complex electro-mechanical assemblies demonstrates that the proposed framework achieves a 38.4% reduction in lifecycle greenhouse gas emissions, a 29.2% increase in resource recovery rate, and a 22.5% improvement in operational reliability (MTBF) compared to standard linear design baselines. Furthermore, manufacturing defect rates were reduced by 18.6% through closed-loop quality parameter tuning. This research establishes a quantitative, actionable

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

engineering roadmap for transforming linear industrial systems into closed-loop, resilient, and high-quality circular manufacturing ecosystems.

KEYWORDS: *Eco-Design, Circular Economy, Product Reliability, Manufacturing Quality, Design for Remanufacturing, Life Cycle Assessment, Quality Function Deployment.*

INTRODUCTION

The global industrial sector is facing unprecedented pressure arising from resource scarcity, regulatory mandates, and rising environmental degradation [1]. For decades, modern manufacturing has adhered to a linear paradigm—commonly characterized as the 'take-make-dispose' model—where raw materials are extracted, processed into high-value components, utilized during a finite operational lifespan, and ultimately discarded into landfills [2]. This linear approach not only accelerates ecological destruction and carbon emissions but also exposes global supply chains to extreme price volatility and critical raw material shortages [3]. To counteract these systemic vulnerabilities, the concept of the Circular Economy (CE) has emerged as an essential industrial alternative, aiming to decouple economic growth from finite resource consumption through perpetual material loops, continuous reuse, remanufacturing, and recycling [4].

Despite the undeniable environmental benefits of circularity, transitioning from a linear model to a circular manufacturing framework presents substantial engineering challenges [5]. Historically, product development frameworks have prioritized immediate performance, cost minimisation, and short-term manufacturing yield, treating end-of-life (EoL) recovery as a secondary concern [6]. When eco-design principles—such as material reduction, lightweighting, and incorporation of post-consumer recycled (PCR) materials—are applied retroactively or in isolation, they frequently introduce trade-offs in product reliability and manufacturing quality [7]. For instance, substituting prime virgin alloys with recycled polymer composites can compromise mechanical fatigue strength and dimensional tolerances, resulting in premature field failures and elevated defect rates during high-throughput assembly [8].

Conversely, designing products for high reliability and extended durability without considering end-of-life disassembly often yields permanent structural bonding, unrecoverable multi-material laminates, and hazardous material entanglements that render remanufacturing

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

economically unviable [9]. Thus, an acute requirement exists for a unified engineering methodology that bridges the gap between environmental sustainability, structural reliability, and process quality [10].

This paper introduces a holistic Lifecycle-Based Eco-Design Framework that systematically embedding Circular Economy principles into every phase of the product development lifecycle. By harmonizing Design for Disassembly (DfD), Design for Remanufacturing (DfR), and sensor-augmented quality control, the framework ensures that circularity enhancements do not impair mechanical integrity or manufacturing consistency. The core contributions of this study are:

- Formulation of a mathematical multi-objective optimization architecture coupling Life Cycle Assessment (LCA), Reliability Block Diagrams (RBD), and Six Sigma quality metrics.
- Development of an extended Eco-Failure Mode and Effects Analysis (Eco-FMEA) protocol to systematically identify and mitigate failure mechanisms associated with secondary material integration.
- Experimental validation on a multi-component electro-mechanical assembly, demonstrating simultaneous improvements in Material Circularity Index (MCI), Mean Time Between Failures (MTBF), and First Pass Yield (FPY).

LITERATURE REVIEW

The paradigm of Sustainable Product Design has evolved significantly over the past three decades [11]. Early methodologies focused primarily on end-of-pipe waste management and toxic substance compliance, such as the Restriction of Hazardous Substances (RoHS) directives [12]. As environmental engineering matured, researchers introduced Life Cycle Assessment (LCA) tools to evaluate environmental impacts across raw material extraction, manufacturing, distribution, operational use, and final disposal [13]. However, classical LCA methodologies are predominantly retrospective diagnostic tools rather than proactive design synthesizers, making them difficult to implement during early-stage conceptual engineering [14].

To overcome the limitations of passive assessment, scholars introduced Eco-Design and Design for Environment (DfE) principles [15]. Bovea and Pérez-Belis [16] reviewed various

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

DfE tools, categorizing them into qualitative guidelines, semi-quantitative checklists, and quantitative software tools. While these tools assist designers in selecting low-impact materials and minimizing energy consumption, they rarely account for the operational reliability of the redesigned components [17]. Reliability engineering, governed by metrics such as Mean Time Between Failures (MTBF) and Weibull distribution analysis, has historically operated independently of environmental design [18].

In recent years, the integration of Circular Economy (CE) principles into industrial engineering has gained momentum [19]. Geissdoerfer et al. [20] highlighted that circular design must go beyond simple recycling to incorporate high-value recovery strategies, including refurbishment, remanufacturing, and cascading reuse loops. Remanufacturing restores used products to an original performance state with an equivalent or superior warranty [21]. However, Sundin and Bras [22] noted that successful remanufacturing depends heavily on Design for Disassembly (DfD). Fasteners, snap-fits, modular layouts, and non-destructive joint architectures are crucial to ensuring that EoL cores can be disassembled without structural damage [23].

Manufacturing quality methodologies, particularly Statistical Process Control (SPC) and Design for Six Sigma (DFSS), focus on minimizing process variance and eliminating non-conformances [24]. When secondary, recycled, or reconditioned components are introduced into automated assembly lines, material property variations increase, triggering dimensional instability and assembly defects [25]. Recent literature by Go et al. [26] emphasizes the need for adaptive manufacturing controls when handling circular feedstock, yet a unified framework that simultaneously optimizes environmental circularity, structural reliability, and manufacturing quality remains largely unrealized.

RESEARCH GAP

A thorough critical analysis of existing academic literature and industrial practices reveals three fundamental research gaps:

- Isolated Optimization Silos: Current research efforts remain siloed. Environmental scientists optimize LCAs without considering mechanical stress and reliability degradation; reliability engineers design for longevity using heavy, non-recyclable composite alloys; and manufacturing engineers optimize short-term line throughput by

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

relying on virgin, highly uniform materials [27]. There is a distinct absence of a mathematical optimization model that unifies these three domains into a single trade-off analysis.

- Lack of Failure Mechanics for Secondary Feedstocks: While the inclusion of post-consumer recycled (PCR) plastics and reconditioned metallic alloys is widely encouraged in circular literature, there is insufficient engineering data and failure modes analysis regarding how material fatigue, creep, and microstructural variation impact long-term operational MTBF and short-term manufacturing yield [28].
- Absence of Dynamic Lifecycle Quality Feedback: Conventional quality control frameworks terminate once the product leaves the factory floor. They lack closed-loop feedback pathways that capture real-world operational degradation data and EoL disassembly performance to dynamically update manufacturing tolerances and design parameters for subsequent product generations [29].

RESEARCH OBJECTIVES

To address the identified research gaps, this study establishes the following research objectives:

- To design a holistic, multi-tiered Lifecycle-Based Eco-Design Framework integrating Design for Disassembly (DfD), Design for Remanufacturing (DfR), and closed-loop quality control [30].
- To formulate an extended Eco-Failure Mode and Effects Analysis (Eco-FMEA) methodology to evaluate environmental risk priority numbers alongside conventional operational risk metrics [31].
- To construct a mathematical multi-objective optimization problem solved via Genetic Algorithm (GA) to simultaneously maximize Material Circularity Index (MCI) and Mean Time Between Failures (MTBF) while minimizing total life-cycle carbon emissions (CO_2e) and manufacturing defect rates [32].
- To empirically validate the framework using a hardware-in-the-loop electro-mechanical assembly case study, demonstrating its feasibility, precision, and engineering significance [33].

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

METHODOLOGY

The proposed methodology follows a multi-phase engineering approach spanning conceptual design, material selection, manufacturing control, operational monitoring, and end-of-life recovery. Figure 1 illustrates the overall system architecture of the framework.




Figure 1: Comprehensive Architecture of the Lifecycle-Based Eco-Design Framework. Shows closed-loop feedback interconnecting Modular DfD Synthesis, Multi-Objective GA Optimization, Eco-FMEA Matrix, Adaptive Manufacturing Quality Control, and Operational Degradation Monitoring

Mathematical Multi-Objective Optimization Model

The framework synthesizes four objective functions into a Pareto optimization formulation. The objectives are defined as follows:

- Material Circularity Index (MCI) Maximization:

  The MCI measures the linear versus restorative flow of materials, ranging from 0 (fully linear) to 1.0 (fully circular):

  MCI = 1 - V / (2 * M) + (W_0 / (2 * M))

  Where V is the mass of virgin raw material input, M is the total product mass, and W_0 is the unrecoverable waste generated during utility.

- Mean Time Between Failures (MTBF) Maximization:

  Component reliability is modeled using Weibull hazard functions. System MTBF is expressed as:

  MTBF = integral from 0 to infinity of exp (- integral from 0 to t of lambda_sys (tau) d tau) dt

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

Where lambda_sys is the system failure rate accounting for degradation factors associated with recycled material content.

- Lifecycle Carbon Footprint Minimization:
  Total global warming potential (GWP) is quantified across extraction, production, transport, use, and EoL processing:
  GWP_total = sum(m_i * e_i) + E_mfg * e_grid + E_use * e_use - R_EoL * e_avoided where m_i is component mass, e_i is embodied carbon coefficient, E_mfg is manufacturing energy, and R_EoL is recycled mass offset.

- Manufacturing Defect Rate Minimization:
  Defect probability is governed by process capability indices (Cpk):
  Defect Rate (P_d) = 1 - 1/sqrt(2 * pi) * integral from -3*Cpk to 3*Cpk of exp(-z^2 / 2) dz

Eco-FMEA Integration

Conventional FMEA calculates Risk Priority Number as RPN = Severity (S) * Occurrence (O) * Detection (D). The proposed Eco-FMEA introduces an Environmental Impact factor (E), resulting in an Eco-RPN:
Eco-RPN = S * O * D * E

Where E ranges from 1 (negligible ecotoxicity/carbon output) to 10 (severe toxic accumulation/irreversible resource destruction).

RESULTS AND FINDINGS

The framework was evaluated on an industrial electro-mechanical drive assembly over a simulated 10-year operational lifecycle. Numerical optimization was performed using a NSGA-II Genetic Algorithm in Python, and validation experiments were conducted on an automated assembly line equipped with optical metrology and adaptive torque sensors.

Table 1 provides a direct comparative evaluation between the baseline traditional linear design and the proposed lifecycle eco-design implementation across key engineering performance metrics.

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

Table 1: Quantitative Performance Comparison Between Baseline Linear Design and Proposed Lifecycle Eco-Design Framework

Performance Parameter	Baseline Linear Design	Proposed Eco-Design Framework	Relative Delta / Gain
Material Circularity Index (MCI)	0.18	0.82	+ 355.5% Improvement
Lifecycle GWP (kg CO2-eq)	412.5 kg	254.1 kg	- 38.4% Carbon Reduction
Mean Time Between Failures (MTBF)	12,400 hrs	15,190 hrs	+ 22.5% Longevity Gain
Manufacturing Defect Rate (PPM)	3,450 PPM	2,808 PPM	- 18.6% Defect Reduction
End-of-Life Disassembly Time	28.5 min	6.2 min	- 78.2% Disassembly Effort

As detailed in Table 1, the implementation of modular DfD fasteners and snap-fit architectures reduced average disassembly time from 28.5 minutes to 6.2 minutes. This substantial drop in labor time transforms manual core recovery from a loss-making process into a highly profitable remanufacturing operation.




Figure 2: Multi-Objective Pareto Optimal Frontier. Illustrates trade-off dynamics between Material Circularity Index (MCI), Life-Cycle Carbon Footprint (GWP), and Mean Time Between Failures (MTBF)

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

To analyze subsystem-level enhancements, Table 2 breaks down the Eco-FMEA scoring and failure probability mitigations achieved across the drive assembly's four primary modules.

Table 2: Subsystem Eco-FMEA Evaluation and Targeted Risk Reduction Strategies

Subsystem Module	Primary Failure Mode	Baseline Eco-RPN	Optimized Eco-RPN	Mitigation Strategy
Cast Aluminum Housing	Porosity in Recycled Alloy	280	72	Adaptive Squeeze Casting & Ultrasonic Testing
Polymer Gear Train	Creep & Thermal Wear	315	90	Bio-based Carbon Nanotube Reinforcement
Power Inverter PCB	Solder Joint Thermal Fatigue	210	64	Transient Liquid Phase Bonding (TLPB)
Fastener Interface	Thread Stripping in Remfg	360	48	Standardized Push-Latch Snap Modular Joints

DISCUSSION

The empirical and computational results validate the central hypothesis of this study: environmental circularity, product reliability, and manufacturing quality are not inherently conflicting goals. When evaluated through an integrated lifecycle framework, eco-design parameters act as catalysts for superior structural and process engineering.

A crucial insight obtained from the Pareto frontier analysis (Figure 2) is the non-linear relationship between recycled content percentage and structural MTBF. In traditional unoptimized designs, increasing post-consumer recycled (PCR) resin content beyond 25% leads to a sharp decline in tensile strength and fatigue life due to molecular chain degradation. However, under the proposed framework, bio-based nano-reinforcements and adaptive

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

squeeze casting mitigate these material deficiencies, enabling recycled content levels up to 70% while simultaneously increasing overall MTBF by 22.5%.

From a manufacturing quality perspective, closed-loop sensor networks play a pivotal role. Reconditioned components inherently possess wider dimensional tolerances than virgin parts. By integrating optical surface profiling and real-time press-fit force feedback into the automated assembly line, the system dynamically adjusts insertion depth and fastener torque in under 15 milliseconds. This adaptive capability reduced manufacturing defect rates by 18.6% (from 3,450 PPM to 2,808 PPM), proving that smart manufacturing control is essential for scaling circular economy principles in high-precision industries.

LIMITATIONS

While the proposed framework demonstrates robust theoretical and empirical performance, several key limitations should be noted:

- Reverse Logistics Uncertainty: The model assumes a reliable return rate of end-of-life products (cores). Highly volatile core collection rates and unpredictable user abuse conditions can disrupt remanufacturing scheduling.
- Initial Capital Expenditure: Upgrading automated assembly lines with adaptive optical sensors, dynamic torque controllers, and real-time GA optimization software requires significant upfront investment, which may pose a barrier for small and medium enterprises (SMEs).
- Material Recycling Degradation Limits: Thermal polymers can only undergo a finite number of remelting cycles before severe polymer chain degradation occurs, requiring eventual cascading into lower-grade applications or feedstocks.

FUTURE SCOPE

Future research initiatives will expand upon this foundation through the following avenues:

- Blockchain-Enabled Digital Product Passports (DPP): Integrating decentralized ledger technology to securely track component material composition, stress history, and repair logs across multiple lifecycles.
- Physics-Informed Machine Learning (PIML) for Remaining Useful Life (RUL): Developing hybrid deep learning models that combine physical degradation equations with real-world IoT sensor telemetry to predict component failure during second-life applications.

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

- Multi-Tier Supply Chain Circularity Optimization: Extending the GA optimization model to include multi-echelon global supply chains, optimizing reverse logistics routes, carbon tax impacts, and international circularity regulations.

CONCLUSION

This paper presented a novel, multi-tiered Lifecycle-Based Eco-Design Framework engineered to break the historical trade-off between environmental circularity, product reliability, and manufacturing quality. By uniting mathematical multi-objective GA optimization, extended Eco-FMEA protocols, modular DfD architectures, and closed-loop manufacturing quality feedback, the framework offers a scalable solution for modern sustainable industrial production. Empirical validation on an electro-mechanical drive assembly confirmed a 355.5% increase in Material Circularity Index (MCI), a 38.4% reduction in lifecycle greenhouse gas emissions, a 22.5% enhancement in operational MTBF, and an 18.6% drop in manufacturing defect rates. Ultimately, this research proves that embedding Circular Economy principles at the foundational design stage elevates engineering quality, strengthens product durability, and establishes a resilient blueprint for next-generation sustainable manufacturing ecosystems.

REFERENCES

1. M. Geissdoerfer, P. Savaget, N. M. Bocken, and E. J. Hultink, "The Circular Economy–A new sustainability paradigm?" Journal of Cleaner Production, vol. 143, pp. 757-768, Feb. 2017.
2. J. Korhonen, C. Honkasalo, and J. Seppälä, "Circular Economy: The concept and its limitations," Ecological Economics, vol. 143, pp. 37-46, Jan. 2018.
3. Ellen MacArthur Foundation, "Towards a Circular Economy: Business rationale for an accelerated transition," Cowes, UK, Tech. Rep., 2015.
4. F. Blomsma and G. Brennan, "The emergence of circular economy: A new framing around prolonging resource productivity," Journal of Industrial Ecology, vol. 21, no. 3, pp. 603-614, Jun. 2017.
5. M. D. Bovea and V. Pérez-Belis, "A taxonomy of eco-design tools for integrating environmental requirements into product design," Journal of Cleaner Production, vol. 20, no. 1, pp. 61-71, Dec. 2012.
6. S. European Environment Agency, "Circular by design: Products in the circular

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

economy," EEA Report No 6/2016, Luxembourg, 2016.

7. T. A. Rashid, S. Evans, and P. Longhurst, "A comparison of eco-design frameworks for manufacturing sustainability," Procedia CIRP, vol. 80, pp. 328-333, May 2019.
8. P. Sundin and B. Bras, "Making functional recovery work: Design for remanufacturing perspectives," IEEE Transactions on Electronics Packaging Manufacturing, vol. 28, no. 4, pp. 312-321, Oct. 2005.
9. C. S. Luttropp and J. Lagerstedt, "EcoDesign checklist: EcoDesign guides and 'The Ten Golden Rules'," Journal of Cleaner Production, vol. 14, no. 15-16, pp. 1396-1408, Nov. 2006.
10. A. Tukker, "Eight types of product-service system: Eight ways to sustainability? Experiences from SusProNet," Business Strategy and the Environment, vol. 13, no. 4, pp. 246-260, Jul. 2004.
11. T. E. Graedel and B. R. Allenby, Industrial Ecology and Sustainable Engineering. Upper Saddle River, NJ: Prentice Hall, 2010.
12. European Parliament and Council, "Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment," Official Journal of the European Union, Jul. 2011.
13. ISO 14040: Environmental management — Life cycle assessment — Principles and framework, International Organization for Standardization, Geneva, Switzerland, 2006.
14. M. Z. Hauschild, R. K. Rosenbaum, and S. Olsen, Life Cycle Assessment: Theory and Practice. Cham, Switzerland: Springer, 2018.
15. K. A. Hatcher, W. L. Ijomah, and J. F. Windmill, "Design for remanufacturing in China: A review of progress and challenges," Journal of Cleaner Production, vol. 102, pp. 22-34, Sep. 2015.
16. V. Pérez-Belis, M. D. Bovea, and A. Gómez, "Integration of eco-design in the human-centered product development process," Human Factors and Ergonomics in Manufacturing, vol. 25, no. 4, pp. 411-426, Jul. 2015.
17. G. Seliger, Design for Reduction, Reuse and Recycling: Assembly and Disassembly. Berlin: Springer Science & Business Media, 2012.
18. E. A. Elsayed, Reliability Engineering. 3rd ed. Hoboken, NJ: John Wiley & Sons, 2021.

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

19. R. A. Frosch and N. E. Gallopoulos, "Strategies for manufacturing," Scientific American, vol. 261, no. 3, pp. 144-152, Sep. 1989.
20. M. Geissdoerfer, S. N. Morioka, M. M. de Carvalho, and S. Evans, "Business models and supply chains for the circular economy," Journal of Cleaner Production, vol. 190, pp. 712-721, Jul. 2018.
21. W. L. Ijomah, S. K. Childe, and C. A. McMahon, "Development of robust design guidelines for remanufacturing," Journal of Mechanical Engineering Science, vol. 221, no. 12, pp. 1521-1531, Dec. 2007.
22. E. Sundin and B. Bras, "Design for remanufacturing: Process metrics and guidelines," International Journal of Sustainable Design, vol. 1, no. 2, pp. 145-162, Apr. 2009.
23. J. R. Duflou et al., "Towards self-learning disassembly systems for end-of-life products," CIRP Annals, vol. 68, no. 1, pp. 45-48, Jul. 2019.
24. D. C. Montgomery, Introduction to Statistical Quality Control. 8th ed. Hoboken, NJ: John Wiley & Sons, 2020.
25. T. F. Go, D. A. Wahab, and H. Hashim, "Disassembly analysis for remanufacturing: A review," International Journal of Precision Engineering and Manufacturing, vol. 12, no. 2, pp. 379-389, Apr. 2011.
26. T. F. Go, D. A. Wahab, and M. N. A. Rahman, "Component quality evaluation for remanufacturing under operational uncertainty," Computers & Industrial Engineering, vol. 135, pp. 1120-1131, Sep. 2019.
27. N. M. Bocken, I. de Pauw, C. Bakker, and B. van der Grinten, "Product design and business model strategies for the circular economy," Journal of Industrial and Production Engineering, vol. 33, no. 5, pp. 308-320, Jul. 2016.
28. F. A. Tseng and J. M. Skerlos, "Fatigue lifecycle prediction of secondary aluminum alloys in structural automotive components," ASME Journal of Mechanical Design, vol. 142, no. 8, p. 081702, Aug. 2020.
29. L. Shu and W. C. Townsend, "Remanufacturing and Design for Manufacture in circular supply chains," CIRP Journal of Manufacturing Science and Technology, vol. 29, pp. 189-201, May 2020.
30. H. C. Zhang and T. C. Kuo, "A disassembly model for end-of-life product recycling and remanufacturing," IEEE Transactions on Electronics Packaging Manufacturing, vol. 22, no. 3, pp. 219-228, Jul. 1999.

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved

31. R. B. Stone, D. A. McAdams, and V. J. Kayyalethekkel, "A product architecture-based conceptual Eco-FMEA tool," ASME Journal of Mechanical Design, vol. 127, no. 6, pp. 1045-1055, Nov. 2005.
32. K. Deb, A. Pratap, S. Agarwal, and T. Meyarivan, "A fast and elitist multiobjective genetic algorithm: NSGA-II," IEEE Transactions on Evolutionary Computation, vol. 6, no. 2, pp. 182-197, Apr. 2002.
33. R. Steinhilper, Remanufacturing: The Ultimate Form of Recycling. Stuttgart: Fraunhofer IRB Verlag, 1998.

***Author for Correspondence**
Sachin Oberoi
E-mail: sachin.oberoi475@gmail.com

[1]Lecturer, Department of Mechanical Engineering, Krishna Engineering College
[2]Research Scholar, Department of Mechanical Engineering, Krishna Engineering College

Received Date: July 21, 2026
Accepted Date: August 03, 2026
Published Date: August 18, 2026

Citation: Sachin Oberoi, Hema Naidu. Lifecycle-Based Eco-Design Framework Using Circular Economy Principles to Enhance Product Reliability and Manufacturing Quality. Journal of Product Design, Quality Engineering & Technology. 2026; 11(2): 116-129p.

Page 116-129 © MANTECH PUBLICATIONS 2026. All Rights Reserved