

Remote Sensing Approaches For Dam Site Selection And Stability Assessment

Dr. Neha Kapoor

Associate Professor

Department of Civil Engineering

Indian Institute of Technology, Roorkee

Corresponding Author's Email: neha.kapoor@iitroorkee.ac.in

Mr. Ankit Joshi

Research Scholar

Department of Geoinformatics

Indian Institute of Technology, Roorkee

Corresponding Author's Email: ankit.joshi@iitroorkee.ac.in

Abstract

Dam site selection and stability assessment are critical steps in water resource management and infrastructure development. The integration of remote sensing technologies provides a non-invasive, efficient, and comprehensive approach to identify suitable dam locations and evaluate their geological and environmental stability. This paper reviews various remote sensing techniques, including multispectral and hyperspectral satellite imagery, Digital Elevation Models (DEM), Synthetic Aperture Radar (SAR), and Geographic Information Systems (GIS), utilized in the assessment of dam sites. The methodologies incorporate land use/land cover analysis, terrain slope evaluation, geological fault detection, soil moisture assessment, and sedimentation monitoring. A case study example is provided to illustrate the application of these techniques. A detailed table summarizes the key parameters analyzed through remote sensing for dam site evaluation. Limitations and future prospects of remote sensing in dam engineering are also discussed. The findings highlight how remote sensing

enhances traditional geotechnical methods, supporting sustainable and safe dam construction.

Keywords

Dam Site Selection, Remote Sensing, Stability Assessment, Digital Elevation Model, SAR, GIS, Sedimentation Monitoring

INTRODUCTION

Dams play a pivotal role in water storage, flood control, irrigation, and hydropower generation. Selecting an optimal dam site that ensures long-term structural stability and minimal environmental impact is a challenging task. Conventional ground-based surveys are often time-consuming, costly, and restricted by difficult terrain. Remote sensing technologies offer a synoptic and cost-effective alternative, capable of providing vital geological, hydrological, and environmental data over large areas.

This paper presents a comprehensive overview of remote sensing approaches for dam site selection and stability assessment. The integration of satellite imagery, radar data, and GIS tools allows for detailed terrain and geological analyses, enhancing decision-making in dam engineering.

REMOTE SENSING TECHNIQUES FOR DAM SITE SELECTION

1. Multispectral and Hyperspectral Imaging

Satellite sensors like Landsat and Sentinel capture spectral data useful for land use/land cover (LULC) classification. Identification of vegetation, soil types, and water bodies helps in preliminary site screening to avoid ecologically sensitive or unsuitable regions.

2. Digital Elevation Models (DEMs)

High-resolution DEMs derived from SRTM or LiDAR provide elevation, slope, and aspect data. These parameters influence water flow, reservoir capacity, and dam stability by indicating potential flood zones, steep slopes prone to landslides, and sediment deposition areas.

3. Synthetic Aperture Radar (SAR) and Interferometric SAR (InSAR)

SAR penetrates cloud cover and provides surface deformation data. InSAR detects ground

movements, fault activity, and soil subsidence, critical for assessing seismic risks and foundation stability at dam sites.

4. Soil Moisture and Hydrological Analysis

Microwave remote sensing estimates soil moisture content, important for evaluating seepage risks and foundation conditions. Hydrological models integrated with remote sensing data assess watershed characteristics affecting dam inflow and sediment load.

5. GIS Integration

GIS platforms enable overlaying and analyzing multiple datasets—geology, hydrology, topography, and land use—to generate comprehensive suitability maps for dam site selection.

METHODOLOGY6

• **Data Collection:**

- Landsat 8 OLI for LULC
- SRTM DEM for terrain parameters
- Sentinel-1 SAR for deformation monitoring
- SMAP satellite data for soil moisture

• **Data Processing:**

- Image correction, classification, and thematic mapping
- DEM analysis for slope, aspect, and elevation zoning
- InSAR time-series analysis for ground stability
- GIS overlay for multi-criteria decision analysis (MCDA)

TABLE 1: Remote Sensing Parameters for Dam Site Selection and Stability Assessment

Parameter	Description	Relevance to Dam Engineering	Data Source
Land Use/Land Cover	Vegetation, soil, water body classification	Identifies suitable sites, avoids ecological zones	Multispectral satellite
Terrain Slope	Degree of steepness of land	Steep slopes risk landslides, affect dam stability	DEM

Parameter	Description	Relevance to Dam Engineering	Data Source
Elevation	Height above sea level	Influences reservoir capacity and flood risk	DEM
Fault Lines	Location of active faults	Critical for seismic hazard assessment	Geological maps, SAR
Ground Deformation	Surface displacement over time	Indicates unstable foundations	InSAR
Soil Moisture	Moisture content in soil	Impacts seepage and foundation strength	Microwave sensors
Sedimentation Zones	Areas prone to sediment accumulation	Affects reservoir storage and lifespan	Multitemporal imagery

Table 1: Key remote sensing parameters for dam site selection and stability.

CASE STUDY: DAM SITE SELECTION IN A HILLY REGION

A dam site selection study was conducted in the Himalayan foothills using the above techniques. Multispectral images helped delineate forested areas and barren lands, excluding protected forests from the candidate zones. DEM analysis identified gentler slopes for reservoir construction, reducing landslide risk.

Sentinel-1 InSAR detected minor ground deformation along suspected fault lines, leading to the avoidance of those areas. Soil moisture data from SMAP revealed regions with high seepage potential, unsuitable for dam foundations. The final GIS-based suitability map highlighted zones optimal for dam construction with minimal environmental and geological risks.

DISCUSSION

Remote sensing considerably reduces fieldwork requirements and enables periodic monitoring post-construction. Combining multiple remote sensing datasets improves the reliability of dam site assessments.

However, limitations such as spatial resolution, data acquisition intervals, and atmospheric interference exist. Validation through ground truthing remains essential. Advances in UAV-based remote sensing and integration of machine learning algorithms promise enhanced accuracy and automation in dam site evaluations.

CONCLUSION

The application of remote sensing approaches in dam site selection and stability assessment offers an efficient, large-scale, and multi-criteria analysis platform. Satellite data provide vital information on terrain, geology, hydrology, and environmental conditions, enabling informed decision-making. The integration of SAR and InSAR further aids in identifying geotechnical hazards. While remote sensing cannot fully replace traditional surveys, it substantially supplements them, improving safety and sustainability in dam engineering projects. Future research should focus on enhancing data resolution and developing integrated automated frameworks for real-time monitoring and risk assessment.

REFERENCES

- [1] Chang, K.-T., *Introduction to Geographic Information Systems*, McGraw-Hill, 2016.
- [2] Gorsevski, P.V., et al., "Application of Remote Sensing and GIS in Dam Site Selection," *Environmental Monitoring and Assessment*, vol. 164, pp. 277-289, 2010.
- [3] Li, Z., et al., "Satellite-Based DEM Generation and Its Application in Dam Engineering," *Journal of Hydrology*, vol. 522, pp. 563-573, 2015.
- [4] Massonnet, D., et al., "The Use of InSAR for Monitoring Surface Deformation," *Remote Sensing Reviews*, vol. 12, no. 3, pp. 277-289, 1995.
- [5] Mishra, S.K., et al., "Soil Moisture Estimation Using Microwave Remote Sensing for Hydrological Applications," *Remote Sensing*, vol. 9, 2017.
- [6] Pradhan, B., "Remote Sensing and GIS for Natural Hazard Management," *Natural Hazards*, vol. 52, pp. 621-636, 2010.
- [7] Singh, R., et al., "Geospatial Techniques in Dam Site Selection and Stability Assessment," *International Journal of Remote Sensing*, vol. 38, no. 5, pp. 1321-1340, 2017.

[8] Ustin, S.L., "Hyperspectral Remote Sensing for Environmental Monitoring," *Environmental Science & Technology*, vol. 39, no. 13, pp. 4213-4218, 2005.