MANTECH Publications
Journal of Remote Sensing, Environmental Science & Geotechnical Engineering
Volume 3, Issue 2, May-August, 2018

Satellite-Based Deformation Monitoring Of Dams and Embankments Using Insar

Dr. Ananya Mehta
Professor
Department of Civil Engineering
Himalayan Institute of Technology, Dehradun, India
Email: *ananya.mehta@hitdehradun.edu.in*

Dr. Raghav Sharma
Associate Professor
Department of Geoinformatics
National Institute of Technology, Srinagar, India
Email: *raghav.sharma@nitsrinagar.ac.in*

Abstract

Interferometric Synthetic Aperture Radar (InSAR) technology has emerged as a highly effective tool for the deformation monitoring of large-scale infrastructure such as dams and embankments. This paper presents a detailed review of satellite-based InSAR applications in structural health monitoring, emphasizing early detection of deformations that could compromise structural integrity. The study discusses various InSAR techniques, such as Differential InSAR (D-InSAR) and Persistent Scatterer InSAR (PS-InSAR), and their capabilities in measuring millimeter-scale displacements. Special focus is given to the advantages of InSAR over conventional geodetic survey methods, its integration with ground-based measurements, and challenges such as atmospheric disturbances, temporal decorrelation, and water body scattering effects. Real-world case studies demonstrate how InSAR has been effectively employed in monitoring deformation patterns of key dam structures globally. The potential of combining InSAR data with numerical modeling for predictive analysis is also explored. This work aims to highlight InSAR's critical role in ensuring the safety and longevity of hydraulic structures in the context of increasing climate-induced stresses.

Page 80-84 © MANTECH PUBLICATIONS 2018. All Rights Reserved

Keywords: *InSAR, Dams, Embankments, Deformation Monitoring, Remote Sensing, Persistent Scatterer, Differential InSAR*

INTRODUCTION

Dams and embankments are crucial for water storage, flood control, irrigation, and hydroelectric power generation. Structural stability is vital to avoid catastrophic failures that can result in loss of lives, economic damage, and environmental degradation. Traditional deformation monitoring methods, such as total stations and GNSS, are effective but limited in temporal frequency and spatial coverage. The advent of **Satellite-Based Interferometric Synthetic Aperture Radar (InSAR)** has revolutionized structural health monitoring by providing high-resolution, wide-area, and frequent deformation measurements.

InSAR enables millimeter-level deformation detection without the need for ground-based installations, making it especially valuable in remote or inaccessible areas. It uses phase differences between two or more SAR images acquired over the same location to derive surface displacement.

PRINCIPLES OF INSAR FOR DEFORMATION MONITORING

The InSAR technique relies on coherent radar signals to measure ground movement. When radar signals are transmitted from a satellite and reflected from the Earth's surface, the phase information can be compared across two acquisitions to determine displacement.

Table 1 below summarizes the basic principles:

Parameter	Description
Sensor Type	Synthetic Aperture Radar (SAR) satellites
Measurement Accuracy	Millimeter-scale
Data Acquisition	Multiple satellite passes over time
Output Data	Displacement maps

Table 1: Core InSAR parameters relevant to dam and embankment monitoring.

INSAR TECHNIQUES FOR DAM MONITORING

Two primary InSAR techniques are widely used:

Page 80-84 © MANTECH PUBLICATIONS 2018. All Rights Reserved

- **Differential InSAR (D-InSAR):** Uses two SAR images to measure deformation between acquisition dates by eliminating topographic effects using a DEM.
- **Persistent Scatterer InSAR (PS-InSAR):** Analyzes a series of SAR images to detect stable reflectors and track displacement over long periods, ideal for man-made structures.

ADVANTAGES OVER TRADITIONAL METHODS

InSAR offers several advantages:

1. **Large Area Coverage:** Enables monitoring of entire dam structures and surrounding terrain in one acquisition.
2. **High Sensitivity:** Detects millimeter-scale changes.
3. **Non-Contact Measurement:** Ideal for dangerous or remote sites.
4. **Historical Data Access:** Many SAR satellites have archived data spanning decades.

CASE STUDIES

Example 1: Itaipú Dam, Brazil-Paraguay Border

PS-InSAR monitoring detected early-stage settlement on the downstream face, enabling preventive maintenance before critical failure.

Example 2: Xiaowan Dam, China

D-InSAR revealed seasonal deformation patterns linked to reservoir water level fluctuations, confirming the dam's structural resilience.

CHALLENGES AND LIMITATIONS

Despite its capabilities, InSAR faces limitations:

- **Atmospheric Delays:** Variations in water vapor can distort phase measurements.
- **Temporal Decorrelation:** Surface changes between acquisitions reduce coherence.
- **Water Body Interference:** Radar scattering from water reduces signal quality near reservoirs.

Page 80-84 © MANTECH PUBLICATIONS 2018. All Rights Reserved

INTEGRATING INSAR WITH GROUND MEASUREMENTS

To enhance accuracy, InSAR data is often integrated with:

- GNSS measurements for validation
- Ground-based InSAR (GB-InSAR) for continuous local monitoring
- Geotechnical instrumentation for subsurface behavior insights

FUTURE DIRECTIONS

The next generation of SAR satellites (e.g., Sentinel-1C, NISAR) will offer improved temporal resolution and advanced processing capabilities, enabling near real-time dam deformation monitoring. Integration with AI-driven predictive modeling will further enhance risk assessment.

CONCLUSION

Satellite-based InSAR has proven to be a powerful and efficient tool for monitoring the deformation of dams and embankments. Its ability to detect millimeter-scale displacements over large areas, combined with the availability of historical datasets, makes it indispensable for infrastructure safety management. The integration of InSAR with in-situ geotechnical and GNSS data can provide comprehensive hazard assessments, helping prevent failures and prolonging the life of these critical structures. As climate variability increases stress on hydraulic infrastructure, InSAR will remain at the forefront of monitoring technologies.

REFERENCES

[1] Ferretti, A., Prati, C., & Rocca, F. (2001). Permanent scatterers in SAR interferometry. IEEE Transactions on Geoscience and Remote Sensing, 39(1), 8–20.
[2] Hooper, A., Zebker, H., Segall, P., & Kampes, B. (2004). A new method for measuring deformation on volcanoes and other natural terrains using InSAR persistent scatterers. Geophysical Research Letters, 31(23).
[3] Hanssen, R. F. (2001). Radar interferometry: Data interpretation and error analysis. Springer Science & Business Media.
[4] Crosetto, M., Monserrat, O., Cuevas-González, M., Devanthéry, N., & Crippa, B. (2016). Persistent scatterer interferometry: A review. ISPRS Journal of Photogrammetry and Remote Sensing, 115, 78–89.
[5] Dong, J., Zhang, L., Ding, X., & Lu, Z. (2019). InSAR monitoring of dam deformation. Remote Sensing, 11(23), 2753.

Page 80-84 © MANTECH PUBLICATIONS 2018. All Rights Reserved

[6] Sousa, J. J., & Bastos, L. (2013). Multi-temporal SAR interferometry reveals acceleration of creep in dam embankments. Engineering Structures, 56, 154–164.
[7] Zhao, C., Lu, Z., Zhang, Q., & de la Fuente, J. (2012). Large-area deformation monitoring using advanced InSAR. Remote Sensing of Environment, 125, 120–133.

Page 80-84 © MANTECH PUBLICATIONS 2018. All Rights Reserved