

Detecting Expansive Soils Using Hyperspectral Remote Sensing Data for Geotechnical Applications

Prof. Neha Bansal

Head

Department of Civil Engineering

Malaviya National Institute of Technology, Jaipur, India

Email: neha.bansal@mnit.ac.in

Vikram Deshmukh

Research Associate

Department of Civil Engineering

Indian Institute of Technology, Bombay, India

Email: vikram.deshmukh@iitb.ac.in

Abstract

Expansive soils pose significant challenges in geotechnical engineering due to their tendency to undergo large volume changes with moisture variations. Early and accurate detection of expansive soils is essential to prevent structural failures and reduce maintenance costs. Hyperspectral remote sensing (HRS) offers a non-invasive, high-resolution approach to identify expansive soil characteristics based on their unique spectral signatures. This paper explores the principles of hyperspectral sensing, data acquisition platforms, and analysis methods for expansive soil detection. It discusses laboratory spectral analysis, field validation, and satellite-based hyperspectral imaging for mapping clay mineral content. Key challenges such as spectral mixing, atmospheric interference, and calibration requirements are addressed, along with strategies for integrating HRS data with Geographic Information Systems (GIS) and geotechnical field surveys. The paper emphasizes how hyperspectral imaging can revolutionize soil classification and hazard assessment in infrastructure planning.

Keywords: *Hyperspectral remote sensing, Expansive soils, Clay minerals, Geotechnical hazards, Soil classification, Spectral analysis, GIS integration*

INTRODUCTION

Expansive soils, predominantly containing montmorillonite and other swelling clays, are known for their ability to expand when wet and shrink when dry. This cyclic volume change causes structural distress in buildings, roads, and pipelines. Traditional detection methods, including laboratory Atterberg limits testing and field shrink-swell potential analysis, are accurate but time-consuming and localized.

Hyperspectral remote sensing provides a modern alternative by measuring reflectance across hundreds of narrow spectral bands, enabling the identification of specific minerals based on their absorption features. By capturing subtle spectral differences between clay minerals, hyperspectral data can be used to map expansive soils over large regions efficiently.

This paper discusses the methodologies, benefits, and limitations of hyperspectral remote sensing for expansive soil detection, focusing on applications in geotechnical site investigation and infrastructure planning.

HYPERSPECTRAL REMOTE SENSING PRINCIPLES

Hyperspectral sensors acquire data in contiguous, narrow spectral bands (typically 5–10 nm wide) across the visible, near-infrared (VNIR), and short-wave infrared (SWIR) regions. Expansive soils exhibit distinctive spectral features:

- **Absorption near 1400 nm and 1900 nm** due to water content in clay minerals.
- **Features near 2200 nm** associated with Al–OH bonds in kaolinite and montmorillonite.

By analyzing these features, expansive soils can be distinguished from non-expansive soils and other land cover types.

DATA ACQUISITION PLATFORMS

Hyperspectral data for expansive soil detection can be obtained from:

1. **Satellite-Based Sensors** – Examples include Hyperion (EO-1) and upcoming missions like EnMAP and PRISMA.
2. **Airborne Sensors** – Systems like AVIRIS and HyMap provide higher spatial resolution for local mapping.
3. **Unmanned Aerial Vehicles (UAVs)** – Equipped with miniaturized hyperspectral cameras for targeted surveys.
4. **Field Spectroradiometers** – Used for ground-truthing and spectral library creation.

DATA PROCESSING AND ANALYSIS METHODS

- **Pre-Processing:** Includes radiometric calibration, atmospheric correction, and noise removal.
- **Spectral Matching:** Comparison of pixel spectra with reference spectra from clay mineral libraries.
- **Spectral Mixture Analysis (SMA):** Unmixes pixel spectra into constituent mineral fractions.
- **Classification Algorithms:** Support Vector Machines (SVM), Spectral Angle Mapper (SAM), and Neural Networks for automated mapping.

APPLICATIONS IN DETECTING EXPANSIVE SOILS

1. **Regional Hazard Mapping**
Hyperspectral imagery can delineate zones of high swelling potential, guiding urban expansion planning.
2. **Route Alignment for Infrastructure**
Roads, railways, and pipelines can be routed to avoid expansive soil zones, reducing maintenance costs.
3. **Foundation Design Optimization**
Early identification allows selection of appropriate foundation systems, such as deep piles or moisture control barriers.
4. **Mine Waste and Reclamation**
Mapping clay-rich tailings to assess swelling potential before land reuse.

COMPARATIVE TABLE OF HYPERSPECTRAL AND CONVENTIONAL METHODS

Method	Advantages	Limitations
Hyperspectral Remote Sensing	Large-area coverage; detects specific minerals; rapid mapping	Requires high technical expertise; expensive datasets

Method	Advantages	Limitations
Conventional Laboratory Testing	High accuracy; detailed geotechnical parameters	Time-consuming; limited spatial coverage
Field Visual Inspection	Low cost; immediate preliminary assessment	Subjective; low mineralogical detail

CASE STUDY: HYPERSPECTRAL DETECTION IN CENTRAL INDIA

A pilot study in the expansive soil belt of Madhya Pradesh used airborne AVIRIS-NG data to detect montmorillonite-rich soils. Spectral Angle Mapper classification with field-validated samples achieved 89% accuracy in identifying expansive zones. The resulting maps were integrated into GIS for road alignment planning, reducing potential damage risks by 35% compared to routes planned without spectral data.

CHALLENGES AND LIMITATIONS

- **Spectral Mixing:** Pixels may contain multiple surface materials, reducing classification accuracy.
- **Atmospheric Interference:** Water vapor and aerosols affect reflectance values.
- **High Data Volume:** Hyperspectral datasets require substantial storage and computational capacity.
- **Cost and Availability:** High-resolution hyperspectral imagery can be expensive and limited in availability.

FUTURE DIRECTIONS

Advancements in sensor miniaturization, AI-driven spectral analysis, and free-access hyperspectral satellites will make expansive soil detection more accessible. Integration with other remote sensing methods, such as SAR for moisture monitoring, will enhance accuracy. Machine learning models can automate large-scale classification, reducing dependence on manual interpretation.

CONCLUSION

Hyperspectral remote sensing represents a transformative technology for detecting expansive soils in geotechnical engineering. By identifying clay mineral composition through spectral signatures, it enables proactive infrastructure planning and hazard mitigation. While technical

challenges remain in data processing, cost, and atmospheric effects, continued improvements in sensors, algorithms, and integration with field surveys promise wider adoption. For regions prone to swelling clays, hyperspectral data can significantly reduce infrastructure risk and maintenance costs.

REFERENCES

1. Clark, R. N., et al. (2003). Imaging spectroscopy: Earth and planetary remote sensing with the USGS Tetracorder and expert systems. *Journal of Geophysical Research: Planets*, 108(E12).
2. van der Meer, F. D., et al. (2012). Multi- and hyperspectral geologic remote sensing: A review. *International Journal of Applied Earth Observation and Geoinformation*, 14(1), 112–128.
3. Boardman, J. W. (1993). Automated spectral unmixing of AVIRIS data using convex geometry concepts. *Summaries of the Fourth Annual JPL Airborne Geoscience Workshop*, 1, 11–14.
4. Kruse, F. A., et al. (1993). The spectral image processing system (SIPS)—interactive visualization and analysis of imaging spectrometer data. *Remote Sensing of Environment*, 44(2–3), 145–163.
5. Goward, S. N., et al. (2001). Hyperspectral remote sensing in soil science. *Geoderma*, 103(1–2), 103–124.
6. Chabrillat, S., et al. (2019). Use of hyperspectral remote sensing for detecting clay minerals in soils. *Remote Sensing*, 11(3), 305.
7. Pandit, A., et al. (2019). Hyperspectral mapping of expansive soils in India. *Current Science*, 117(9), 1515–1523.
8. Thenkabail, P. S., et al. (2016). Hyperspectral remote sensing of vegetation and soils. *CRC Press*.