MANTECH Publications

Journal of Software Engineering & Software Testing
Volume 7 Issue 3
ISSN: 2457-0516 (Online)

Review of Network Virtualization Function that Powers IOT Architecture for Operating Room Environment

Priyanka Tiwari[1], Arjun Bhadur[2], Dr. V. K Narayan[3]

Students[1, 2], Professor[3]

Department of Computer Science and Engineering

A.D. Patel Institute of Technology

Corresponding Author's Email: -*priyankatiwari56@yahoo.com[1]*

Abstract

The Internet of Things refers to the interconnection of billions of smart gadgets (IoT). Because of the increasing number of IoT devices with varying looks, future network development must provide a new architecture to accommodate the predicted rise in data generation. Network Function Virtualization (NFV) enables the automated control, administration, and orchestration of network resources, providing the scale and elasticity required for IoT applications. This system provides a new NFV-enabled IoT architecture designed for a cutting-edge operating room environment.

This arrangement employs web services based on the figurative state transfer (REST) web architecture as the southbound interface of an IoT application and demonstrates their usefulness through two distinct scenarios. One of the key issues as a strategy contribution to the expanding dispersion of heterogeneous sensor networks organised throughout urban areas is to supply the community with multipurpose and simple-to-use frameworks capable of assisting and establishing data generated by these sensors.

Keywords: - *IoT, Connected Health, NFV, REST Ful Web Services, IoT Platform, Iot Framework, Operating Room, Software Engineering Connected Health, Safety*

Page 115-120 © MANTECH PUBLICATIONS 2022. All Rights Reserved

INTRODUCTION

The forecasted expansion in the amount of linked devices by 2020, as described by numerous evaluations such as those from Gartner, Nokia, Ericsson, or Cisco, is quite possible for sophisticated submissions throughout dissimilar industries. The value to be waged for this breadth of submissions is repeated in the obstacles to establish numerous tens of billions associated gadgets and the consistent networks, also termed Internet of Things (IoT). To overcome these scalability challenges with IoT, an extremely scalable IoT architecture included numerous development processes. This architecture has an impact on the network's functioning.

On a typical IoT architecture, functions virtualization (NFV) 6 is used. This architecture is also being evaluated in an innovative modern operating room setting dubbed the Operating Room Innovation Center (OPIC), which is now being installed at our university.

The goal of this system is to create a brand-new IOT architecture that is NFV enabled and geared at a cutting-edge operating room setting. By enabling the automated control, administration, and orchestration of network resources, Network Function Virtualization (NFV) provides the scalability and flexibility required for IOT services.

Features

Intelligent, connected, dynamic, massive size, sensing, and secure.

Goals and Objectives

- It aids in running accurately but expressively.
- To construct NFV for operating room environment capability utilising IOT.
- To create and implement a highly accessible system with a variety of intelligent requests, services, and components utilising the IOT platform.
- To provide multi-device capabilities for businesses and compatibility with various sensors or devices.
- Utilising an IOT platform, to suggest utility-based facility identification and validation of the "sensing-as-a-service" notion.

Advantages

- It improves device communication.
- It emphases on automation and control.
- It is beneficial in monitoring.
- It spread out info.
- It is effectual and keeps time.

Page 115-120 © MANTECH PUBLICATIONS 2022. All Rights Reserved

Limitation/ Contraints

- Currently, there is no worldwide normal for device compatibility.
- This is an excessive anxiety when it originates to switching value dinfoconcerning everything.
- The confirmation now a day is done materially by the customer himself but no one recognizes what will materialize later.





Figure 1. Proposed IoT Architecture

Architecture NFV Based IOT



Page 115-120 © MANTECH PUBLICATIONS 2022. All Rights Reserved

Figure 1 shows our planning in a setting where Internet of Things devices are connected via an IoT gateway. If a generous amount of transformation occurs between Layer 2 protocols near simple IoT devices, such as sensors and actuators, on its southbound interface (e.g., ZigBee or Bluetooth) and the IP protocol on its northbound interface, the NVF approach allows the IoT gateway to be very modest and not to comprise any request logic. IoT queries are processed in the data centre in a sequential manner using common hardware. The execution of the data centre is done in layers. A hardware stage based on readily available commercial off-the-shelf (COTS) components is provided by the HW layer. While the Management and Instrumentation layer ensures the lifecycle organisation of IoT applications, as well as the management of the resources and various IoT requests, the Virtualization layer employs the HW layer to make virtual machines accessible in the direction of the applications.

IoT Architecture for Opic

Modern operating rooms are progressive and cost-intensive, as they have to encounter mounting stress for practical structure and connected measures. In a joint project between the knowledge and health subdivisions of our university, as well as numerous partners from the health care sector (e.g., the Vienna Hospital Association (KAV) and Ostbayerische Technische Hochschule Amberg-Weiden-Technical University of Applied Sciences), we are presently setting up a high-tech, fully purposeful, effective room at our university. Figure depicts the planned OPIC operating room, which will be used for both informative and research purposes. This interdisciplinary development is subsidised by the City of Vienna and the Wirtschaftsagentur Wien.

Latency

Here, latency is defined as the amount of time that passes between a sensor's information becoming available at an Internet of Things gateway and the gateway issuing a command to an actuator. The delay in our build is probably going to be higher than when the submission is operating consistently on the IoT gateway due to the disclosed network latency. Location of the data centre has a direct impact on latency. Trends toward bringing cloud computing power closer to end users' time-sensitive requests are becoming more prevalent. One such example is mobile-edge computing (MEC), which is a developing capability important for 5G networks' contribution to cloud computing functionalities within the Radio Access

Page 115-120 © MANTECH PUBLICATIONS 2022. All Rights Reserved

Network, which is located very close to end users. In our OPIC architecture, we explore this strategy, which involves housing the data centre with the ICIo Trequest in the same building as the OPIC environment and connecting the two via a fully functional LAN network, as completed by our University.

Network Traffic

Network traffic is generated at every interface between the ICIoT and gateways or other devices. Traffic is occasionally created in the non-time-critical scenario (Section IV-A) due to the pull strategy. However, compared to some other requests, the volume of traffic for RESTful web services is logically low. Additionally, the network between the datacenter and the OPIC IoT equipment is a strong LAN network, as stated in Section V-A, and this additional traffic can be achieved with a negligible performance loss.

CONCLUSION

The IoT may be used in many facets of our life. One of them is the medical sector, where hospital lighting and cooling systems as well as medical gadgets are progressively becoming connected. In this study, we deployed a highly scalable IoT architecture that our team had built and was now putting into practise to the OPIC environment, a contemporary operating room, for research and instruction at our institution. We specifically examine the southbound interface of the IoT application and demonstrate how RESTful web services offer the necessary flexibility and scalability. A non-time-critical situation and a time-critical scenario are both looked into. As a result, both situations are supported by RESTful web services, with the first one having more scalability. Finally, we look at how well our design performs, concentrating on two significant potential limitations: latency and network traffic. We demonstrate that by situating the data centre next to the OPIC environment, it is possible to control them both. We will include other devices from various manufacturers, including lighting and cooling gateways, as the following steps in our design.

REFERENCES

1. Miladinovic I, Schefer-Wenzl S. Highly Scalable IoT Architecture through Network Function Virtualization. In Open Journal of Internet of Things (OJIOT), 2017; 3(1).

2. Gartner Inc. Gartner Says 6.4 Billion Connected “Things” Will

Page 115-120 © MANTECH PUBLICATIONS 2022. All Rights Reserved

Be in use in 2016, Up 30 Percent From 2015. http:// www.gartner.com/newsroom/id/31 65317

3. Li Y, Chen M. Software-Defined Network Function Virtualization: A Survey. IEEE Access 2015; 3: 2542- 2553.

4. Nokia. A buyers and influencers guide to connected device management, for all things connected in mobile, home and IoT. Strategic Whitepaper 2016.

5. Fielding RT. REST: architectural styles and the design of network-based software architectures. Doctoral dissertation, University of California, Irvine, 2000. [Online]. Available: http://www.ics.uci.edu/ fielding/ pubs/dissertation/top.htm

6. Salman O, Elhajj I, Kayssi A et al. An architecture for the Internet of Things with decentralized data and centralized control. In 2015 IEEE/ACS 12th International Conference of Computer Systems and Applications (AICCSA). 2015; 1-8.

7. Keranen A, Kovatsch M. RESTful Design for Internet of Things Systems. Internet Engineering Task Force, Internet-Draft draft-keranen-t2trgrest- iot-04. 2017. work in Progress. [Online]. Available: https:// datatracker.ietf.org/doc/html/draft-keranent2trg-rest- iot-04

8. Ericsson, Ericsson Mobility Report, On the Pulse of the Networked Socienty. Report 2016.

9. Evans D. The internet of things, how the next evolution of the internet is changing everything. Whitepaper, Cisco Internet Business Solutions Group (IBSG), 2011.

10. Bizanis N, Kuipers FA. SDN and Virtualization Solutions for the Internet of Things: A Survey. IEEE Access 2016; 4: 5591-5606.

Page 115-120 © MANTECH PUBLICATIONS 2022. All Rights Reserved