MANTECH Publications

Journal of Water Resource Engineering and Pollution Studies
Volume 5, Issue 2, May- August, 2020

Mapping Water Intelligence: Role of Remote Sensing and GIS in Hydrological Modeling

Dr. Kavita Deshmukh
Assistant Professor
Department of Civil Engineering
National Institute of Technology, Bhopal
***Email**: kavita.deshmukh@nitbpl.ac.in*

Rajesh Meena
M.Tech Scholar
Department of Civil Engineering
National Institute of Technology, Bhopal
***Email:** rajesh.meena.mtech@nitbpl.ac.in*

Abstract

Remote sensing and Geographic Information Systems (GIS) have revolutionized hydrological modeling by enhancing spatial and temporal data availability. These technologies facilitate watershed delineation, rainfall-runoff modeling, flood forecasting, groundwater mapping, and land use analysis. This paper explores the integration of remote sensing and GIS in hydrological models, comparing different techniques and highlighting their advantages in accuracy and resource management. It also emphasizes recent advancements in satellite imagery and digital elevation models (DEMs), offering a comprehensive overview of their applications in sustainable water resource management in data-scarce regions.

Keywords: *Remote sensing, GIS, Hydrological modeling, Watershed, DEM, Flood forecasting, Water resources*

Page 38-41 © MANTECH PUBLICATIONS 2020. All Rights Reserved

INTRODUCTION

Hydrological modeling is a critical tool in managing water resources, especially in the face of growing urbanization and climate change. Traditional data collection methods are often laborious, expensive, and spatially limited. Remote sensing and GIS technologies offer scalable, cost-effective, and spatially continuous solutions. These tools are especially valuable in data-scarce or inaccessible terrains where conventional methods fall short. By incorporating real-time satellite data, DEMs, and GIS-based spatial analysis, hydrological models are increasingly capable of simulating natural processes with improved precision.

APPLICATIONS OF REMOTE SENSING AND GIS IN HYDROLOGY

Watershed Delineation

Watershed delineation is a primary application of GIS and remote sensing. DEMs extracted from satellite data allow for the identification of catchment boundaries, stream networks, and flow accumulation. Tools like ArcGIS and QGIS simplify these processes, facilitating the development of hydrological response units for modeling purposes.

Rainfall-Runoff Modeling

Satellite-based precipitation products such as TRMM and GPM are instrumental in rainfall-runoff modeling. These datasets help simulate runoff in ungauged basins using hydrological models like SWAT, HEC-HMS, and MIKE SHE, improving the predictability of water flows across complex terrain.

Flood Forecasting and Monitoring

Remote sensing enables real-time flood monitoring through radar and optical imagery. SAR sensors penetrate cloud cover, providing flood extent mapping even during storms. GIS integrates this information with digital maps and infrastructure layers to support emergency response and risk reduction strategies.

Groundwater Potential Mapping

Combining remote sensing with GIS helps identify zones suitable for groundwater extraction based on parameters like land use, slope, soil type, and drainage density. Techniques such as AHP (Analytic Hierarchy Process) and MIF (Multi-Influencing Factor) are used to assign weights to thematic layers for decision-making.

Land Use and Land Cover Analysis

Understanding how land use changes affect hydrology is vital for accurate modeling. Remote sensing facilitates classification of land use types and change detection. This information feeds into hydrological models to evaluate impacts on infiltration, evapotranspiration, and runoff.

Page 38-41 © MANTECH PUBLICATIONS 2020. All Rights Reserved

COMPARISON OF REMOTE SENSING DATA IN HYDROLOGICAL APPLICATIONS

Satellite	Spatial Resolution	Temporal Resolution	Applications
Landsat 8	30 m	16 days	Land use, Watershed delineation
Sentinel-1 (SAR)	10 m	6–12 days	Flood mapping, Soil moisture
MODIS	250–1000 m	Daily	Evapotranspiration, Snow cover
TRMM / GPM	~25 km	3 hours	Rainfall estimation

Table 1: Comparison of commonly used remote sensing satellite data used in hydrological modeling.

BENEFITS OF INTEGRATING REMOTE SENSING AND GIS

The synergy of remote sensing and GIS offers several benefits:

- **Wider spatial coverage**: Satellite data provide large-area observations, overcoming ground-based data limitations.
- **Frequent updates**: New satellite passes offer updated information, essential for time-sensitive applications like floods.
- **Cost-effectiveness**: Remote sensing reduces fieldwork needs, lowering long-term costs.
- **Accessibility**: Many datasets (e.g., MODIS, Landsat, GPM) are freely available for academic and institutional use.
- **Scalability**: Methods can be applied from local to continental scales.

LIMITATIONS AND CHALLENGES

Despite the benefits, there are challenges in applying remote sensing and GIS:

- **Resolution trade-offs**: Higher spatial resolution data often have lower temporal resolution and vice versa.
- **Cloud cover**: Optical satellites may fail during cloudy conditions; radar alternatives are needed.
- **Calibration needs**: Models must be validated using ground truth data to ensure accuracy.
- **Data handling**: Processing large datasets requires computational power and specialized skills.

CASE STUDIES AND EXAMPLES

- **Ganga Basin Modeling (India)**: Integration of Landsat and TRMM datasets using SWAT improved runoff prediction in ungauged sub-basins.
- **Amazon Flood Mapping**: Sentinel-1 SAR imagery supported accurate flood inundation delineation during monsoon seasons.
- **Groundwater Zoning in Rajasthan**: GIS and remote sensing techniques mapped groundwater potential zones using thematic layers like geology, land cover, and slope.

Page 38-41 © MANTECH PUBLICATIONS 2020. All Rights Reserved

FUTURE TRENDS

- **AI and Machine Learning**: Algorithms are being developed to extract features and model hydrological behavior using remote sensing inputs.
- **Cloud-based Processing**: Platforms like Google Earth Engine allow scalable analysis of terabytes of geospatial data in real time.
- **Improved Sensors**: Higher resolution and multi-spectral capabilities from new satellites will enhance accuracy and temporal detail.
- **IoT Integration**: Remote sensing can be combined with in-situ sensors (IoT) for smart water systems.

CONCLUSION

The integration of remote sensing and GIS has significantly enhanced the capabilities of hydrological modeling. From watershed delineation to flood forecasting, these technologies provide a robust framework for informed water management, especially in developing regions. With advancements in satellite resolution, cloud computing, and open-source GIS tools, the accessibility and effectiveness of hydrological applications are rapidly increasing. A strategic combination of spatial data with hydrological models is essential for sustainable and resilient water systems in the face of climate change and increasing demand.

REFERENCES

1. Dutta, D. et al., "Remote Sensing and GIS in Hydrology," *Journal of Hydrologic Engineering*, 2019.
2. Jha, M.K. and Chowdary, V.M., "Integrated Remote Sensing and GIS for Groundwater Exploration," *Water Resources Management*, 2007.
3. Maidment, D.R., "GIS and Hydrologic Modeling—An Overview," *Journal of Hydrologic Engineering*, 2002.
4. Tripathi, M.P. et al., "Runoff Modeling Using Satellite-Based Rainfall Data in SWAT Model," *Hydrological Sciences Journal*, 2014.
5. Roy, P.S. et al., "Application of Remote Sensing and GIS in Flood Hazard Mapping," *Current Science*, 2010.
6. Singh, R.D. et al., "Use of GIS in Water Resources," *Central Water Commission Report*, 2018.
7. Ghayoumian, J. et al., "Groundwater Modeling Using Remote Sensing and GIS," *Environmental Geology*, 2007.
8. Rawat, J.S. and Kumar, M., "Monitoring Land Use Changes Using Remote Sensing and GIS," *Journal of Environmental Research*, 2015.

Page 38-41 © MANTECH PUBLICATIONS 2020. All Rights Reserved