MANTECH Publications

Recent Trends in Electrical Machines and Drives
Volume 10, Issue 2, May- August 2025

# *High-Efficiency Multilevel Inverters for Industrial Drive Applications*

***Dr. Rajesh Kumar Singh[1], Simran Khabiya[2], Shreya Basu[3]***

*Assistant Professor[1], Students[2, 3]*

*Department of Electrical Engineering*

*Suryodaya Institute of Technology*

***Email:*** *rajeshk_singh@gmail.com[1]*

***ABSTRACT***

*Multilevel inverters have emerged as a key solution for industrial electric drive applications requiring high power quality and efficiency. This paper provides an in-depth analysis of recent trends in multilevel inverter topologies, focusing on Neutral Point Clamped (NPC), Flying Capacitor (FC), and Modular Multilevel Converters (MMC). These inverters reduce harmonic distortion, improve voltage balancing, and enhance overall system reliability. The implementation of advanced modulation strategies, such as Space Vector Pulse Width Modulation (SVPWM) and Selective Harmonic Elimination (SHE), is discussed to maximize inverter performance. Furthermore, the paper addresses the integration of energy storage systems and renewable sources with multilevel inverters for industrial applications. Experimental results show that multilevel inverters can achieve efficiency improvements up to 98%, with significant reductions in Total Harmonic Distortion (THD), making them suitable for high-performance industrial motor drives.*

***KEYWORDS:*** *Multilevel Inverters, Harmonic Reduction, Industrial Drives, Space Vector PWM, Modular Multilevel Converters*



Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

## INTRODUCTION

Industrial drive applications have witnessed significant advancements over the past few decades, primarily due to the increasing demand for energy efficiency, reliability, and precise control. One of the key technologies enabling these improvements is the multilevel inverter (MLI). Unlike traditional two-level inverters, multilevel inverters can produce a stepped voltage waveform with reduced harmonic distortion, leading to better performance and reduced stress on electrical components. High-efficiency MLIs have become essential in applications such as electric motors, robotics, rolling mills, and renewable energy interfacing with industrial drives.

The primary advantage of MLIs lies in their capability to generate higher output voltages without increasing the voltage rating of power semiconductor devices. This feature reduces switching losses, minimizes electromagnetic interference (EMI), and enhances the overall efficiency of the system. The growing trend of energy-conscious industrial systems has driven researchers and engineers to explore different topologies, modulation strategies, and control techniques to achieve optimal performance in industrial drive applications.

## LITERATURE REVIEW

Multilevel inverters were first introduced in the 1970s, with the Neutral Point Clamped (NPC) inverter being among the earliest topologies. Over the years, several configurations have been developed, including Flying Capacitor (FC) and Cascaded H-Bridge (CHB) inverters. Each topology offers unique advantages and limitations in terms of scalability, voltage levels, efficiency, and complexity.

The NPC inverter is widely appreciated for its simplicity in balancing the neutral point voltage and reducing total harmonic distortion (THD). However, it requires a high number of clamping diodes, making it less suitable for high-voltage industrial drives where component count and losses are critical. The FC inverter offers voltage level flexibility and better harmonic performance but requires extensive capacitor management strategies to ensure voltage balancing, which adds complexity to the control system.

CHB inverters, on the other hand, have become popular in medium- and high-voltage industrial applications. These inverters use series-connected H-bridge cells, each powered by isolated DC sources, which allows for modular design and scalability. The modularity of CHB inverters simplifies maintenance and enables fault-tolerant operation, which is crucial for industrial


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

environments where downtime can be costly. Researchers have demonstrated that CHB inverters can achieve efficiency levels exceeding 98% under optimal operating conditions, making them a prime candidate for industrial drive applications.

Recent studies have explored hybrid multilevel inverters, which combine the benefits of different topologies to overcome individual limitations. For instance, combining NPC and CHB topologies can achieve both high voltage output and reduced component stress. Moreover, the advent of wide-bandgap semiconductors, such as Silicon Carbide (SiC) and Gallium Nitride (GaN), has further enhanced the efficiency and switching speed of MLIs, allowing higher frequency operation with lower switching losses.

## TOPOLOGIES OF MULTILEVEL INVERTERS

The performance, efficiency, and reliability of industrial drive systems are strongly influenced by the choice of multilevel inverter (MLI) topology. Selecting the appropriate topology is essential for meeting application-specific requirements such as voltage level, harmonic performance, modularity, fault tolerance, and cost-effectiveness. The commonly used MLI topologies can be classified as follows:

### 1. Neutral Point Clamped (NPC) Inverters:

NPC inverters, also known as diode-clamped inverters, are one of the earliest and most widely used multilevel topologies. They employ clamping diodes to divide the DC link voltage into multiple levels, allowing the inverter to generate a stepped output voltage waveform. Each voltage level reduces the voltage stress on semiconductor devices, which improves the inverter's reliability and extends the lifespan of the switches.

NPC inverters are particularly effective in high-voltage industrial applications, such as large motor drives, rolling mills, and heavy-duty pumps. One of the main advantages of NPC inverters is their ability to produce low total harmonic distortion (THD) waveforms, which reduces heating and torque ripple in motors. However, a significant challenge lies in maintaining the voltage balance of the DC link capacitors. Unbalanced voltages can lead to uneven power distribution and reduce overall efficiency. Advanced control strategies, such as balancing algorithms or voltage sensors, are often employed to address this issue.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

**2. Flying Capacitor (FC) Inverters:**

FC inverters generate multiple voltage levels by inserting series capacitors into the power circuit. These capacitors are charged and discharged in a controlled manner to achieve intermediate voltage steps between the DC link voltage and ground. The FC topology provides a high degree of flexibility in generating voltage levels and reducing harmonic content in the output waveform.

A major advantage of FC inverters is their ability to achieve more voltage levels with fewer semiconductor switches compared to diode-clamped inverters, making them suitable for medium-voltage industrial applications. They are commonly used in variable-speed drives, induction motor control, and medium-power renewable energy systems. However, the major challenge is capacitor voltage balancing, which becomes more complex as the number of levels increases. Sophisticated control algorithms are required to maintain capacitor voltages within safe limits, ensuring the stability and reliability of the system.

**3. Cascaded H-Bridge (CHB) Inverters:**

CHB inverters consist of multiple H-bridge cells connected in series, each powered by an isolated DC source. Each H-bridge can produce three levels of voltage (positive, zero, and negative), and by cascading multiple cells, the inverter can generate a high-quality multilevel output waveform with a significant reduction in harmonics.

The key advantages of CHB inverters include modularity, scalability, and fault tolerance. Because the H-bridge cells are independent, faulty modules can be bypassed without completely shutting down the system. This makes CHB inverters highly suitable for industrial drives requiring high power, reliability, and continuous operation, such as in conveyor systems, extrusion machines, and electric traction motors. Additionally, CHB inverters are easier to expand for higher voltage applications by adding more H-bridge cells, offering flexibility for future upgrades. The modular design also simplifies maintenance, as individual cells can be replaced without affecting the rest of the system.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved





***Figure 1: Block Diagram of a Cascaded H-Bridge Multilevel Inverter***

**4. Hybrid Topologies:**

Hybrid multilevel inverters combine features from different topologies, aiming to achieve superior performance while minimizing drawbacks such as high component count, complexity, or voltage stress. For example, NPC-CHB hybrid inverters integrate diode clamping for voltage stress reduction and modular H-bridge cells for scalability.

Hybrid topologies are particularly beneficial in applications where both high voltage and high power are required, and where energy efficiency is critical. By leveraging the strengths of multiple topologies, hybrid inverters can reduce switching losses, improve waveform quality, and simplify control strategies compared to conventional MLI designs. They are increasingly used in modern industrial drives, renewable energy systems, and high-performance electric traction applications.

***Table 1: Comparison of Multilevel Inverter Topologies***

| Topology | Voltage Levels | Component Count | Efficiency (%) | Industrial Suitability |
|---|---|---|---|---|
| NPC | Medium-High | High | 95–97 | Medium-High voltage |
| FC | Medium | Very High | 94–96 | Medium voltage |
| CHB | Medium-High | Medium | 96–98 | Medium-High voltage |
| Hybrid | Medium-High | Medium | 97–98 | High reliability |

**CONTROL STRATEGIES FOR HIGH-EFFICIENCY MLI**

The efficiency, reliability, and dynamic performance of multilevel inverters (MLIs) in industrial


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

drives are strongly influenced by the control strategies employed. Selecting the appropriate control method is crucial for reducing switching losses, minimizing harmonics, maintaining voltage balance, and ensuring optimal operation under varying load conditions.

Over the years, several advanced control strategies have been developed for MLIs, each with its own advantages and limitations.

1. **Pulse Width Modulation (PWM):**

Pulse Width Modulation (PWM) is the most widely used technique for controlling the output voltage and current of MLIs. PWM regulates the inverter switches to generate a voltage waveform that closely approximates a sinusoidal signal. Two commonly used PWM techniques are:

- **Sinusoidal PWM (SPWM):** SPWM involves comparing a sinusoidal reference signal with a high-frequency triangular carrier wave. The intersection points determine the switching instants of the inverter devices. This method is simple, easy to implement, and effective for reducing low-order harmonics in the output voltage. SPWM is suitable for standard industrial drives such as pumps, fans, and conveyors, where moderate performance is acceptable.

- **Space Vector PWM (SVPWM):** SVPWM is a more sophisticated technique that uses the space vector representation of voltages to optimize switching. Unlike SPWM, SVPWM maximizes the utilization of the DC bus voltage and reduces total harmonic distortion (THD). This results in higher efficiency and smoother motor operation. SVPWM is particularly useful in high-performance applications such as robotics, electric traction motors, and CNC machines, where precise torque and speed control are critical.

**2. Selective Harmonic Elimination (SHE):**

SHE is an advanced PWM strategy aimed at eliminating specific low-order harmonics from the inverter output. By calculating precise switching angles for each voltage level, SHE minimizes harmonic distortion and improves waveform quality.

- This method is particularly advantageous in medium- and high-voltage applications, such as rolling mills, industrial motor drives, and grid-connected renewable energy systems, where harmonic mitigation is critical for both equipment longevity and regulatory compliance.
- SHE can be implemented in combination with SPWM or other modulation techniques to optimize both harmonic performance and switching losses.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- Challenges in SHE include solving complex nonlinear equations for switching angles and maintaining voltage balance in real-time, particularly in high-level MLIs with multiple voltage steps.

**3. Model Predictive Control (MPC):**

Model Predictive Control is an advanced, real-time control strategy that predicts the future behavior of the inverter system over a finite horizon. Based on this prediction, MPC selects the optimal switching states to achieve desired performance while satisfying system constraints.

- MPC simultaneously optimizes multiple objectives, including minimizing switching losses, reducing THD, and maintaining voltage and current within safe limits.
- It is highly adaptable to changing load conditions and can handle nonlinearities in industrial drive systems.
- MPC has gained popularity in high-performance industrial drives, such as variable- speed induction motors and permanent magnet synchronous motors, due to its fast dynamic response and robustness.
- One limitation of MPC is its computational complexity, which requires powerful microcontrollers or DSP-based platforms for real-time implementation.

**4. Fuzzy and Artificial Intelligence (AI)-Based Controllers:**

Fuzzy logic and AI-based controllers are increasingly being applied to MLIs to enhance performance under uncertain and nonlinear operating conditions.

- **Fuzzy Logic Controllers (FLCs):** FLCs use a rule-based system to mimic human reasoning in controlling inverter switching. They can adapt to load variations, motor parameter changes, and external disturbances without requiring an accurate mathematical model of the system. FLCs improve transient response, reduce torque ripple, and minimize losses in industrial drive applications such as robotics, rolling mills, and automated conveyors.

- **Machine Learning and AI-Based Techniques:** Machine learning algorithms, including neural networks and reinforcement learning, are used to optimize switching patterns in real-time, predict load behavior, and enhance fault-tolerant operation. AI- based controllers can also support predictive maintenance by analyzing inverter performance data and detecting early signs of component degradation. These techniques are especially valuable in Industry 4.0 environments, where smart factories require adaptive and self-optimizing drive systems.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

*Table 2: Control Strategies for High-Efficiency MLIs*

| Control Strategy | Advantages | Disadvantages | Suitable Applications |
|---|---|---|---|
| SPWM | Simple, easy to implement | Moderate THD | Standard industrial drives |
| SVPWM | Lower THD, better voltage utilization | Complex | High-performance motor drives |
| SHE | Eliminates specific harmonics | Requires solving nonlinear equations | Medium-high voltage systems |
| MPC | Predictive, reduces losses, fast response | Computationally intensive | Advanced industrial drives |
| Fuzzy/AI | Adaptive, robust | Needs training and tuning | Variable load environments, robotics |

## CHALLENGES IN INDUSTRIAL DRIVE APPLICATIONS

Although multilevel inverters (MLIs) offer significant advantages for industrial drive systems, including higher efficiency, reduced harmonic distortion, and improved voltage quality, their practical implementation in industrial environments is accompanied by several challenges. Addressing these challenges is crucial to ensure reliable, safe, and cost-effective operation. The main challenges are discussed in detail below:

### 1. Complexity of Control:

Higher-level MLIs, particularly those with more than five voltage levels, require sophisticated control algorithms to manage multiple aspects of operation. These include voltage balancing among capacitors, precise switching sequences, and harmonic mitigation. Implementing such algorithms in real-time can be computationally intensive. In industrial applications like high-speed rolling mills or robotics, any delay or inaccuracy in control can lead to mechanical stress, torque ripple, or reduced process efficiency. Additionally, external disturbances, such as voltage fluctuations in the supply network or sudden changes in load torque, require controllers to be adaptive and robust. This complexity often necessitates the use of advanced digital signal processors (DSPs) or field-programmable gate arrays (FPGAs) for real-time control implementation.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

**2. Component Count and Cost:**

As the number of levels in an MLI increases, the number of power electronic components— such as IGBTs, MOSFETs, diodes, and capacitors—also increases. For example, a seven- level NPC inverter requires more switches and clamping diodes than a three-level inverter, which directly impacts the system's cost and size. Additionally, larger component counts increase the probability of failure and complicate maintenance. For small or medium-scale industries, balancing the trade-off between improved waveform quality and the increased investment in hardware is a significant challenge. Careful economic analysis is necessary to select a topology that meets both performance and cost constraints.

**3. Switching Losses and Thermal Management:**

Even though MLIs are designed for high efficiency, switching losses cannot be entirely eliminated, especially at high operating frequencies used in industrial drives for precise motor control. Frequent switching generates heat in power devices, which can degrade device reliability and reduce lifespan. Efficient thermal management strategies—such as heat sinks, forced air or liquid cooling, and thermal monitoring systems—are essential to prevent overheating. For example, in high-power conveyor drives or extrusion machines, failure to manage thermal stress can lead to device breakdown, unplanned downtime, and increased maintenance costs. Advanced wide-bandgap devices like SiC and GaN transistors help reduce switching losses, but thermal management remains critical.

**4. Fault Tolerance and Reliability:**

Industrial environments are often harsh, with variable loads, dust, moisture, and temperature fluctuations. Any fault in the inverter, such as a short-circuited switch or capacitor failure, can halt the entire process, causing financial losses and operational delays. Ensuring fault tolerance is, therefore, a critical design requirement. Techniques like redundant modules, bypass circuits, and fault detection algorithms help maintain operation even when individual components fail. Predictive maintenance, using sensors and AI-based diagnostics, can identify potential failures before they occur, enhancing reliability and minimizing downtime.

**5. Electromagnetic Interference (EMI):**

Fast switching operations in MLIs generate high-frequency transients that can cause electromagnetic interference (EMI). EMI can adversely affect sensitive equipment in industrial plants, including sensors, communication lines, and control systems. Uncontrolled EMI may lead


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

to inaccurate measurements, signal disruptions, or malfunctioning of nearby electronic devices. To mitigate EMI, careful design practices are required, including proper grounding, shielding, and layout optimization. Passive and active filtering techniques can be employed to suppress EMI without compromising inverter efficiency.

**6. Additional Considerations:**

Beyond the major challenges mentioned, industrial MLIs face other practical constraints. These include the physical footprint of large inverter systems, noise generated by high- frequency switching, maintenance complexity in multi-level configurations, and compatibility with legacy industrial motors and controllers. Furthermore, regulatory standards for grid connection and electromagnetic compatibility may impose additional design constraints.

## SCOPE OF HIGH-EFFICIENCY MULTILEVEL INVERTERS

The future of industrial drive systems is closely linked with high-efficiency MLIs. Some of the emerging areas of scope include:

1. **Integration with Renewable Energy Systems:** MLIs can interface industrial drives with solar, wind, and hybrid energy systems, enabling energy-efficient operations while maintaining power quality.
2. **Wide-Bandgap Semiconductor Devices:** SiC and GaN devices offer higher switching speeds, lower conduction losses, and better thermal performance, allowing MLIs to operate at higher frequencies with increased efficiency.
3. **Advanced Control Techniques:** The adoption of predictive, adaptive, and AI-based control strategies can enhance MLI performance, reduce losses, and ensure robust operation under varying load conditions.
4. **Electric Vehicle and Smart Factory Applications:** High-efficiency MLIs are crucial for electric vehicle traction drives and smart factory automation, where energy efficiency and precise control directly impact operational cost and system performance.
5. **Modular and Scalable Designs:** Modular inverter designs offer flexibility for future upgrades, easier maintenance, and fault-tolerant operation. This approach is particularly useful in large industrial installations where continuous operation is essential.

### Industrial Applications

Multilevel inverters have found extensive application across various industrial sectors:

1. **Motor Drives:** MLIs are widely used in AC motor drives, such as induction motors and


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

permanent magnet synchronous motors, to achieve high efficiency, low torque ripple, and precise speed control.

2. **Robotics and Automation:** In industrial robots and automated conveyor systems, MLIs provide smooth motion control and reduce mechanical stress on actuators.
3. **Renewable Energy Integration:** MLIs enable smooth connection of renewable energy sources to industrial grids, allowing efficient power conversion and minimal harmonic injection.
4. **HVAC Systems:** High-efficiency inverters are used in industrial heating, ventilation, and air conditioning systems to regulate motor speed and reduce energy consumption.
5. **Process Industry Drives:** Applications in pumps, compressors, and rolling mills benefit from MLIs' ability to provide stable voltage and frequency control, reducing energy losses and improving process reliability.

**Performance Evaluation and Simulation**

Evaluating the performance of multilevel inverters (MLIs) is essential for ensuring their suitability and reliability in industrial drive applications. Simulation platforms such as MATLAB/Simulink, PSCAD, or PLECS are commonly used to model inverter behavior, optimize control strategies, and predict real-world performance without the need for costly prototypes. These simulations allow researchers and engineers to analyze multiple performance parameters under various operating conditions, including load variations, fault conditions, and switching scenarios.

**1. Total Harmonic Distortion (THD):**

Total Harmonic Distortion is a critical performance metric for MLIs. Lower THD indicates that the inverter output waveform closely approximates a pure sinusoidal voltage, resulting in smoother operation of connected motors and reduced electrical stress. High THD can lead to increased heating, vibration, torque ripple, and premature aging of equipment. In high- efficiency industrial applications, THD is typically maintained below 5%. Simulation studies allow engineers to assess the impact of different inverter topologies, modulation techniques (such as SPWM, SVPWM, or SHE), and control algorithms on THD. For example, combining selective harmonic elimination with cascaded H-bridge inverters often reduces THD more effectively than traditional PWM methods alone.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

**2. Switching Losses:**

Switching losses occur during the turn-on and turn-off transitions of semiconductor devices, such as IGBTs, MOSFETs, SiC, or GaN switches. High switching losses reduce overall inverter efficiency and generate additional heat, which must be dissipated to maintain device reliability. Through simulation, the effects of switching frequency, dead-time intervals, and modulation strategies on switching losses can be analyzed. Model-based studies help in selecting optimal switching schemes that minimize losses while maintaining waveform quality. For instance, high-frequency SVPWM combined with wide-bandgap devices significantly reduces switching losses in industrial motor drives.

**3. Voltage and Current Ripple:**

Voltage and current ripple are fluctuations superimposed on the desired output waveform. Excessive ripple can reduce the life of connected motors, capacitors, and other devices due to increased thermal and mechanical stress. Simulations can model these ripple effects under different operating conditions, including transient loads and voltage imbalances. Designers can evaluate the influence of filter components (such as LC or LCL filters), topology selection, and control strategies on ripple reduction. A well-designed multilevel inverter, especially with hybrid or cascaded topologies, can minimize voltage and current ripple, improving the overall reliability and efficiency of industrial drives.

**4. Dynamic Response:**

Dynamic response refers to the ability of the inverter to react rapidly to changes in load or operating conditions. In industrial environments, mechanical or electrical loads often vary suddenly, as in conveyor systems, rolling mills, or robotic arms. A fast dynamic response ensures that motor speed, torque, and voltage remain within desired limits, preventing mechanical stress and process disruptions. Simulation platforms enable the testing of dynamic performance under transient conditions, such as sudden acceleration, deceleration, or step load changes. Advanced control strategies, including model predictive control (MPC) or AI-based adaptive controllers, are particularly effective in improving dynamic response while maintaining low THD and minimal losses.

**5. Combined Performance Evaluation:**

Simulations often combine all these parameters to evaluate the overall performance of MLIs. By integrating advanced modulation techniques with hybrid inverter topologies, studies have shown


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

that industrial MLIs can achieve efficiency levels exceeding 97% while maintaining THD below 5% and reducing voltage ripple. For example, a cascaded H-bridge inverter with SVPWM or MPC control can simultaneously minimize switching losses, reduce harmonics, and provide robust performance under dynamic load conditions.

**6. Benefits of Simulation in Industrial Applications:**

- **Cost and Time Efficiency:** Allows designers to test multiple topologies and control strategies without building expensive hardware prototypes.
- **Predictive Analysis:** Identifies potential issues such as overvoltage, thermal stress, or component failure before physical implementation.
- **Optimization:** Enables fine-tuning of switching frequencies, modulation indices, filter parameters, and control gains to maximize efficiency and reliability.
- **Fault Analysis:** Simulates fault conditions like open-circuit switches, DC link imbalances, or sudden load changes, facilitating the design of fault-tolerant systems.

***Table 3: Performance Metrics of MLIs***

| Parameter | Typical Value | Remarks |
|---|---|---|
| Total Harmonic Distortion (THD) | <5% | Low THD desirable for motors |
| Efficiency | 96–98% | High efficiency reduces energy loss |
| Voltage Ripple | <3% | Ensures smooth motor operation |
| Switching Frequency | 1–10 kHz | Depends on device and topology |
| Load Response Time | <5 ms | Critical for dynamic industrial applications |

**FUTURE TRENDS**

The future development of high-efficiency MLIs for industrial drives is expected to focus on:

1. **Fault-Tolerant Modular Designs:** Enabling continuous operation even under component failure.
2. **Integration with IoT and Industry 4.0:** Smart monitoring and predictive maintenance using real-time data.
3. **Energy Storage Integration:** Coupling MLIs with battery storage or supercapacitors for peak shaving and load management.
4. **Ultra-High-Speed Drives:** Enabling applications in high-speed machining, electric


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

aviation, and advanced robotics.

5. **Environmentally Friendly Designs:** Reduction of rare-earth magnet dependency and use of recyclable materials in inverter components.

## CONCLUSION

Multilevel inverters have proven to be an effective technology for enhancing the performance of industrial electric drive systems, particularly in applications requiring high power and stringent power quality requirements. By employing multiple voltage levels, these inverters significantly reduce harmonic distortion and improve voltage waveform quality, leading to smoother motor operation and reduced stress on drive components. Advances in modulation techniques such as SVPWM and SHE enable precise control over switching patterns, contributing to higher efficiency and lower electromagnetic interference. The inclusion of energy storage and renewable energy sources within the inverter framework adds versatility, enabling industrial applications to achieve sustainability targets while maintaining operational reliability. Experimental results validate the theoretical models, demonstrating up to 98% efficiency and substantial THD reduction. Challenges such as capacitor voltage balancing and complexity in control strategies remain, but ongoing research into fault- tolerant topologies and predictive maintenance algorithms promises further improvements. The future of industrial drives lies in further miniaturization, cost reduction, and integration of smart control algorithms for fully autonomous systems.

## REFERENCES

1. Barnawi, A. B., Alfifi, A. R. A., Elbarbary, Z. M. S., Alqahtani, S. F., & Shaik, I. M. (2023). Review of multilevel inverter for high-power applications. *ResearchGate*. Retrieved from https://www.researchgate.net/publication/374617250
2. Sharma, B. (2025). A comprehensive review of multi-level inverters and their applications. *Scientific Reports*. https://doi.org/10.1038/s41598-024-84296-1
3. Taha, T. A. (2025). Recent advancements in multilevel inverters: Topologies, modulation techniques, and emerging applications. *Symmetry*, 17(7), 1010. https://doi.org/10.3390/sym17071010
4. Lemssaddak, S. (2025). Examining the current advancements in intelligent multilevel inverters for electric vehicle charging applications. *ScienceDirect*. https://doi.org/10.1016/j.ijepes.2025.106783
5. Halim, W. A. (2016). Review of multilevel inverter topologies and its applications.


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved

*Journal of Telecommunication, Electronic and Computer Engineering*, 8(1), 1–6. Retrieved from https://jtec.utem.edu.my/jtec/article/download/1278/769/3550

6. Chaturvedi, P. (2018). Conventional multilevel inverter: Topologies and control techniques. In *Power Electronics Handbook* (pp. 1–22). Elsevier. https://doi.org/10.1016/B978-0-12-814568-5.00003-4
7. Azizi, A. (2025). A review on topology and control strategies of high-power multilevel inverters. *ScienceDirect*. https://doi.org/10.1016/j.ijepes.2025.106714
8. Subha Lakshmi, N. (2024). A high efficient 33 level inverter for electric vehicle applications. *Taylor & Francis Online.* https://doi.org/10.1080/00051144.2024.2309445
9. Shakeera, S. (2024). An innovative 11-level multilevel inverter topology with reduced complexity. *Scientific Reports*. https://doi.org/10.1038/s41598-024-73791-0
10. Vishvakarma, A., & Singh, S. (2023). Multilevel inverters and its control strategies: A review. *Semantic Scholar*. Retrieved from https://www.semanticscholar.org/paper/Multilevel-inverters-and-its-control-strategies%3A-A-Vishvakarma-Singh/d34a73749715757ff021fad8c703eece5e83095c
11. Iraji, F., Tashakor, N., & Goetz, S. (2022). A generalized switched-capacitor modular multilevel inverter topology for multiphase electrical machines. *arXiv*. https://arxiv.org/abs/2204.06867
12. Pourdadashnia, A., Farhadi-Kangarlu, M., & Sadoughi, M. (2021). Staircase selective harmonic elimination in multilevel inverters to achieve wide output voltage range. *arXiv*. https://arxiv.org/abs/2104.05759


Page 91-105 © MANTECH PUBLICATIONS 2025. All Rights Reserved