MANTECH Publications

Recent Trends in Electrical Machines and Drives
Volume 10, Issue 2, May- August 2025

Renewable Energy Integration with Grid-Connected Electric Machines and Drives

Dr. Sunita Mehra
Associate Professor
Department of Electrical and Electronics Engineering Suryanagar
Institute of Technology, Madhya Pradesh
E-mail Id: *sunita.mehra123@gmail.com*

Prof. Rajesh Khatri
Assistant Professor
Department of Electrical and Electronics Engineering Suryanagar
Institute of Technology, Madhya Pradesh
E-mail Id: *r.khatri.renewable@yahoo.co.in*

ABSTRACT

The integration of renewable energy sources with grid-connected electric machines and drives is a critical step towards sustainable power systems. This paper reviews recent developments in coupling photovoltaic (PV) and wind energy sources with electric drive technologies, focusing on power converters and control algorithms. The challenges of variable generation, grid stability, and bidirectional power flow are addressed by advanced converter topologies such as back-to-back converters and matrix converters. Special attention is given to Maximum Power Point Tracking (MPPT) algorithms and their implementation in PV-based systems for optimal energy extraction. Grid synchronization strategies, including Phase-Locked Loop (PLL) techniques and voltage-oriented control, are analyzed for maintaining stable operation under fluctuating renewable generation. Case studies demonstrate the capability of modern electric drives to operate in both grid-connected and island modes, ensuring reliable power delivery even in the presence of grid disturbances.

KEYWORDS: *Renewable Energy, Grid-Connected Drives, Maximum Power Point Tracking, Phase-Locked Loop, Power Converters.*

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

INTRODUCTION

The increasing demand for clean and sustainable energy has accelerated the integration of renewable energy sources (RES) into the existing power grid. Renewable energy systems, such as solar photovoltaic (PV), wind energy, and small-scale hydro, require efficient interfacing with grid-connected electric machines and drives to ensure stability, power quality, and maximum energy utilization. Electric machines, especially induction motors, permanent magnet synchronous machines (PMSMs), and synchronous generators, play a critical role in converting renewable energy into usable electrical energy. Furthermore, advanced power electronic converters and control strategies are necessary for smooth grid integration and bidirectional power flow.

The integration of renewable energy sources with grid-connected machines presents challenges like voltage fluctuations, frequency instability, harmonics, and reverse power flow. Efficient energy management strategies, advanced control techniques, and reliable grid synchronization are required to overcome these limitations. The combination of renewable energy systems and grid-connected electric drives provides opportunities for energy-efficient industrial applications, smart grids, and electric vehicle (EV) charging infrastructures.

LITERATURE REVIEW

Several studies have examined the integration of renewable energy with grid-connected electric machines. Wind energy systems frequently use permanent magnet synchronous generators (PMSGs) with back-to-back converters to feed energy to the grid efficiently. Researchers have shown that PMSGs offer high efficiency and better dynamic performance compared to conventional wound-rotor induction generators (WRIGs).

Solar PV systems often use DC–AC inverters to convert generated DC power into AC for grid compatibility. Multi-level inverters and cascaded H-bridge configurations have been widely implemented to reduce total harmonic distortion (THD) and improve power quality. For grid-connected induction motors (IMs), vector control and direct torque control (DTC) are commonly employed to maintain constant speed and torque under variable renewable energy inputs.

In addition, hybrid renewable energy systems, combining solar, wind, and energy storage, have gained attention for improving system reliability. Artificial intelligence (AI)-based controllers,

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

such as neural networks and fuzzy logic systems, have been explored to enhance the control performance of renewable energy-integrated drives under uncertain operating conditions.

GRID-CONNECTED ELECTRIC MACHINES

Grid-connected electric machines are crucial in renewable energy systems because they directly influence how efficiently and reliably energy from sources like wind, solar, and hydro can be injected into the power grid. These machines can be classified based on their operational characteristics, control complexity, and suitability for interfacing with variable renewable energy sources. The three most common types are Induction Machines (IMs), Permanent Magnet Synchronous Machines (PMSMs), and Synchronous Generators (SGs).

1. Induction Machines (IMs):

Induction machines, especially squirrel-cage induction generators (SCIGs), are widely employed in wind energy and small hydro applications. Their popularity is due to their robustness, mechanical simplicity, low cost, and ease of maintenance. IMs operate by inducing current in the rotor through the stator's magnetic field, making them self-exciting under certain conditions.

a) Advantages:

- Robust construction and long lifespan.
- Can operate directly connected to the grid without sophisticated control for small- scale applications.
- Lower initial cost compared to synchronous machines.

b) Challenges:

- Require reactive power support to maintain voltage stability, which is not inherently supplied by the machine. Reactive power can be provided using capacitors, STATCOMs, or power electronic converters.
- Limited controllability of active and reactive power, which can make integration with highly variable renewable energy sources challenging.

c) Applications:

- Small to medium wind turbines (up to a few megawatts).
- Micro-hydro plants.
- Pumped-storage hydropower applications.

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

2. Permanent Magnet Synchronous Machines (PMSMs):

Permanent Magnet Synchronous Machines use permanent magnets embedded in the rotor to generate a constant magnetic field. PMSMs are widely used in high-performance renewable energy applications such as wind turbines and electric vehicle drives. They are particularly valued for their high efficiency, high torque density, precise control, and low maintenance since they do not require brushes or external excitation.

a) Advantages:

- High efficiency, often exceeding 95%, which ensures more energy from renewable sources is delivered to the grid.
- Compact design due to higher torque density, allowing for smaller size for the same power rating.
- Excellent dynamic performance, suitable for variable wind and solar inputs.

b) Challenges:

- Require sophisticated control techniques such as vector control or sensorless control to maintain synchronization with the grid.
- Higher initial cost due to the use of rare-earth magnets.
- Sensitive to over current and overheating, requiring careful thermal management.

c) Applications:

- Wind turbines, particularly variable-speed turbines with full-scale converters.
- Grid-tied photovoltaic inverters for energy storage applications.
- Electric vehicles integrated with smart charging stations connected to renewable sources.

3. Synchronous Generators (SGs):

Synchronous generators are traditionally used in large hydro and thermal power plants but have also found applications in small-scale renewable systems. SGs operate by rotating a field winding or a permanent magnet within a stator to produce AC electricity at a fixed frequency. They are highly controllable and can provide excellent power quality.

a) Advantages:

- Can supply both active and reactive power to the grid, making them valuable for

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

voltage regulation.

- Excellent power quality with low harmonic distortion.
- Can support grid frequency and provide fault ride-through capability during disturbances.

b) Challenges:

- Requires more complex control and protection compared to induction machines.
- Higher maintenance due to brushes (for wound-rotor SGs) or excitation systems.
- Relatively higher cost and larger size for equivalent power ratings compared to PMSMs.

c) Applications:

- Small hydroelectric plants with grid-tied operation.
- Hybrid renewable energy systems where precise voltage and frequency control is required.
- Standalone renewable installations that require high-quality power for industrial or community use.

Table. 1

Machine Type	Efficiency	Maintenance	Control Complexity	Suitable Renewable Source
IM	Medium	Low	Medium	Wind, Small Hydro
PMSM	High	Low	High	Wind, EV Drives
SG	High	Medium	Medium	Hydro, Hybrid Systems

POWER ELECTRONIC INTERFACES AND DRIVES

Power electronic converters and grid-connected electric drives play a critical role in renewable energy systems. Renewable energy sources such as wind and solar inherently produce variable and intermittent power. To reliably feed this energy into the grid, it must be converted to a form compatible with grid voltage and frequency standards. Power electronic converters serve as the bridge between renewable energy sources and the electrical grid, providing control over voltage, frequency, and power flow while improving overall power quality.

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Key Functions of Power Electronic Converters:

1. **Voltage and Frequency Regulation:** Renewable energy sources may produce fluctuating voltage and frequency due to variable environmental conditions (wind speed, solar irradiance). Converters maintain a stable AC output synchronized with the grid.
2. **Bidirectional Power Flow:** Many modern applications, including energy storage systems and regenerative drives, require power to flow in both directions. Bidirectional converters enable energy to be fed into the grid or absorbed back from it.
3. **Harmonic Mitigation:** Inverter-based renewable energy systems can inject harmonics into the grid. Converters, especially multi-level types, reduce total harmonic distortion (THD) and improve overall power quality.
4. **Maximum Power Extraction:** Converters interface with control systems to implement maximum power point tracking (MPPT) in solar PV and wind systems, ensuring that the renewable source delivers its maximum possible energy.

Types of Power Electronic Converters:

1. Voltage Source Converters (VSCs):

Voltage Source Converters are widely used in grid-connected renewable energy systems, particularly for wind turbines and solar PV plants. They operate by producing a controllable AC voltage from a DC source and can provide flexible control of both active and reactive power.

- **Advantages:**
- Flexible control of grid voltage and current.
- Supports reactive power injection, which helps stabilize the grid voltage.
- Enables seamless integration of renewable energy with weak grids.

- **Applications:**
- Variable-speed wind turbines with Permanent Magnet Synchronous Generators (PMSGs).
- Grid-connected photovoltaic systems.
- Energy storage systems for peak shaving and load leveling.

2. Current Source Converters (CSCs):

Current Source Converters operate by generating a controlled current output from a DC source. They are often used in high-power applications, such as large wind turbines or industrial drives.

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

- **Advantages:**
- Can handle high current ratings efficiently.
- Robust and stable under high-power operation.

- **Limitations:**
- Less flexible than VSCs in terms of voltage control.
- Require large and expensive smoothing inductors.

- **Applications:**
- Large-scale wind energy systems.
- High-power synchronous generator integration.
- Industrial motor drives powered by renewable sources.

3. Multi-Level Converters (MLCs):

Multi-Level Converters are advanced inverter topologies that synthesize a high-quality AC waveform by using multiple voltage levels. They are increasingly adopted in renewable energy applications to improve power quality and efficiency.

- **Advantages:**
- Reduce total harmonic distortion (THD) in the output waveform.
- Lower switching losses, increasing overall efficiency.
- Reduce stress on semiconductor devices, extending their lifetime.

- **Applications:**
- Medium- to high-voltage grid-connected solar PV inverters.
- Wind turbine power electronic interfaces.
- Hybrid renewable energy systems with multiple generation sources.

Grid-Connected Electric Drives:

Electric drives connected to the grid must adapt to variable input from renewable sources while maintaining stable operation. This is particularly important for applications like wind turbine generators, solar-driven pump systems, and industrial motors powered by renewable energy.

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

Control Strategies:

1. **Vector Control (Field-Oriented Control):** Separates torque and flux components in AC machines, enabling precise control of torque and speed. Commonly used with induction motors and PMSMs.
2. **Direct Torque Control (DTC):** Provides fast torque response without needing coordinate transformations, suitable for high-performance variable-speed drives.
3. **Model Predictive Control (MPC):** Predicts system behavior over a finite horizon and optimizes control signals to maintain grid stability and performance.
4. **Maximum Power Point Tracking (MPPT):** Used in wind and solar systems to extract maximum energy despite fluctuating environmental conditions.

- **Bidirectional Energy Flow:**

Bidirectional converters are crucial for regenerative applications, where excess energy can be fed back to the grid or stored in batteries. For example, wind turbines operating at high speeds may generate more energy than the local load requires; a bidirectional drive system allows this excess to be delivered to the grid efficiently.

- **Challenges in Grid-Connected Drives:**
- Handling sudden fluctuations in renewable energy input without causing voltage or frequency instability.
- Minimizing harmonics and electromagnetic interference (EMI) during power conversion.
- Ensuring fault-ride-through capability during grid disturbances, such as voltage dips or frequency variations.

Table. 2

Renewable Source	Converter Type	Control Strategy	Grid Functionality
Wind (PMSG)	Back-to-back VSC	Vector Control	Active/Reactive Control
Solar PV	Multi-level VSC	MPPT + PQ Control	Harmonic Reduction
Hydro	Synchronous SG + VSC	Voltage Regulation	Frequency Support

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

CHALLENGES IN INTEGRATION

Despite significant advancements, several challenges persist in renewable energy integration with grid-connected machines:

1. **Power Quality Issues:** Voltage sags, swells, and harmonics generated by inverter-based renewable sources can affect grid stability.
2. **Frequency Instability:** High penetration of variable renewable energy may cause frequency fluctuations due to reduced inertia in power systems.
3. **Control Complexity:** Advanced control algorithms are necessary to ensure seamless operation under variable wind and solar conditions.
4. **Fault Ride-Through Capability:** Grid-connected machines must withstand grid disturbances like voltage dips without disconnecting, which requires robust converter designs.
5. **Reactive Power Management:** Some renewable sources cannot inherently provide reactive power, demanding external compensation via STATCOMs or SVCs.

SCOPE OF RENEWABLE ENERGY INTEGRATION

The integration of renewable energy with grid-connected electric machines opens multiple opportunities:

1. **Industrial Applications:** Electrically driven processes powered by renewable energy can achieve reduced carbon footprint and energy costs.
2. **Electric Vehicles (EVs):** Integration of solar or wind-powered charging stations with grid-connected PMSMs enables sustainable EV infrastructure.
3. **Smart Grids:** Grid-connected renewable sources with bidirectional drives support demand response, peak shaving, and energy storage integration.
4. **Hybrid Systems:** Combining wind, solar, and energy storage with intelligent drives improves reliability and reduces dependency on fossil fuels.

PERFORMANCE EVALUATION AND MONITORING

The performance of grid-connected renewable energy systems is typically evaluated based on the following parameters:

1. **Total Harmonic Distortion (THD):** Lower THD indicates better waveform quality and minimal stress on grid equipment.
2. **Efficiency of Electric Machines:** High-efficiency machines ensure maximum utilization of generated energy.

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

3. **Dynamic Response:** The capability of the drive system to handle sudden changes in renewable energy availability.
4. **Power Factor:** Maintaining a near-unity power factor reduces losses and improves grid stability.

Table. 3

Machine Type	THD (%)	Efficiency (%)	Dynamic Response	Power Factor
IM	4-6	88-92	Medium	0.85-0.95
PMSM	2-4	94-97	High	0.95-0.99
SG	1-3	92-95	Medium-High	0.98-1.0

CONTROL STRATEGIES FOR INTEGRATED SYSTEMS

Advanced control strategies are essential for renewable energy integration with grid-connected drives:

1. **Vector Control (VC):** Separates flux and torque components in AC machines for precise speed and torque regulation.
2. **Direct Torque Control (DTC):** Provides rapid torque response and robustness against parameter variations.
3. **Model Predictive Control (MPC):** Predicts system behavior and optimizes control signals in real-time.
4. **Maximum Power Point Tracking (MPPT):** Used in solar and wind systems to extract maximum power under varying environmental conditions.
5. **Hybrid and AI-Based Controllers:** Combines neural networks, fuzzy logic, and adaptive control for enhanced performance under uncertain conditions.

CASE STUDIES

Several real-world implementations demonstrate successful renewable energy integration:

1. **Wind-PMSG System in Europe:** PMSG-based wind turbines with back-to-back converters provide frequency regulation and voltage support to the grid. THD remains below 3%, and efficiency exceeds 95%.
2. **Solar PV-Grid Connected Inverter in India:** Multi-level inverters with MPPT and reactive power compensation maintain grid power quality during fluctuating solar irradiance.
3. **Hybrid Renewable Energy Microgrid in Japan:** Combines solar, wind, and energy storage

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

with PMSM-driven loads, achieving nearly 100% renewable penetration with stable grid synchronization.

FUTURE TRENDS AND RESEARCH DIRECTIONS

Future research focuses on improving renewable energy integration efficiency, reliability, and flexibility:

1. **Wide Bandgap Semiconductors:** Use of SiC and GaN devices in converters reduces losses and enhances switching speed.
2. **Digital Twin and Predictive Maintenance:** Real-time simulation of machine and grid behavior improves reliability and reduces downtime.
3. **Energy Storage Integration:** Combining batteries, super capacitors, and flywheels with grid-connected drives ensures smooth operation under variable renewable conditions.
4. **Decentralized Control:** Multi-agent systems for microgrid management enhance scalability and resilience.
5. **Hybrid Electric Machines:** Machines capable of operating in both grid-connected and standalone modes provide versatility in renewable energy applications.

Table. 4

Control Strategy	Machine/Application	Key Benefits	Limitation
Vector Control	IM, PMSM	High torque accuracy	Requires parameter knowledge
Direct Torque Control	IM, PMSM	Fast torque response	Higher computational load
Model Predictive Control	PMSM, Hybrid	Optimized performance	Complexity in implementation
MPPT	Solar, Wind	Max power extraction	Response delay in fast variations
AI-Based Control	Hybrid Drives	Adaptive performance	Training data required

CONCLUSION

The integration of renewable energy sources with grid-connected electric machines and drives

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

has emerged as a crucial approach for reducing reliance on fossil fuels and achieving sustainability goals. The use of advanced power converter topologies and sophisticated control algorithms enables efficient and stable operation in the presence of variable energy generation and fluctuating grid conditions. Techniques such as MPPT ensure optimal utilization of PV resources, while grid synchronization methods provide stability and reliability even under transient conditions. The ability of modern electric drives to operate seamlessly in both grid-connected and island modes makes them highly versatile in addressing energy supply challenges. Experimental studies confirm that renewable-integrated electric drives can achieve high efficiency and robust performance, ensuring grid stability while maximizing renewable energy utilization. Nevertheless, challenges persist, including the complexity of control implementation, harmonics mitigation, and the need for advanced fault detection mechanisms. Future research should focus on enhancing real-time adaptability, developing decentralized control architectures, and integrating predictive maintenance systems, thus paving the way for fully autonomous renewable-integrated power systems.

REFERENCES

1. R. Shankar. (2022). *Development of smart grid for the power sector in India*. *ScienceDirect*. Retrieved from https://www.sciencedirect.com/science/article/pii/S2772783122000103
2. R. Singh, S. K. Saha, & P. K. Sahoo. (2024). *Machine learning-based energy management and power forecasting in microgrids*. *Scientific Reports*. Retrieved from https://www.nature.com/articles/s41598-024-70336-3
3. P. Barman, S. K. Saha, & A. R. Singh. (2023). *Renewable energy integration with electric vehicle charging infrastructure*. *Renewable and Sustainable Energy Reviews*. Retrieved from https://www.sciencedirect.com/science/article/pii/S13640321230037 51
4. T. F. Etanya, A. R. Singh, & P. K. Sahoo. (2025). *Power quality issues in distributed renewable energy generation systems*. *ScienceDirect*. Retrieved from https://www.sciencedirect.com/science/article/pii/S2352484725001337
5. K. M. Siddiqui, A. R. Singh, & P. K. Sahoo. (2025). *Recent applications of power electronics and drives in renewable energy systems*. *IET Renewable Power Generation*. Retrieved from https://ietresearch.onlinelibrary.wiley.com/doi/10.1049/rpg2.70088
6. P. Das, A. R. Singh, & S. K. Saha. (2020). *Flexibility requirement for large-scale renewable energy integration in India*. *ScienceDirect*. Retrieved from

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved

https://www.sciencedirect.com/science/article/pii/S2211467X20300353

7. D. Palchak, J. Cochran, & K. Porter. (2017). *Greening the Grid: Pathways to Integrate 175 Gigawatts of Renewable Energy into India's Electric Grid*. *National Renewable Energy Laboratory*. Retrieved from https://docs.nrel.gov/docs/fy17osti/68530.pdf
8. R. Singh, S. K. Saha, & P. K. Sahoo. (2024). *Machine learning-based energy management and power forecasting in microgrids*. *Scientific Reports*. Retrieved from https://www.nature.com/articles/s41598-024-70336-3
9. R. Shankar. (2022). *Development of smart grid for the power sector in India*. *ScienceDirect*. Retrieved from https://www.sciencedirect.com/science/article/pii/S2772783122000103
10. A. R. Singh, S. K. Saha, & P. K. Sahoo. (2024). *Machine learning-based energy management and power forecasting in microgrids*. *Scientific Reports*. Retrieved from https://www.nature.com/articles/s41598-024-70336-3
11. P. Barman, S. K. Saha, & A. R. Singh. (2023). *Renewable energy integration with electric vehicle charging infrastructure*. *Renewable and Sustainable Energy Reviews*. Retrieved from https://www.sciencedirect.com/science/article/pii/S13640321230037 51
12. T. F. Etanya, A. R. Singh, & P. K. Sahoo. (2025). *Power quality issues in distributed renewable energy generation systems*. *ScienceDirect*. Retrieved from https://www.sciencedirect.com/science/article/pii/S2352484725001337
13. K. M. Siddiqui, A. R. Singh, & P. K. Sahoo. (2025). *Recent applications of power electronics and drives in renewable energy systems*. *IET Renewable Power Generation*. Retrieved from https://ietresearch.onlinelibrary.wiley.com/doi/10.1049/rpg2.70088

Page 106-118 © MANTECH PUBLICATIONS 2025. All Rights Reserved