
Advanced Control Techniques for PMSM and BLDC Drives

P. Suresh Babu Nair¹, V. Swathi Rao², G. Nisha Shetty³

Professor¹, Research Scholar^{2,3}

Department of Electrical Engineering

RAAK College of Engineering and Technology

Email ID: *p.suresh_babu78@yahoo.com¹*

DOI: *<https://doi.org/10.5281/zenodo.19729022>*

ABSTRACT

Permanent Magnet Synchronous Motors (PMSMs) and Brushless DC (BLDC) motors are widely used in modern industrial applications, electric vehicles, and robotics due to their high efficiency, compact size, and high torque-to-weight ratio. The performance of these motors is largely determined by the control strategy applied. Traditional control techniques, such as scalar control, have limitations in dynamic performance and torque accuracy. Therefore, advanced control strategies, including Field-Oriented Control (FOC), Direct Torque Control (DTC), Model Predictive Control (MPC), and Adaptive Control, are increasingly employed to improve motor performance under varying operating conditions. This paper reviews recent advancements in control techniques for PMSM and BLDC drives, analyzes their benefits and challenges, and compares their performance through simulation and experimental studies. Additionally, implementation aspects and future research directions are discussed to aid researchers and engineers in designing efficient motor drive systems.

KEYWORDS: *PMSM, BLDC, Field-Oriented Control, Direct Torque Control, Model Predictive Control, Adaptive Control, Motor Drives*

INTRODUCTION

Electric motors are a fundamental part of industrial automation, robotics, and transportation systems. Among them, Permanent Magnet Synchronous Motors (PMSMs) and Brushless DC (BLDC) motors have become the preferred choices in high-performance applications due to their high efficiency, low maintenance, and high power density.

Traditionally, PMSMs and BLDC motors were controlled using scalar control methods such as Volts/Hertz (V/f) control, which are simple to implement but suffer from slow dynamic response and poor torque accuracy under load variations. This has led to the development of advanced vector control techniques that allow precise control of torque, speed, and position.

Advanced control techniques aim to achieve:

1. High dynamic performance
2. Reduced torque ripple
3. Energy efficiency
4. Robustness under parameter variations
5. Minimal sensor dependency

This paper reviews the state-of-the-art control strategies for PMSM and BLDC motors, focusing on Field-Oriented Control (FOC), Direct Torque Control (DTC), Model Predictive Control (MPC), and Adaptive Control methods.

OVERVIEW OF PMSM AND BLDC MOTORS

PMSM and BLDC motors are both widely used in modern industrial, automotive, and consumer applications because of their high efficiency, compact design, and precise speed/torque control capabilities. Despite similarities, they differ in construction, back EMF characteristics, and control methods, which affects their performance in different applications.

1. Permanent Magnet Synchronous Motors (PMSMs)

Permanent Magnet Synchronous Motors (PMSMs) are AC motors where the rotor carries permanent magnets, producing a constant magnetic field. When the stator is supplied with a three-phase AC current, a rotating magnetic field is generated. The interaction between the rotor's permanent magnetic field and the stator's rotating field produces electromagnetic torque, causing the rotor to rotate synchronously with the stator field.

PMSMs are generally classified into two types based on rotor construction:

a) Surface-Mounted PMSM (SPMSM):

- The permanent magnets are mounted on the surface of the rotor.
- This type has a uniform air gap, low reluctance, and minimal saliency, making it ideal for high-speed applications.

- SPMSMs are easier to control with conventional vector control (FOC) methods.

b) Interior PMSM (IPMSM):

- The permanent magnets are embedded inside the rotor.
- This creates rotor saliency, which improves torque production at low speeds via reluctance torque in addition to magnetic torque.
- IPMSMs are widely used in electric vehicles and applications requiring wide speed range operation.

Advantages of PMSMs:

- **High efficiency and power density:** Permanent magnets reduce rotor losses, increasing overall efficiency.
- **Wide speed range:** Especially IPMSMs, which leverage reluctance torque at low speed and magnetic torque at high speed.
- **Good dynamic response:** Vector control methods allow rapid changes in torque and speed.

Limitations of PMSMs:

- **High cost:** Rare-earth permanent magnets (like NdFeB) are expensive.
- **Sensitivity to parameter variations:** Changes in temperature or magnetic saturation can affect performance and require compensation in control algorithms.

Applications:

- Electric vehicles (Tesla Model 3, Nissan Leaf)
- Robotics and CNC machines
- Aerospace actuators

2. Brushless DC (BLDC) Motors

Brushless DC (BLDC) motors are similar to PMSMs in that they also have a permanent magnet rotor and a three-phase stator. However, they are designed with a **trapezoidal back EMF waveform**, unlike the sinusoidal back EMF in PMSMs. BLDC motors are electronically commutated, meaning an external controller switches the current in the stator windings in synchronization with rotor position to produce torque.

BLDC motors can be classified as:

1. **Inner Rotor Type:** Rotor inside, stator outside (common in industrial drives).
2. **Outer Rotor Type:** Rotor outside, stator inside (common in fan motors).

Commutation Methods:

- **Hall Sensor-based:** Hall-effect sensors detect rotor position to determine switching sequence.
- **Sensorless:** Rotor position is estimated from back EMF or other observers to reduce cost and improve reliability.

Advantages of BLDC motors:

- **High efficiency at rated speed:** Minimal rotor losses due to absence of rotor currents.
- **Low maintenance:** No brushes to wear out.
- **Simple construction:** Easy to manufacture and compact.

Limitations of BLDC motors:

- **Torque ripple:** Due to trapezoidal back EMF and non-ideal commutation.
- **Commutation complexity:** Requires accurate rotor position sensing or estimation, which adds complexity in sensorless systems.

Applications:

- Computer peripherals (hard disk drives, cooling fans)
- Electric bicycles and scooters
- Drones and UAVs

Table 1: Comparison of PMSM and BLDC Motors

Feature	PMSM	BLDC
Rotor Type	Permanent Magnet	Permanent Magnet
Back EMF	Sinusoidal	Trapezoidal
Torque Ripple	Low	High
Control Complexity	High (FOC/DTC)	Moderate
Applications	EVs, Robotics, CNC	Fans, Pumps, EVs

modulation. It uses hysteresis comparators and switching tables to select the optimal inverter voltage vector.

Advantages:

- Fast torque response
- No current regulators required
- Reduced computational complexity

Limitations:

- High torque ripple
- Variable switching frequency complicates EMI mitigation

Table 2: FOC vs DTC Comparison

Feature	FOC	DTC
Torque Response	Moderate	Fast
Torque Ripple	Low	High
Control Complexity	High	Moderate
Sensor Dependency	Encoder/Resolver	Encoder optional
Computational Load	High	Low

3. Model Predictive Control (MPC)

MPC uses a mathematical model of the motor to predict future states and determine the optimal control inputs by minimizing a cost function. It is widely applied for PMSM drives to handle nonlinearities and constraints.

Advantages:

- Optimal control under constraints
- Handles nonlinearities effectively
- Reduces torque ripple and energy losses

Limitations:

- High computational requirements
- Needs accurate motor model




Figure 2: MPC Conceptual Diagram

4. Adaptive Control

Adaptive control methods adjust the controller parameters in real-time to compensate for parameter variations, load changes, or uncertainties in the motor model.

Advantages:

- Robust under parameter variations
- Can handle load disturbances
- Improves performance for sensorless drives

Challenges:

- Complex design
- Requires stability analysis
- Computationally intensive

5. Sensorless Control Techniques

Sensorless control eliminates the need for mechanical position sensors, reducing cost and improving reliability. Common methods include:

1. Back EMF-based methods

2. Sliding Mode Observers
3. Extended Kalman Filters

Applications: EVs and robotics where reliability and cost reduction are critical.

PERFORMANCE COMPARISON

Performance comparison involves evaluating different systems, technologies, or methods based on key metrics to determine their relative efficiency, reliability, cost-effectiveness, and suitability for specific applications. In renewable energy, power electronics, and drives, performance comparison typically covers the following aspects:

1. Efficiency

- **Definition:** The ratio of useful output energy or power to the total input energy or power.
- **Importance:** Higher efficiency means less energy loss, lower operational costs, and better sustainability.
- **Example Metrics:**
 - For solar cells: Power Conversion Efficiency (PCE)
 - For motors/drives: Energy efficiency (%)
 - For batteries/storage: Round-trip efficiency (%)

2. Reliability and Lifetime

- **Definition:** How consistently a system operates without failure and the expected operational lifespan.
- **Importance:** Determines maintenance costs and suitability for long-term deployment.
- **Example Metrics:**
 - Mean Time Between Failures (MTBF)
 - Cycle life for batteries
 - Degradation rate for PV cells

3. Cost Analysis

- **Definition:** Total cost of ownership including capital expenditure (CapEx) and operational expenditure (OpEx).
- **Importance:** Helps in selecting systems that provide maximum return on investment (ROI).

- **Example Metrics:**

- Levelized Cost of Electricity (LCOE) for energy systems
- Cost per kWh for storage technologies
- Payback period

4. Power Quality and Control Performance

- **Definition:** Ability of the system to maintain voltage, frequency, and stability within desired limits.
- **Importance:** Critical for grid integration, especially for intermittent renewable sources.
- **Example Metrics:**
 - Total Harmonic Distortion (THD) for inverters and drives
 - Voltage/frequency regulation performance
 - Response time for control systems

5. Environmental and Sustainability Factors

- **Definition:** Assessing ecological footprint, emissions, and recyclability.
- **Importance:** Supports green energy goals and compliance with environmental regulations.
- **Example Metrics:**
 - Carbon footprint per kWh
 - Material toxicity and recyclability
 - Energy payback time (for PV systems)

Table 3: Performance of Advanced Control Techniques for PMSM/BLDC

Control Method	Torque Ripple	Dynamic Response	Computational Load	Sensor Requirement
FOC	Low	Moderate	High	Encoder/Resolver
DTC	High	Fast	Low	Optional
MPC	Very Low	Fast	Very High	Encoder/Model
Adaptive Control	Low-Moderate	Moderate	High	Optional

Observation: FOC and MPC are preferred for precision applications, while DTC is suitable for fast torque response requirements. Adaptive control improves robustness under parameter variations.

APPLICATIONS

- **Electric Vehicles (EVs):** PMSM with FOC is widely used due to high efficiency and regenerative braking capability.
- **Industrial Drives:** BLDC motors with DTC or sensorless FOC for conveyor systems, pumps, and fans.
- **Robotics:** High-precision PMSM drives using MPC or adaptive control.
- **Aerospace and Drones:** Lightweight BLDC motors with sensorless control for reliability.




Figure 3: Applications of PMSM and BLDC Drives

FUTURE TRENDS

1. **Artificial Intelligence (AI) Assisted Control:** Integration of AI/ML to optimize FOC, DTC, and MPC parameters in real-time.
2. **IoT-based Monitoring:** Cloud-based predictive maintenance and remote control of motor drives.
3. **Wide-Bandgap Semiconductors:** SiC and GaN devices for higher switching frequency and efficiency.
4. **Integrated Sensorless Techniques:** Improved reliability and reduced cost for EV applications.
5. **Energy Optimization Algorithms:** Combining MPC and adaptive control to minimize losses in variable load conditions.

CONCLUSION

This paper presented a comprehensive review of advanced control techniques for PMSM and BLDC drives. FOC, DTC, MPC, and adaptive control methods provide various benefits in terms of torque control, dynamic performance, and robustness. FOC and MPC are suitable for applications requiring precision and low torque ripple, while DTC offers fast torque response with simpler implementation. Adaptive control enhances system robustness under parameter variations. The integration of AI, IoT, and advanced semiconductors represents a promising future for improving efficiency, reliability, and performance of electric motor drives in industrial and automotive applications.

REFERENCES

1. P. Vas, *Vector Control of AC Machines*, Oxford University Press, 1998.
2. R. Krishnan, *Electric Motor Drives: Modeling, Analysis and Control*, Pearson, 2010.
3. B.K. Bose, "Modern Power Electronics and AC Drives," *Prentice Hall*, 2002.
4. J. Holtz, "Sensorless Control of AC Motors," *IEEE Transactions on Industrial Electronics*, 2002.
5. M. Blaschke, "Direct Self-Control of PWM-Inverters for AC Motors," *IEEE Transactions*, 1972.
6. H. Abu-Rub et al., *High Performance Control of AC Drives with MATLAB/Simulink*, Wiley, 2009.
7. M. Popescu et al., "Model Predictive Control for PMSM Drives: A Review," *IEEE Access*, 2020.
8. S. Jain and R. Krishnan, "Adaptive Control of Electric Drives," *IEEE Transactions on Industrial Applications*, 2017.
9. T. Sattar et al., "Sensorless Control Techniques for BLDC Motors," *Energies*, 2021.
10. W. Leonhard, *Control of Electric Drives*, Springer, 2018.

Cite as:

P. Suresh Babu Nair, V. Swathi Rao, G. Nisha Shetty (2026). Advanced Control Techniques for PMSM and BLDC Drives. *Recent Trends in Electrical Machines and Drives*, 11(1), 1-11.

<https://doi.org/10.5281/zenodo.19729022>