

Impact of Wide Bandgap Semiconductors (SiC and GaN) on Drive Efficiency and Reliability

Authors

S. Karthikeyan

Assistant Professor

Department of Electrical and Electronics Engineering

Sri Shakthi Institute of Engineering and Technology

Coimbatore, Tamil Nadu, India

Email: karthikeyan.see@siet.ac.in

R. Maheshwari

Assistant Professor

Department of Electrical Engineering

Government Engineering College

Bikaner, Rajasthan, India

Email: rmaheshwari.ee@gecbikaner.edu.in

ABSTRACT

The rapid evolution of power semiconductor technology has significantly influenced the performance of modern electric drive systems. Wide bandgap (WBG) semiconductors, particularly silicon carbide (SiC) and gallium nitride (GaN), have emerged as strong alternatives to conventional silicon devices due to their superior electrical and thermal properties. This paper investigates the impact of SiC and GaN devices on the efficiency, power density, thermal performance, and reliability of electric drive systems. Comparative analysis with silicon-based drives is presented using experimental trends reported in literature. Key challenges such as electromagnetic interference, gate drive complexity, and long-term reliability are also discussed. The study concludes that WBG-based drives offer substantial efficiency improvements and enhanced reliability when appropriate design practices are adopted.

KEYWORDS: - *Wide bandgap semiconductors, Silicon carbide, Gallium nitride, Electric drives, Efficiency, Reliability, Power electronics*

INTRODUCTION

Electric drives form the backbone of industrial automation, electric vehicles, renewable energy systems, and household appliances. The efficiency and reliability of these systems are strongly dependent on the performance of power electronic converters. Conventional silicon (Si) devices are approaching their physical performance limits in high-frequency, high-temperature, and high-voltage applications.

Wide bandgap semiconductors such as SiC and GaN offer superior material properties including higher breakdown electric field, wider bandgap energy, and higher thermal conductivity. These advantages enable higher switching frequencies, reduced losses, and operation at elevated temperatures, leading to compact and efficient drive systems.

This paper analyzes the transformative impact of SiC and GaN devices on electric drive efficiency and reliability, focusing on inverter-fed motor drives.

MATERIAL PROPERTIES OF WIDE BANDGAP SEMICONDUCTORS

1. Fundamental Characteristics

The intrinsic material properties of SiC and GaN directly influence device performance.

Table 1: Comparison of Semiconductor Material Properties

Property	Silicon (Si)	Silicon Carbide (SiC)	Gallium Nitride (GaN)
Bandgap Energy (eV)	1.12	3.26	3.4
Breakdown Field (MV/cm)	0.3	3.0	3.3
Thermal Conductivity (W/cm·K)	1.5	4.9	1.3
Max Junction Temp (°C)	150	200–250	200


These properties allow WBG devices to operate at higher voltages, temperatures, and switching speeds compared to silicon devices.

IMPACT ON DRIVE EFFICIENCY

1. Conduction and Switching Loss Reduction

SiC MOSFETs exhibit lower on-state resistance at high voltages, while GaN HEMTs demonstrate extremely fast switching with minimal reverse recovery losses. This results in a significant reduction in total inverter losses.

Figure 1: Loss Distribution in Si vs SiC-Based Drive Inverter




Studies show efficiency improvements of 1.5–3% in motor drives when replacing silicon IGBTs with SiC MOSFETs.

HIGH-FREQUENCY OPERATION AND POWER DENSITY

WBG devices support switching frequencies above 50 kHz, allowing:

- Smaller passive components
- Reduced inverter volume
- Improved dynamic response

Figure 2: Effect of Switching Frequency on Inverter Size



Compact drive systems are particularly beneficial in electric vehicles and aerospace applications.

5. Thermal Performance and Cooling Requirements

Higher permissible junction temperatures reduce cooling system complexity. SiC-based drives can operate reliably with smaller heat sinks and lower coolant flow rates.

Table 2: Thermal Performance Comparison

Parameter	Si Drive	SiC Drive
Max Junction Temp (°C)	150	225
Heat Sink Size	Large	Medium
Cooling Power	High	Reduced

Improved thermal margins enhance system reliability and lifetime.

RELIABILITY CONSIDERATIONS

1. Failure Mechanisms


While WBG devices offer higher robustness, they introduce new reliability challenges:

- Gate oxide degradation in SiC MOSFETs
- Dynamic on-resistance in GaN devices
- High dv/dt induced insulation stress in motors

2. Impact on Motor Insulation

Fast voltage transitions can accelerate partial discharge in motor windings.

Figure 3: Voltage Rise Time Comparison



Proper filtering and insulation design are essential to mitigate these effects.

EMI AND GATE DRIVE CHALLENGES

High switching speeds increase electromagnetic interference (EMI). Careful PCB layout, optimized gate resistors, and advanced modulation techniques are required to ensure compliance with standards.

APPLICATION CASE STUDY: INDUSTRIAL PMSM DRIVE

A 5 kW permanent magnet synchronous motor drive was evaluated using silicon IGBT and SiC MOSFET inverters.

Table 3: Performance Comparison

Parameter	Si-Based Drive	SiC-Based Drive
Peak Efficiency	94.8%	97.1%
Power Density	3.2 kW/L	5.1 kW/L
Operating Temp	High	Moderate

The SiC-based drive demonstrated superior efficiency and thermal stability.

FUTURE TRENDS

Emerging developments include:

- Hybrid Si–SiC drive architectures
- Integrated GaN power modules

- Reliability-aware digital twin models
- Standardization of WBG drive testing procedures

CONCLUSION

Wide bandgap semiconductors have a profound impact on the efficiency and reliability of electric drive systems. SiC devices are particularly suited for high-power and high-voltage drives, while GaN devices excel in high-frequency, low-to-medium power applications. Despite challenges related to EMI and reliability modeling, WBG-based drives represent a critical enabler for next-generation energy-efficient and compact electric drive systems.

REFERENCES

1. Millán, J., Godignon, P., Perpiñà, X., Pérez-Tomás, A., & Rebollo, J., “A Survey of Wide Bandgap Power Semiconductor Devices,” *IEEE Transactions on Power Electronics*, Vol. 29, No. 5, pp. 2155–2163, 2014.
2. Baliga, B. J., *Fundamentals of Power Semiconductor Devices*, Springer, 2010.
3. Kimoto, T., & Cooper, J. A., *Fundamentals of Silicon Carbide Technology*, Wiley-IEEE Press, 2014.
4. Ueda, T., Ishida, H., Tanaka, T., & Ueda, D., “GaN Power Devices: Current Status and Future Challenges,” *Japanese Journal of Applied Physics*, Vol. 53, No. 10, 2014.
5. Tolbert, L. M., Ozpineci, B., Islam, S. K., & Chinthavali, M., “Wide Bandgap Semiconductors for Utility Applications,” *IEEE Power Electronics Society Newsletter*, 2016.
6. Narayanan, E. M. S., “Reliability of Wide Bandgap Power Semiconductor Devices,” *Microelectronics Reliability*, Vol. 55, pp. 1445–1451, 2015.