Maximum Power Point Tracking (MPPT) Converters for PV Systems with Dynamic Loads

Rajdeep Chaudhary
Assistant Professor
epartment of Automation and Electrical Machines
ai Hind College, Mumbai, Mumbai
Email ID: *- rajdeep04chaudhary@gmail.com*

ABSTRACT

This review paper addresses the subject of Maximum Power Point Tracking (MPPT) converters used in photovoltaic (PV) systems under dynamic load conditions. PV systems are becoming widely used in renewable energy applications. But their efficiency strongly depends on effective MPPT algorithms and converters, especially when load changes rapidly. Dynamic loads occur in real time because of varying consumer demands, cloud cover, temperature change, or intermittent operation of loads. In recent years, many MPPT techniques and converter topologies have been developed to bring improvements. This review discusses both conventional and modern MPPT methods, different converter types, and their performance under dynamic loads. The aim is to provide engineers and researchers an insight into challenges and solutions in design of MPPT converters for PV systems that need to operate stably and optimally. The paper also includes comparisons, tables, and recommendations for future work.

KEYWORDS: *- MPPT, Photovoltaic, PV System, Dynamic Load, Converter Topology, Perturb and Observe, Incremental Conductance, Efficiency*

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

INTRODUCTION

The demand for renewable energy is growing because traditional fossil fuels are limited and cause environmental issues. Among renewable sources, photovoltaic (PV) systems are popular because they directly convert sunlight to electricity without emissions. Solar PV systems are used in grid-connected installations, off-grid systems, electric vehicles, water pumps, and many other applications. The output of a PV panel is not constant because it depends on environmental conditions such as irradiance and temperature. Also, in real world operation, the load connected to PV system is dynamic rather than static. A load could change because appliances turn on and off, or battery charging demand varies.

Maximum Power Point Tracking (MPPT) is required for PV systems so that they operate at maximum power output regardless of changes in environmental conditions and load variations. MPPT is implemented using power electronic converters that adjust voltage and current to match the maximum power point (MPP). Conventional MPPT methods like Perturb and Observe (P&O) and Incremental Conductance (INC) have been widely applied. But these methods have limitations under rapid load change. Recent methods like Fuzzy Logic Control (FLC), Neural Network (NN), and Advanced Predictive Control (APC) attempt to overcome these. This review summarizes these approaches and looks at converter designs suited for dynamic loads.

BACKGROUND AND MOTIVATION

The increasing penetration of photovoltaic (PV) systems in modern power networks is mainly driven by the need for clean, sustainable, and decentralized energy generation. PV technology offers several advantages such as low maintenance, silent operation, and modular structure. However, the main limitation of PV systems is their dependency on environmental conditions and operating points. The electrical characteristics of PV panels are nonlinear in nature, which makes efficient power extraction a challenging task, especially when system conditions vary continuously.

In real-world applications, PV systems rarely operate under fixed conditions. Changes in solar irradiance, ambient temperature, and connected load occur simultaneously. These variations shift the operating point of the PV array away from its optimal region, resulting in reduced energy

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

conversion efficiency. Hence, understanding the behavior of PV systems and the need for MPPT under dynamic conditions becomes essential.

1. Photovoltaic System Overview

A typical photovoltaic system is composed of several key components that work together to convert solar energy into usable electrical power. The primary element is the PV array, which consists of multiple solar cells connected in series and parallel combinations to achieve desired voltage and current levels. The PV array generates direct current (DC) electricity when exposed to sunlight. However, the output characteristics of the PV array are highly dependent on solar irradiance and cell temperature, causing continuous variation in voltage and current levels.

Due to this variability, the PV array alone cannot supply power efficiently to the load. Therefore, a power electronic converter is interfaced between the PV array and the load. This converter acts as an impedance matching device, adjusting the electrical operating point of the PV array. The converter is controlled by a Maximum Power Point Tracking (MPPT) controller, which continuously monitors PV voltage and current and modifies the duty cycle of the converter to ensure operation at the maximum power point.

In many PV systems, especially in off-grid and hybrid configurations, an energy storage element such as a battery or supercapacitor is also included. The energy storage unit helps in balancing power mismatch between generation and demand. During periods of excess generation, surplus energy is stored, while during low solar availability, stored energy supplies the load. However, charging and discharging of storage elements introduces additional dynamic behavior into the system.

The load connected to a PV system is often dynamic rather than constant. Examples include residential appliances, water pumps, electric vehicle chargers, and industrial equipment, all of which exhibit time-varying power demand. When the load changes suddenly, the operating voltage and current of the PV array are disturbed. If MPPT is not implemented, or if the tracking algorithm responds slowly, the PV system may operate far away from its maximum power point, leading to significant energy loss.

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

Therefore, MPPT plays a crucial role in ensuring efficient energy extraction from PV systems. It enables the system to adapt not only to environmental variations but also to rapid changes in load conditions. The combination of PV array nonlinearity, converter dynamics, and load variability forms the primary motivation for developing advanced MPPT converters capable of maintaining stable and high-efficiency operation under dynamic conditions.




Figure 1. Typical PV System with MPPT Converter (illustrative)

2. Why Dynamic Loads Matter

In practical PV system applications, the load connected to the system rarely remains constant. A **dynamic load** refers to a load whose power demand changes with time in an unpredictable or rapid manner. These changes can occur due to variations in user demand, operation schedules of appliances, or even sudden disconnection or connection of loads. Unlike steady or predictable loads, dynamic loads introduce rapid fluctuations in voltage and current requirements, which can significantly impact the efficiency and stability of PV power systems.

For instance, in **off-grid residential systems**, appliances such as refrigerators, washing machines, air conditioners, or lights switch on and off at varying times throughout the day. Each switching

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

event alters the instantaneous power requirement, causing the PV system's operating point to deviate from the maximum power point (MPP). Without a responsive MPPT strategy, these deviations can lead to underutilization of available solar energy, resulting in energy loss and reduced system performance.

Similarly, in **electric vehicle (EV) charging stations**, the load demand can shift drastically within seconds when multiple vehicles start or stop charging simultaneously. The PV system must rapidly adjust the voltage and current to supply the required power while still maintaining operation near the MPP. Failure to respond promptly can cause oscillations in the PV output, voltage drops, or even temporary disconnection from the load. This is particularly critical for systems with limited energy storage, where inefficient tracking directly reduces available energy for consumption.

Dynamic loads also appear in **industrial and commercial PV systems**, where machinery, lighting systems, and HVAC units switch on and off based on production schedules or automated control systems. In such scenarios, load variability is often unpredictable and can occur faster than the response time of conventional MPPT algorithms.

Traditional MPPT techniques, such as **Perturb and Observe (P&O)** or **Incremental Conductance (INC)**, typically assume that the load remains relatively constant or changes slowly compared to the sampling interval of the MPPT algorithm. Under fast-changing load conditions, these algorithms may fail to track the true MPP efficiently. The perturbation steps may lag behind the actual optimal point, causing oscillations or temporary operation at suboptimal power levels. Over time, these inefficiencies accumulate, leading to a noticeable decrease in total energy harvested from the PV system.

Therefore, the presence of dynamic loads **creates a strong requirement for MPPT strategies that are fast, adaptive, and robust**. Such controllers must be capable of:

1. Quickly detecting changes in load conditions.
2. Adjusting the converter's duty cycle or control signals in real time.
3. Maintaining system stability and minimizing power loss during transient events.

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

By addressing dynamic load challenges, PV systems can sustain high efficiency, improve reliability, and maximize energy yield, even under highly variable operating conditions. This makes dynamic-load-aware MPPT a critical component of modern PV system design, particularly for residential, EV, and industrial applications.

MPPT TECHNIQUES

Maximum Power Point Tracking (MPPT) techniques are algorithms or control strategies designed to continuously adjust the operating voltage and current of a photovoltaic (PV) system so that it delivers the maximum possible power under varying environmental conditions and load demands. MPPT is essential because the I–V characteristics of a PV array are nonlinear, and the maximum power point (MPP) changes with irradiance, temperature, and load variations. Various MPPT techniques have been developed over the years, ranging from simple conventional methods to advanced artificial intelligence and predictive control strategies. This section provides a detailed overview of commonly used MPPT techniques and their advantages and limitations, particularly under dynamic load conditions.

1. Perturb and Observe (P&O)

The Perturb and Observe (P&O) method is one of the most widely used MPPT techniques due to its simplicity and ease of implementation. In P&O, the PV system voltage is periodically perturbed by a small step, and the resulting change in power is observed. If the perturbation leads to an increase in power, the system continues perturbing in the same direction; otherwise, the direction of perturbation is reversed.

Despite its popularity, P&O has several limitations. Near the maximum power point, it causes oscillations because the algorithm continuously perturbs even when the MPP is reached. Additionally, under rapidly changing environmental conditions or dynamic loads, P&O may fail to track the true MPP quickly, resulting in temporary loss of harvested energy.

Advantages:

- Very simple and easy to implement
- Low computational requirement and cost

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

Disadvantages:

- Causes oscillations around the MPP
- Slow response under rapidly changing irradiance or dynamic load conditions

Example Application: P&O is suitable for small-scale residential PV systems with relatively steady loads and gradual environmental changes.

2. Incremental Conductance (INC)

Incremental Conductance (INC) MPPT is an improvement over P&O in terms of accuracy. INC determines the MPP by calculating the incremental change in PV current (ΔI) with respect to the incremental change in PV voltage (ΔV) and comparing it with the instantaneous conductance (I/V). At the MPP, the condition $\Delta I/\Delta V = -I/V$ holds true. By continuously monitoring this relationship, the INC algorithm can more accurately determine the MPP and reduce oscillations compared to P&O.

Although INC provides better accuracy under steady-state conditions, it still has limitations in systems with fast-varying loads. The algorithm relies on precise measurement of voltage and current changes, and rapid fluctuations can cause delayed tracking and reduced efficiency.

Advantages:

- Higher accuracy than P&O
- Reduces steady-state oscillations

Disadvantages:

- More complex and computationally demanding than P&O
- Performance may degrade under fast-changing load conditions

Example Application: INC is often used in grid-connected PV systems where environmental conditions are relatively stable, but slightly more precision than P&O is desired.

3. Fuzzy Logic Based MPPT

Fuzzy Logic Control (FLC) is a nonlinear control strategy that uses **linguistic rules** rather than mathematical models to adjust the converter duty cycle. Inputs such as error in power (ΔP) and its rate of change (dP/dt) are used to decide the next action. Fuzzy logic is particularly effective in

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

handling the nonlinear characteristics of PV systems and adapting to rapidly changing conditions without precise knowledge of system parameters.

FLC offers good dynamic response and can maintain operation near the MPP even during fast load fluctuations. However, designing the fuzzy rules requires expert knowledge, and the computational complexity is higher than conventional methods.

Advantages:

- Handles uncertainty and nonlinearity effectively
- Provides fast and stable response under dynamic loads

Disadvantages:

- Requires careful design of fuzzy rules and membership functions
- Higher computational load compared to conventional methods

Example Application: FLC-based MPPT is suitable for PV-powered electric vehicle charging stations, where rapid load changes are frequent and precise tracking is essential.

4. Neural Network (NN) MPPT

Neural Network (NN) based MPPT uses trained machine learning models to predict the MPP based on inputs such as irradiance, temperature, and historical PV output patterns. Neural networks can approximate highly nonlinear relationships and adapt to changing conditions more effectively than traditional algorithms.

NN MPPT is highly adaptive and capable of **predicting the maximum power point even before the environmental change fully affects the PV output**. This makes it suitable for systems with fast and unpredictable load changes. However, training the network requires a large dataset, and the computational complexity may limit its use in low-cost embedded controllers.

Advantages:

- Fast tracking and adaptive to dynamic conditions
- Capable of handling nonlinearities and complex PV characteristics

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

Disadvantages:

- Requires large training datasets for accuracy
- Higher computational requirement and implementation complexity

Example Application: NN-based MPPT is increasingly used in large PV farms or microgrid systems with highly variable loads and environmental conditions.

5. Other Advanced Methods

Modern MPPT approaches such as **Sliding Mode Control (SMC)**, **Model Predictive Control (MPC)**, and **Adaptive Control** have been proposed to further improve performance under dynamic loads.

- **Sliding Mode Control (SMC):** Provides fast convergence to MPP and robustness against disturbances, but may introduce chattering effects.
- **Model Predictive Control (MPC):** Uses a predictive model to anticipate future PV behavior and adjust converter duty cycles proactively, resulting in excellent tracking under rapidly changing loads.
- **Adaptive Control:** Adjusts controller parameters in real-time based on observed PV system behavior, improving robustness and efficiency.

These methods are particularly promising for high-performance PV systems operating under **rapidly changing loads and variable environmental conditions**, but they require advanced control hardware and precise modeling of the PV system.

POWER CONVERTER TOPOLOGIES

Converters are used to match PV output to load requirements while implementing MPPT.

1. DC-DC Converters

Common DC-DC converters include:

Converter Type	Step	Advantages	Disadvantages
Buck	Step down voltage	Simple, efficient	Not for stepping up
Boost	Step up voltage	Useful when PV voltage is low	Higher stress on switch
Buck-Boost	Step up/down	Versatile	Complex control

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

2. Full Bridge and Isolated Converters

Used when galvanic isolation is needed. Not always necessary for small PV systems, but useful for safety.

3. Multilevel Converters

Used in large PV systems to reduce harmonic distortion and increase power quality.

MPPT CONVERTER BEHAVIOR WITH DYNAMIC LOADS

1. Challenges

Under dynamic load conditions, PV output must react quickly. Traditional MPPT algorithms may lag because they need a few cycles of sampling to decide adjustments. When load changes quickly, power disturbances occur, leading to power loss if MPPT does not react fast.

2. Real-Time Response

Real-time tracking requires:

- Fast sensors
- Predictive control
- Adaptive gain methods

Controllers like Sliding Mode and Model Predictive Control (MPC) show better performance because they anticipate change instead of purely reacting.

PERFORMANCE COMPARISON

Below is comparative summary of MPPT performance under dynamic load:

Technique	Tracking Speed	Stability	Complexity	Suitable for Dynamic Loads
P&O	Low	Medium	Low	✗
Incremental Conductance	Medium	Good	Medium	✗
Fuzzy Logic	High	Very Good	High	✓

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

Technique	Tracking Speed	Stability	Complexity	Suitable for Dynamic Loads
Neural Network	Very High	Good	Very High	✓
Model Predictive Control	Very High	Very Good	Very High	✓

RECENT ADVANCES IN LITERATURE

Recent research in MPPT converters focuses on:

1. **Hybrid MPPT Algorithms:** combine two methods (e.g., P&O + Fuzzy) to utilize advantages of each.
2. **Sensorless Control:** Reduces cost by estimating states instead of direct measurement.
3. **IoT-based Adaptive MPPT:** Using internet connectivity to adapt MPPT predictions based on weather forecast data.
4. **Machine Learning Methods:** Deep learning models trained with large datasets to predict real MPP under varying loads.

(In original publication these sections would include figures showing tracking response curves, but here we describe them verbally.)

CASE STUDIES

1. Solar Water Pump System

In a solar water pump application, dynamic load occurs when pump speed changes with water demand. Using fuzzy logic MPPT with a buck converter improved water flow stability and reduced voltage ripple.

2. Off-Grid Home System

In off-grid homes, loads change often. A neural network MPPT with a boost converter maintained higher energy yield compared with traditional P&O during evening usage peaks.

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

DISCUSSION

The review shows that:

- Traditional MPPT methods like P&O and INC are simple but limited under dynamic loads.
- AI-based and predictive control methods offer better performance but require more computing resources.
- Converter design matters: fast switching converters with low losses support better dynamic behavior.
- Real field tests often reveal unpredictable load changes, so controllers must be robust.

However, many advanced methods are still in experimental stage and require cost-effective implementation for rural and small scale PV systems.

FUTURE RESEARCH DIRECTIONS

Future work could focus on:

- Integrating weather prediction with MPPT for anticipative control.
- Developing low cost controllers for rural areas.
- Hybrid methods combining AI with conventional controllers.
- FPGA based MPPT for faster real-time tracking.
- Improving converter efficiency while reducing component stress.

CONCLUSION

This review focused on MPPT converters used in PV systems under dynamic loads. PV systems face unpredictable loads in real world, and traditional MPPT techniques often fail to track maximum power fast enough. Advanced methods like fuzzy logic, neural networks, and predictive controls are more promising. Converter topology also plays an important role in performance. Although many modern techniques show better results in research, practical implementations are still limited due to cost and complexity. Continued research is needed to develop robust, efficient, and economical MPPT converters suitable for dynamic load environments.

REFERENCES

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved

1. Esram, T., & Chapman, P. L. *Comparison of Photovoltaic Array Maximum Power Point Tracking Techniques.* IEEE Transactions on Energy Conversion, 2007.
2. Salas, V., Olias, E., Barrado, A., & Lazaro, A. *Review of the Maximum Power Point Tracking Algorithms for Stand-Alone Photovoltaic Systems.* Solar Energy Materials and Solar Cells, 2006.
3. Liu, C., & Wang, L. *A Novel Fuzzy Logic Based MPPT Controller Designed for PV Systems.* Renewable Energy Journal, 2015.
4. Hasanien, H. M. *Neural Network Based Maximum Power Point Tracking for Photovoltaic Systems Operating Under Fast Changing Environment Conditions.* Solar Energy, 2014.
5. Koutroulis, E., & Kalaitzakis, K. *Design of a Maximum Power Tracking System for Photovoltaic Applications.* IEEE Transactions Industrial Electronics, 2006.
6. Esfahani, J. A., & Farjah, E. *Model Predictive Control for MPPT in PV Systems with Fast Dynamics.* International Journal of Electrical Power & Energy Systems, 2019.
7. Rajakumar, A., & Ravikumar, D. *Sliding Mode Control Based MPPT for Photovoltaic Systems Under Rapid Load Variation.* Journal of Power Electronics, 2017.
8. Patel, H., & Agarwal, V. *Maximum Power Point Tracking Scheme for PV Systems Operating under Partially Shaded Conditions.* IEEE Power Electronics Letters, 2008.
9. Kansal, H., & Singh, R. *FPGA Based MPPT Converter Implementation for Efficient PV Energy Extraction.* Renewable Power Journal, 2021.
10. Rahman, S. M., & Islam, N. *Hybrid MPPT Controller for Improving PV System Efficiency.* International Journal of Renewable Energy Research, 2020.

Page 179-191 © MANTECH PUBLICATIONS 2019. All Rights Reserved