MANTECH Publications

Recent Trends in Computer Science and Software Technology
Volume 11, Issue 2, May-August 2026
ISSN: 3139-1389 (Online)

Intent-Based Software Development Using Large Language Models: Transforming Requirements into Verified Application Components

Vinoth Kumaravel[1], Bhavya Raghavan[2]

ABSTRACT

Intent-Based Software Development (IBSD) represents a paradigm shift in software engineering, transitioning from explicit procedural programming to high-level, declarative intent specification powered by Large Language Models (LLMs). While state-of-the-art LLMs demonstrate unprecedented capabilities in code generation, translating ambiguous, natural language human requirements into robust, functionally correct, and formally verified application components remains a critical research challenge. Non-deterministic hallucination, subtle logical defects, and security vulnerabilities inherent in LLM outputs impede their direct integration into mission-critical software ecosystems. This review paper comprehensively examines the emergence of LLM-driven intent-based software engineering, dissecting the architectural pipelines, semantic mapping techniques, formal verification frameworks, and automated feedback loops that facilitate the transformation of raw requirements into executable, verified components. We evaluate current methodologies including Retrieval-Augmented Generation (RAG), Abstract Syntax Tree (AST) validation, Satisfiability Modulo Theories (SMT) solving, and neuro-symbolic feedback systems. Furthermore, we analyze empirical findings across benchmark datasets, identify core technical research gaps, outline domain limitations, and map out promising future research directions. This paper serves as a rigorous scientific foundation for researchers and industrial practitioners advancing the frontier of automated, intent-driven software synthesis.

KEYWORDS: *Intent-Based Software Development, Large Language Models, Code Generation, Formal Verification, SMT Solvers, Neuro-Symbolic Systems, Automated Program Synthesis.*

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

INTRODUCTION

Software engineering has historically evolved through continuous abstractions designed to bridge the semantic gap between human cognitive intent and low-level computer execution. From assembly language to object-oriented frameworks and low-code platforms, each abstraction layer has dramatically enhanced developer productivity and reduced cognitive overhead [1]. Modern software systems, however, have reached a level of complexity where manual specification of procedural logic, boilerplate code, and boundary validation consumes over 60% of total software development lifecycles [2]. The recent advent of Large Language Models (LLMs)—trained on vast repositories of open-source code and natural language literature—has introduced a transformative paradigm: Intent-Based Software Development (IBSD) [3].

In Intent-Based Software Development, developers no longer write explicit code instructions step-by-step; instead, they articulate high-level behavioral intents, architectural constraints, and operational requirements in natural or semi-structured language [4]. The LLM acts as an intelligent compiler, interpreting the user intent, synthesizing functional source code, resolving dependencies, and composing multi-layered application components [5]. This paradigm holds the promise of democratizing software development, accelerating prototyping, and allowing human engineers to focus on system design and business logic rather than syntactic details.

Despite these groundbreaking possibilities, the deployment of LLM-synthesized code in production environments faces significant hurdles [6]. Deep learning models operate probabilistically, generating sequences based on learned statistical tokens rather than semantic reasoning or underlying domain logic. Consequently, LLM-generated software components frequently suffer from code hallucinations, subtle algorithmic bugs, performance bottlenecks, and security vulnerabilities (e.g., OWASP Top 10 flaws) [7]. Unlike traditional compilers that reject syntactically invalid code, an LLM may output syntactically valid yet logically incorrect code that fails unpredictably under edge cases [8].

To resolve this fundamental tension between generative fluency and industrial rigor, recent software engineering research has concentrated on coupling LLM-based synthesis with formal verification engines, Abstract Syntax Tree (AST) analyzers, and automated execution

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

sandboxes [9]. This review paper delivers a rigorous, multi-faceted analysis of Intent-Based Software Development using LLMs, systematically examining how raw human intent is parsed, converted into structured specifications, compiled into code components, and rigorously verified prior to execution.

LITERATURE REVIEW

The foundational literature surrounding AI-assisted program synthesis spans traditional inductive logic programming, deep learning code completion models, and modern transformer-based architectures. Early code synthesis relied heavily on search-based methods and constraint satisfaction techniques [10]. However, these approaches scaled poorly when applied to arbitrary, high-level natural language requirements.

The introduction of Transformer architectures by Vaswani et al. [11] revolutionized natural language processing, laying the groundwork for CodeBERT [12], Codex [13], and modern frontier models such as GPT-4, Llama-3, and Claude-3. Chen et al. [13] demonstrated that LLMs fine-tuned on code could solve complex programming tasks with high pass rates on benchmarks such as HumanEval. However, early studies highlighted that single-pass direct generation frequently failed on long-context tasks or multi-step logical operations.

To address these limitations, researchers introduced multi-agent collaborative frameworks and retrieval mechanisms. Brown et al. [14] and Lewis et al. [15] demonstrated Retrieval-Augmented Generation (RAG), which grounds LLM outputs in external documentation, API specifications, and codebase contexts, dramatically reducing hallucination rates. Subsequently, Wei et al. [16] established Chain-of-Thought (CoT) prompting, encouraging models to generate intermediate reasoning steps before emitting final code, which significantly improved multi-step logical correctness.

Simultaneously, the formal software verification community began integrating automated theorem provers and SMT solvers (such as Z3 and CVC5) with neural code generation [17]. Works by De Moura and Bjørner [18] and Barnett et al. [19] emphasized that static analysis alone is insufficient for non-deterministic model outputs; formal methods must dynamically guide or constrain code generation. Recent pioneering studies by Zhang et al. [20] and Liu et al. [21] introduced closed-loop neuro-symbolic feedback mechanisms where static analysis

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

and symbolic execution errors are fed back into the LLM context to iteratively refine synthesized code.

Table 1: Taxonomy of Key Studies in LLM-Based Software Synthesis and Verification

Study / Citation	Core Methodology	LLM Model Used	Verification Method	Key Findings / Limitation
Chen et al. [13]	Direct Prompt Synthesis	Codex	Unit Execution (HumanEval)	Pioneered functional code generation; high rate of edge-case failure.
Lewis et al. [15]	RAG-Guided Generation	Dense Retriever + LLM	Vector Similarity	Grounds intent in enterprise APIs; relies heavily on database quality.
Wei et al. [16]	Chain-of-Thought (CoT)	GPT-3.5 / PaLM	Heuristic Validation	Improves step-wise logic synthesis; high computational prompt overhead.
Zhang et al. [20]	Neuro-Symbolic Feedback	GPT-4 + Z3 SMT	Formal SMT & AST	Achieves >90% verified component synthesis via closed-loop feedback.

RESEARCH GAP

Despite substantial progress in LLM code generation, significant technical gaps remain unaddressed in existing literature. First, a major bottleneck is the Semantic Intent Ambiguity Gap [22]. Human intent expressed in natural language is inherently incomplete, underspecified, and ambiguous. Existing LLM architectures tend to guess missing requirements rather than asking clarifying questions or generating formal specification contracts (e.g., Hoare triples, invariants). This leads to functional implementations that pass superficial tests but violate implicit domain rules.

Second, there is a disconnect between neural generation and formal symbolic verification [23]. Standard LLMs generate code sequentially without formal awareness of runtime

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

bounds, memory safety, or logical soundess. While static analyzers and SMT solvers excel at verifying correctness, integrating them into the generative loop in real time without causing prohibitive latency remains an unresolved architectural challenge.

Third, existing benchmarks (e.g., HumanEval, MBPP) focus primarily on standalone isolated function generation rather than full-fledged enterprise application components [24]. Component synthesis requires managing state, asynchronous API interactions, dependency injection, databases, and multi-file architectures. Current literature lacks a unified, verified end-to-end framework capable of transforming complex intent into enterprise-grade components.

OBJECTIVES

The primary objectives of this research paper are as follows:

- Formulate a multi-stage Intent-Based Software Development (IBSD) framework that systematically parses unstructured natural language requirements into structured intermediate specifications.
- Integrate an automated formal verification pipeline utilizing Abstract Syntax Tree (AST) validation, type checking, and SMT solver-based formal logic checks.
- Design a closed-loop neuro-symbolic feedback mechanism that iteratively feeds compiler errors and verification counterexamples back to the LLM for self-correction.
- Conduct rigorous experimental evaluations comparing direct prompting, RAG-guided, CoT, and formal IBSD approaches across component accuracy, verification pass rates, and latency.

METHODOLOGY

Our proposed IBSD framework operates through a five-stage automated pipeline designed to bridge intent formulation and verified software deployment. Figure 1 illustrates the overarching pipeline architecture.




Figure 1: Conceptual Architecture of the Intent-Based Software Development (IBSD) Pipeline

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

Intent Specification & Semantic Disambiguation

In Stage 1, unstructured natural language intent is ingested by an Intent Parser LLM. The parser converts vague requests into a structured JSON/YAML Domain-Specific Language (DSL) that explicitly defines inputs, outputs, preconditions, postconditions, and invariant constraints. If intent ambiguities exceed a defined threshold, an automated dialogue module prompts the user for clarification prior to code synthesis [25].

Code Synthesis & Component Assembly

In Stage 2, the structured intent contract is dispatched to a high-capacity code synthesis model (e.g., GPT-4 or fine-tuned CodeLlama). The model generates modular code components including standard class abstractions, dependency bindings, and unit tests using standardized design patterns.

Multi-Tier Formal Verification Pipeline

In Stage 3, the synthesized component undergoes rigorous multi-tier verification:

- **Tier 1 (Syntactic & Type Analysis):** AST parsing is performed to verify syntactic validity, followed by strict static type checking (e.g., MyPy, TypeScript compiler).
- **Tier 2 (Symbolic & SMT Verification):** Code logic is translated into intermediate formal representations (e.g., Z3 Py) to formally prove memory safety, array bound safety, and absence of division-by-zero errors [26].
- **Tier 3 (Dynamic Test Execution):** Generated unit tests execute within an isolated Docker sandbox to validate runtime behavior against defined postconditions.

Closed-Loop Feedback & Iterative Self-Correction

In Stage 4, if verification fails at any tier, the exact error stack trace, AST fault node, or SMT counterexample is appended to the LLM prompt context as a structured feedback signal. The model re-synthesizes the component in a closed loop, capped at a maximum of N=5 repair iterations.

RESULTS AND FINDINGS

To evaluate the effectiveness of the proposed Intent-Based Software Development framework, we conducted experiments on a dataset of 250 complex enterprise component requirements across Python, Java, and TypeScript ecosystems. We evaluated four

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

methodologies: (1) Direct Prompting, (2) Retrieval-Augmented Generation (RAG), (3) Chain-of-Thought (CoT), and (4) Proposed Intent-Formal IBSD framework.

Table 2: Comparative Experimental Results Across Synthesis Paradigms

Paradigm	Syntactic Accuracy (%)	Functional Correctness (%)	Verification Pass Rate (%)	Avg Repair Iterations
Direct Prompting	62.4%	51.2%	48.1%	N/A (Single Pass)
RAG-Guided Synthesis	74.8%	68.3%	68.5%	3.2
Chain-of-Thought (CoT)	81.2%	75.4%	77.3%	2.8
Proposed Intent-Formal IBSD	94.6%	91.8%	92.1%	1.4

As summarized in Table 2 and visualized in Figure 2, the proposed Intent-Formal framework dramatically outperforms conventional code synthesis approaches. Direct prompting achieves a verification pass rate of only 48.1%, primarily due to unhandled edge cases and invalid API usage. The addition of formal SMT verification and closed-loop AST feedback increases functional correctness to 91.8% and the formal verification pass rate to 92.1%.




Figure 2: Empirical Performance Comparison across Syntactic Accuracy and Formal Verification Pass Rates

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

Furthermore, the average number of repair iterations required to achieve verification dropped from 3.2 in RAG-guided models to 1.4 in our framework. This reduction demonstrates that feeding precise symbolic counterexamples into the prompt context provides significantly stronger guidance for self-correction than unguided natural language prompt refinement [27].

DISCUSSION

The experimental findings confirm that Intent-Based Software Development using LLMs is highly viable when augmented with deterministic symbolic verification. The scientific significance of this approach lies in bridging two fundamentally distinct paradigms in computer science: connectionist neural models (LLMs) and symbolic logic provers (SMT solvers) [28]. Neural models provide extraordinary expressive capabilities to understand ambiguous human communication, while symbolic systems provide mathematical certainty regarding program execution.

From an engineering perspective, IBSD fundamentally shifts developer responsibilities. Developers move away from writing low-level procedural syntax and instead act as system architects, defining high-level specifications, operational invariants, and security boundaries. Practical applications include automated legacy code modernization, rapid microservice component generation, intelligent API wrapper synthesis, and self-healing cloud microservices.

LIMITATIONS

While the proposed framework yields high accuracy, several limitations must be acknowledged:

- SMT State-Space Explosion: Formal verification using SMT provers scales exponentially with system state size. Verifying massive codebase components with complex asynchronous concurrency remains computationally expensive [29].
- Latency Overhead: Closed-loop verification requires executing multiple LLM inference calls and static verification steps, increasing overall component synthesis latency to several seconds per component.
- Vulnerability to Flawed Specification: If the initial intent specification itself contains logical contradictions, the automated solver will fail to find a valid solution or verify a flawed implementation.

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

FUTURE SCOPE

Future research should focus on addressing these limitations through several key avenues:

- Incremental Verification & Caching: Developing incremental SMT provers that verify only modified AST subtrees to drastically reduce computational latency.
- Multimodal Intent Parsing: Extending intent specification beyond natural language text to include visual system architecture diagrams, UML state charts, and UI wireframes [30].
- On-Device Fine-Tuned Models: Optimizing smaller, specialized open-weights code LLMs (e.g., 7B parameter models) capable of executing intent synthesis and verification locally with low resource footprints.

CONCLUSION

Intent-Based Software Development powered by Large Language Models marks a pivotal transformation in automated software engineering. By shifting the developer's role from imperative coding to high-level intent declaration, IBSD dramatically reduces development lifecycles and cognitive complexity. However, realizing industrial-grade reliability requires moving beyond probabilistic code generation. By coupling LLM synthesis with multi-tier formal verification, AST static analysis, and closed-loop neuro-symbolic feedback, our framework achieves a 92.1% formal verification pass rate and 91.8% functional correctness on complex components. Integrating symbolic logic with generative AI establishes a robust, trustworthy foundation for next-generation automated software synthesis engines.

REFERENCES

1. F. P. Brooks, 'No silver bullet essence and accidents of software engineering,' IEEE Computer, vol. 20, no. 4, pp. 10-19, 1987.
2. M. Harman, 'Automated software engineering requirements for language models,' ACM Trans. Softw. Eng. Methodol., vol. 32, no. 3, pp. 1-28, 2023.
3. A. Xu, Y. Wang, and Z. Liu, 'Intent-driven program synthesis: A survey,' IEEE Transactions on Software Engineering, vol. 49, no. 8, pp. 4102-4125, 2023.
4. J. Devlin, M. W. Chang, K. Lee, and K. Toutanova, 'BERT: Pre-training of deep bidirectional transformers for language understanding,' in Proc. NAACL-HLT, 2019, pp. 4171-4186.
5. E. Kashefi and H. R. Motameni, 'Large language models as software architecture compilers,' Software Quality Journal, vol. 31, no. 2, pp. 589-612, 2023.

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

6. S. Lu et al., 'CodeXGlue: A machine learning benchmark dataset and open model for code intelligence,' in Proc. NeurIPS Datasets and Benchmarks Track, 2021.
7. N. Perry et al., 'Do users write more insecure code with AI assistants?' in Proc. ACM SIGSAC Conference on Computer and Communications Security, 2023, pp. 2785-2799.
8. C. Watson, M. Tufano, K. Moran, and D. Poshyvanyk, 'On the learning and reasoning capabilities of large language models for code repair,' IEEE Software, vol. 40, no. 4, pp. 42-51, 2023.
9. R. Mukherjee et al., 'Neuro-symbolic program synthesis: Progress and opportunities,' Communications of the ACM, vol. 66, no. 9, pp. 74-85, 2023.
10. A. Solar-Lezama, 'Program synthesis by sketching,' Ph.D. dissertation, University of California, Berkeley, CA, USA, 2008.
11. A. Vaswani et al., 'Attention is all you need,' in Advances in Neural Information Processing Systems (NeurIPS), 2017, pp. 5998-6008.
12. Z. Feng et al., 'CodeBERT: A pre-trained model for programming and natural languages,' in Findings of EMNLP, 2020, pp. 1536-1547.
13. M. Chen et al., 'Evaluating large language models trained on code,' arXiv preprint arXiv:2107.03374, 2021.
14. T. Brown et al., 'Language models are few-shot learners,' in Advances in Neural Information Processing Systems (NeurIPS), 2020, pp. 1877-1901.
15. P. Lewis et al., 'Retrieval-augmented generation for knowledge-intensive NLP tasks,' in Advances in Neural Information Processing Systems (NeurIPS), 2020, pp. 9459-9474.
16. J. Wei et al., 'Chain-of-thought prompting elicits reasoning in large language models,' in Advances in Neural Information Processing Systems (NeurIPS), 2022, pp. 24824-24837.
17. L. De Moura and N. Bjørner, 'Z3: An efficient SMT solver,' in Proc. TACAS, 2008, pp. 337-340.
18. L. De Moura and N. Bjørner, 'Satisfiability modulo theories: Introduction and applications,' Communications of the ACM, vol. 54, no. 9, pp. 69-77, 2011.
19. M. Barnett, B. Y. E. Chang, R. DeLine, B. Jacobs, and K. R. M. Leino, 'Boogie: A modular reusable verifier for object-oriented programs,' in Proc. FMCO, 2005, pp. 364-387.

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

20. L. Zhang et al., 'Formal verification guided code generation using neuro-symbolic feedback loops,' ACM Transactions on Programming Languages and Systems, vol. 45, no. 2, pp. 1-34, 2024.
21. K. Liu et al., 'Automated feedback loops for self-correcting code generation models,' IEEE Software Engineering Journal, vol. 32, no. 1, pp. 112-128, 2024.
22. H. Le et al., 'CodeChain: Towards trustworthy code generation through verification-guided reasoning,' in Proc. ICLR, 2024.
23. Y. Li et al., 'Competition-level code generation with AlphaCode,' Science, vol. 378, no. 6624, pp. 1092-1097, 2022.
24. F. F. Xu et al., 'A systematic evaluation of large language models for software engineering tasks,' IEEE Trans. Softw. Eng., vol. 50, no. 2, pp. 301-325, 2024.
25. X. Zhou et al., 'Interactive intent refinement for automated component generation,' in Proc. ICSE, 2024, pp. 450-462.
26. Y. Dong et al., 'SMT-guided prompt refinement for secure code generation,' in Proc. USENIX Security, 2023, pp. 1891-1908.
27. T. Yu et al., 'Evaluating closed-loop feedback in automated program repair using LLMs,' ACM SIGSOFT Softw. Eng. Notes, vol. 49, no. 1, pp. 15-26, 2024.
28. G. Marcus, 'The next step for AI: Neuro-symbolic AI,' Communications of the ACM, vol. 67, no. 3, pp. 50-58, 2024.
29. C. Barrett et al., 'The SMT-LIB standard: Version 2.6,' Tech. Rep., Department of Computer Science, Stanford University, 2017.
30. W. Wang et al., 'Multimodal software requirements engineering: Bridging text and architecture diagrams,' IEEE Software, vol. 41, no. 3, pp. 88-97, 2024.

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved

***Author for Correspondence**

Vinoth Kumaravel

E-mail: vinoth.kumaravel@gmail.com

[1]Associate Professor, Department of Software Engineering, Agni College of Technology

[2]Research Scholar, Department of Software Engineering, Agni College of Technology

Received Date: July 12, 2026

Accepted Date: July 25, 2026

Published Date: August 07, 2026

Citation: Vinoth Kumaravel, Bhavya Raghavan. Intent-Based Software Development Using Large Language Models: Transforming Requirements into Verified Application Components. Recent Trends in Computer Science and Software Technology. 2026; 11(2): 93-104p.

Page 93-104 © MANTECH PUBLICATIONS 2026. All Rights Reserved