MANTECH Publications
Recent Trends in Computer Science and Software Technology
Volume 6, Issue 1, January-April 2021

Air Quality Monitoring System

Abhishek Bhosle[1], Deegesh Gala[2], Harsh Gada[3], Manish Bhelande[4]
Students[1, 2, 3], Professor[4]
Department of Information Technology
Shah & Anchor Kutchhi Engineering College, Chembur, Mumbai, Maharashtra
Corresponding Authors' Email id: - *abhishek.bhosle@sakec.ac.in[1], deegesh.gala@sakec.ac.in[2], harsh.gada@sakec.ac.in[3], manish.bhelande@sakec.ac.in[4]*

Abstract

Now-moment of truth is air pollution is individual one of the most influential concern of the globe. Air pollution concedes possibility progress from anthropogenic or natural point of supply. Air pollutants of having or giving an atmosphere meaning like CO, CO2, SO2, NO2, and O3 suspended coarse matter (SPM), repairable pensile particulate matter (RSPM), and changeable organic compounds (VOCs) bear a excellent effect on people as political whole physical. Most of the major large town fashionable developing countries and most large town of the developed rural area exist suffering from it. Thus, to expand a actual time for action or event air quality and contamination listen system exist critical. We bear grown an arduino based air contamination indicator which linked a small-judge, minimum-cost sensor to an arduino microcontroller part. The advantages of the indicator bear a reliable resistance of some degree, very quick response improvement and long-life facial characteristics. It happens to be affordable, easy to use, cheap and minimum-power necessity tools which exist appropriate for mobile calculation, in addition to comprehensible information in visible form accumulation. It has a subject to series of actions to achieve result software intelligent to resolve, collected kind information in visible form with extreme accuracy. Simple instrument that can be commercially make use of.

Keywords*: - Air dirtiness, arduino, gas sensor, anthropogenic, general feeling or mood*

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

INTRODUCTION

Air contamination exist the attendance of extra not wanted concerning life smallest part, particulates or added harmful belongings into the soil gases around the earth. It exist a bigger cause of contamination, allergies, and in the course of time reasons of end of life to few human beings. In addition to harms to other existent being like that mammal in addition to edible material crops, or the environmental or buxom surroundings [1-2]. They exist in addition to responsible for having done for miscellaneous type respiratory contamination (like asthma), causes of various types of malignant growth fashionable thing, if they exist defenseless to these poison or chemical compound for long period of time of opportunity. For example, colorless odorless toxic gas (CO) happen extremely harmful to human beings as it grant permission come to pass weighty asphyxiation, headaches by way of the arrangement of carboxy-red body fluid and accordingly a reason of end of life if defenseless for a very long time. The world physical arranging (WHO) fashionable 2014 approximated that 7 heap human beings end of life general by way of air dirtiness. The very much alike closeness about equaled for one International Energy Agency (IEA) also [3]. These projectiles for weaponry or contaminant exist in addition to being the reason for miscellaneous material tragedy like air pollution and exhaustion of upper layer of atmosphere because of any of anthropogenic conduct, air pollution act the tumor and allure ruling exist of important standing to relieve particular conduct to limit it.

In this project we exist make use of create an IOT Based Air Pollution Monitoring System at which point we will monitor the Air Quality over a netting-attendant utilizing Internet and will cause to happen a class changing in netting-attendant when the air feature lose further the level, way when skilled exist enough amount of injurious something not liquid or solid exist present on the way like CO2, fume, flammable liquid, benzene and NH3. It will show the air kind fashionable PPM on netting-page because we can monitor it very without a doubt. MQ135 sensor, that exist high-quality choice for listen Air Quality as it can detects most injurious something not liquid or solid and can measure their amount correctly. In this IOT project, we can monitor the contamination level from unspecified area utilizing your data processing machine or movable. We can establish this order unspecified area and can also cause to

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

happen few instrument when contamination goes outside limits few level, like we can stimulate the Exhaust fan or can please alert SMS/mail to the consumer.

MATERIALS AND WORKING SUMMARY

We have used Arduino UNO, MQ135 gas sensor, DHT11 sensor, ESP8266 WIFI Module, Bread Board, Jumper wires. Our objective search out take the necessary information in visible form from sensors and to project that ahead of thingspeak cloud to resolve it utilizing a machine intelligence model. Further a SMS happen send to the worried human being if something not liquid or solid ppm goes above the level.

Working- We start with connecting the ESP8266 with the Arduino. ESP8266 runs on 3.3V and if you will give it 5V from the Arduino then it won't work properly and it may get damage. Connect the VCC and the CH_PD to the 3.3V pin of Arduino. The RX pin of ESP8266 works on 3.3V and it will not communicate with the Arduino when we will connect it directly to the Arduino. So, we will have to make a voltage divider for it which will convert the 5V into 3.3V. This can be done by connecting three resistors in series like we did in the circuit. Connect the TX pin of the ESP8266 to the pin 10 of the Arduino and the RX pin of the esp8266 to the pin 9 of Arduino through the resistors. Then we will connect the MQ135 sensor with the Arduino. Connect the VCC and the ground pin of the sensor to the 5V and ground of the Arduino and the Analog pin of sensor to the A0 of the Arduino. The MQ135 sensor can sense NH3, NOx, alcohol, Benzene, smoke, CO2 and some other gases, so it is perfect gas sensor for our Air Quality Monitoring Project. When we will connect it to Arduino then it will sense the gases, and we will get the Pollution level in PPM (parts per million). MQ135 gas sensor gives the output in form of voltage levels and we need to convert it into PPM. So for converting the output in PPM, here we have used a library for MQ135 sensor.

When it exceeds the limit of 1000 PPM, then it starts cause Headaches, sleepiness and stagnant, stale, stuffy air and if exceeds beyond 2000 PPM then it can cause increased heart rate and many other diseases. When the value will be less than 1000 PPM, then the SMS and web-page will display "Fresh Air". Whenever the value will increase 1000 PPM, then the LED will start blinking and the web-page will display "Poor Air, Open Windows". If it will increase 2000 then the LED will

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

keep blinking and web-page will display "Danger! Move to fresh Air".



Figure 1-Arduino



Figure 2- DHT11 Sensor



Figure 3- MQ135 Gas Sensor

WORKING PRINCIPLE

The major chip of the system is DHT11 and MQ135 sensors used for gas sensing analysis [8, 9, 10]. The Arduino or Genuino Uno is a modern microcontroller board based on the ATmega328P. It is simply related to a computer by a USB link or power. Connected to bread board for power source [10-11]. Using jumper wires the MQ135 gas sensor and DHT11 sensor unit is linked to the arduino Uno board. The sensors analog pin is then related to the analog pin 0 and digital pin to digital 8 on the arduino board, while +5V and the GND (ground) pins on the sensor unit are linked to the 5V Vcc and GND (ground) pin correspondingly on the arduino board. Using WIFI module, the arduino Uno board is then linked to Thingspeak cloud system to analyse its model. This part elaborates the hardware and software instruments and structural design of the detector.

METHODOLOGY

The tool grown in this project maybe set up familiar any Wi-Fi hotspot fashionable a supply with inhabitant's city area. As the symbol happen stimulate, the Arduino board loads the required book repository, flashes few primary messages in contact the LCD screen and start become aware of data from the MQ-135 sensor. The

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

responsiveness to stimuli curve of the sensor for various able to be exploded gases exist before expected time noticed above. The sensor can be measure for fear that allure analog something produced physical ability happen proportional to the aggregation of polluting something not liquid or solid fashionable PPM. The analog potential become aware of at the hold in place A0 of the Arduino is convinced to a mathematical advantage by using the fashionable-muscular ADC channel of the Arduino. The Arduino board bear 10-bit ADC channels, so the digitized worth ranges from 0 to 1023. The digitized worth maybe assumed equivalent to the consolidation of effort of gases fashionable PPM. The look at and understand written word financial worth is first presented ahead of LCD screen and give to the ESP8266 module covered fashionable decent string through in essence in continuing order function. The Wi-Fi piece is configured to do business the ThingSpeak IOT stand or stage. ThingSpeak happen an IOT analytics stand or stage time in military operation that admit to aggregate, visualize and break down to components live information in visible form streams fashionable the cloud. ThingSpeak provides instant visualizations of information in visible form position apiece IOT devices to ThingSpeak attendant. With the natural or acquired power in a to execute MATLAB secret language system fashionable ThingSpeak individual can perform connected to the internet examination and determination and subject to series of actions to achieve result of the data as it enter place. The Wi-Fi piece maybe connected with the ThingSpeak attendant by shipping AT commands from the piece. The module first test the AT startup by shipping the following command – AT

The command exist neglect the boss to the Wi-Fi piece utilizing computer program in continuing order function. In reaction to the command 'AT', the promises must respond accompanying 'OK' if the cloud time in military operation happen running. Then, the AT command to view the account of a happening facts happen give as trail - AT + GMRIn reaction to this command, the IOT political stance must act in answer to something by shipping back the account of a happening facts, sdk account of a happening and moment of truth container exist compiled. Next, the AT command to set the relation to Wi-Fi trend happen shipped as act in accordance with - AT + CWMODE = 1By background the limit fashionable CWMODE to 3, the Wi-Fi relates happen configured to SoftAP in addition to station way. This AT

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

command can really take three limits as take the place of:

1. set Wi-Fi connection to station mode
2. set Wi-Fi connection to SoftAP mode
3. set Wi-Fi connection to SoftAP + station mode

The command exist neglect the boss to the Wi-Fi piece utilizing computer program in continuing order function. In reaction to the command 'AT', the promises must respond accompanying 'OK' if the cloud time in military operation happen running. Then, the AT command to view the account of a happening facts happen give as trail - AT + GMRIn reaction to this command, the IOT political stance must act in answer to something by shipping back the account of a happening facts, sdk account of a happening and moment of truth container exist compiled. Next, the AT command to set the relation to Wi-Fi trend happen shipped as act in accordance with - AT + CWMODE = 1By background the limit fashionable CWMODE to 3, the Wi-Fi relates happen configured to SoftAP in addition to station way. This AT command can really take three limits as take the place.

This command takes four limit, place first parameter happen the link ID that maybe any between 0 to 4, second limit happen information in visible form length that maybe maximum 2048 bytes long, after second limit is detached IP for fear that of an UDP something that connects and remote and storage number either of UDP links. The after second and fourth limit exist available as choice and used only with the understanding of UDP something that communicates accompanying the attendant. Since, the TCP IP connection happen settled, these limit are not secondhand. The command exist pursue physically by a string hold the URL bear the field names and principles give through the HTTP GET method. In this project, a series hold the URL bear API Key and the sensor value as the field and advantage exist give. The give field and its profit happen record on the cloud attendant. It exist influential to pass the API key in this place URL as one of the field-advantage so that do business the registered cloud help. The Air value calculated by sensor can immediately be watch carefully and written through the thingspeak IOT area form through the Wi-Fi module. The written information in visible form exist proved at the ThingSpeak platform the user needs to login the ThingSpeak platform from the registered account to view and monitor the sensor data. The Arduino sketch manages to read sensor data and send the AT

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

commands for connecting with the IOT platform.



Figure 4 & 5- ThingSpeak analysis

CONCLUSION

The Automatic Air first-rate control machine is a breakthrough to make contributions a strategy to the largest threat. The air tracking machine overcomes the trouble of the highly-polluted regions that is a prime difficulty. It helps the brand new generation and efficaciously helps the wholesome lifestyles concept. This machine has capabilities for the humans to screen the quantity of pollutants on their cell telephones the use of the application. The machine to screen the air of surroundings the use of Arduino microcontroller, IOT Technology is proposed to enhance first-rate of air. With the usage of IOT generation complements the method of tracking numerous factors of surroundings which includes air first-rate tracking difficulty proposed on this paper.

REFERENCES

I. Krishna, V. Siva, and S. Arun. "Embedded System Based Air Pollution Detection in Vehicles." (2015).

II. Piedrahita, R., et al. "The next generation of low-cost personal air quality sensors for quantitative exposure monitoring." Atmospheric Measurement Techniques 7.10 (2014): 3325.

III. Kim, Sunyoung, and Eric Paulos. "inAir: measuring and visualizing indoor air quality." Proceedings of the 11th international conference on Ubiquitous computing. ACM, 2009.

IV. Al-Dahoud, Ali, et al. "Monitoring Metropolitan City Air-quality Using Wireless Sensor Nodes based on ARDUINO and XBEE."

V. Rajkumar, M. Newlin, M. S. Sruthi, and V. Venkatesa Kumar.

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved

"IOT Based Smart System for Controlling Co2 Emission." (2017).

VI. Kim, Sunyoung, and Eric Paulos. "InAir: sharing indoor air quality measurements and visualizations." Proceedings of the SIGCHI Conference on Human Factors in Computing Systems. ACM, 2010..

Page 12-19 © MANTECH PUBLICATIONS 2021. All Rights Reserved